All Prices in Canadian Dollars.

VISA

and



Accepted for international orders.

See page 107 for ordering & shipping information.

Q COMPONENTS direct mail order


Online Catalog • PDF Version


PLEASE NOTE

A general 5% price increase is in effect on all items in this catalog.

To calculate your cost please multiply the advertised price by 1.05

Thank you.





OCTOBER 2001 · CATALOG 5.1

Loudspeakers and Hardware

Woofers, Mids and Tweeters
Musical Instrument and Pro Sound Drivers
Design Software
Commercial Sound Products
Small and Intercom Speakers
Extension Speakers
Capacitors, Resistors and Inductors
Ready Made Passive Crossovers
Audio Wire, Cable and Connectors
Speaker Cabinet Hardware













ORDERS ONLY: 1-800-363-6336

Help Line: 1-519-884-1140

Fax Line: 1-519-884-0193

Business Hours: Monday to Friday, 8 am to 5 pm EST

Q Components

638 Colby Drive, Waterloo, Ontario, Canada. N2V 1A2

TABLE OF CONTENTS Loudspeaker Design Software Fullrange speakers **Pro Sound Systems Tweeters** 10 mm dome5 - 6 Small speakers High power & Waterproof (Misco)70 **Commercial sound products** 5" & 8" commercial sound speakers73 - 76 Wall and corridor assemblies77 - 78, 82 Wooden wall baffles77 Line matching transformers78 Replacement diaphragms94 Flush mount back boxes81 - 82 Midranges 1-1/2" dome & 4" cone18 Horn21 Woofers (includes bass-mid types) 45 ohm intercom speakers88 P.A. horn drivers (Sammi)88 Sirens90 **Extension speakers** 2-way radio, cell, patio, hom, 70/25 volt91 - 93 Enclosure parts and accessories **Dual voice coil subwoofers** Replacement diaphragms94 Ready made crossovers96 4 ohm Car speakers **Passive Radiators** Gold plated audio connectors98 Vibration devices Shielded audio/video speakers Neutrik Speakons99 Tweeters41 - 42 Enclosure pole mounts100 Carpet covering (Ozite)100 Bullet, horn and piezo tweeters46 - 48 Grill frame attachment pins101 Midrange horns48 Grill cloth (Mellotone)102 Crossover parts Replacement diaphragms94 Pro midrange drivers Electrolytic capacitors103 Pro sound low frequency components Metallized polyester capacitors103 Genuine Eminence recone kits62 Heavy duty low DCR inductor coils104 **CONVERSION FACTORS** To convert: To: Multiply by: Eminence LEGEND series guitar speakers inches millimeters 25.4 millimeters inches 0.0394 cubic feet 28.3163 litres litres cubic feet 0.0353

DESIGN SOFTWARE

Ready for year 2000

Loudspeaker Design is an ART.

For Windows 95/98/NT

Free the artist in you with state-of-the-ART software from ##ARTISTECH.

Design speaker boxes with...

BassBox Pro



Visit us
on the web at
www.ht-audio.com
Our website includes
detailed information
about BassBox Pro,
Xover Pro and other
audio related stuff. We
also provide FAQ's
(frequently asked
questions) and
technical support
topics. Licensed users
can download free
updates and we provide
links to the known
websites of

driver manufactures.

Design crossovers with...

Xover Pro



BassBox Pro helps you quickly design many different types and shapes of speaker boxes. With its Design Wizard, advanced easy-to-use layout and on-line help it is a joy to use. As many as ten designs can be viewed at the same time.

Includes a MONSTER-size driver database with the parameters of thousands of drivers.



Handles many box types, including closed, vented, vented with active filter (B6), bandpass and passive radiator.



Accepts designs with multiple drivers, including isol aric designs. Both the mechanical and electrical configuration can be controlled.

Performance can be evaluated with 9 graphs, including 2 amplitude response graphs, max acoustic power, max electric power, cone displacement, vent velocity, impedance, phase and group delay.

Acoustic data can be imported for drivers and listening spaces. Both automotive and architectural environments are supported.

The response of a passive network can be entered or imported from Xover Pro and used to display the system response.

Includes both driver and passive radiator test procedures.

Create custom printouts with box drawings & parts lists.

Includes a beautiful, well illustrated 204 pg. manual.

BassBox Pro: \$178.50

Xover Pro helps you quickly design passive crossover networks, fow-pass, band-pass and high-pass filters, impedance equalization networks, notch filters and L-pads. Its straight forward layout and on-line help make it very easy to use.

Includes a MONSTER-size database with the parameters of thousands of drivers. Compatible with BassBox Pro.



Designs passive crossovers with a parallel topology. Each filter can be a different type and have a different slope. (1st-4th orders)

Individual component values can be changed and the effects viewed in the graphs.

Impedance equalization is available for the voice coil in uctive reactance and the driver/box resonance peaks.

Performance can be evaluated with 4 graphs including amplitude response, impedance, phase and group delay. Net response can be displayed in both the amplitude and impedance graphs.

The equivalent series resistance (ESR) of capacitors and DC resistance (DCR) of inductors can be estimated or entered.

Includes additional helpful tools like a Parallel-Series Value Calculator, Color Value Decoder and Notch Filter Designer.

The Notch Filter Designer can calculate two types of series notch filters and one type of parallel notch filter.

Create custom printouts with parts lists and schematics.

Includes a beautiful, well illustrated 169 page manual.

Xover Pro: \$137.50

Buy Both and save \$41.00!

Combo Pack: \$275.00



MCB10 PRO SOUND SYSTEM

McBride

MCB₁₀

NEW!



The McBride MCB10 is a high performance professional and commercial sound 2-way loudspeaker system designed for pro sound reinforcement, public address, night club, house of worship, disk jockey and arena applications.

Design Features Include:

- High efficiency drivers and low loss crossover make the most of every watt from your amplifier.
- · Superior projection and high speech intelligibility.
- · Built in pole / stand socket.
- · High output without distortion for accurate sound reproduction.
- Rigid design and high density materials prevent bass robbing enclosure vibrations.
- Dual 1/4" parallel inputs on recessed steel dish.
- Tough Texturelac finish and full size steel grill to withstand abuse and rough handling.

Power200 Wrms / 300 W peak Drivers:
HFPiezo Horn
LF
Enclosure StyleTrapezoid
Freq. Response60 Hz - 23 KHz
Sensitivity98 db (1 W / 1 m)
Dispersion40° Vert. x 100° Horz.
Crossover Point1.8 KHz
Impedance8 Ohms
Input Connectors2 x 1/4" J acks
Pole Socket Yes (1-3/8" diameter)
Dimensions:
Height20.625" (524 mm)
Width Front14.25" (362 mm)
Width Rear8.5" (216 mm)
Depth12.75" (324 mm)
Enclosure Matl3/4" MDF
Grill20 ga. Perf. Steel
FinishBlack Texturelac
Weight35.5 Lbs. (16.12 kg)
Each \$250.00

TWEETERS

TM010A1

Micro 10 mm neodymium polymer dome tweeter - 4 ohm

	29.5 mm
Impedance	4 ohm
Power	.25 W / 6 db / 6 KHz
Freq. Resp	6 KHz - 20 KHz
Total Wt	10 g
Fs	3000 Hz
Voice Coil Dia	10 mm
SPL	85 db
Depth	14 mm
Mounting	Post or Hidden
Min. X-over	6 KHz / 6 db
E I-	M44.55

Each \$14.55

Ferrofluid Cooled

TW010E1

10 mm polymer dome tweeter

Outside Dim	60 x 60 mm
Impedance	8 ohm
Power25	W / 6db / 6 KHz
Freq. Resp	6 KHz - 20 KHz
Magnet Wt	
Fs	3000 Hz
Voice Coil Dia	10 mm
SPL	90 db
Depth	14.4 mm
Baffle Opening	49 mm
Mtg. Cntr	60 mm BC x 4
Min. X-over	6 KHz / 6 db

Each \$9.25

Ferrofluid Cooled

10 mm titanium composite dome tweeter

Each

TW010I1



Ferrofluid Cooled

Outside Dia74 mm Impedance.....8 ohm Power25 W / 6db / 6 KHz Freq. Resp 6 KHz - 20 KHz Magnet Wt17.1 g Fs3000 Hz Voice Coil Dia.....10 mm SPL.....91 db Depth14.4 mm Baffle Opening......49 mm Mtg. Cntr...... 60 mm BC x 3 Min. X-over 6 KHz / 6 db

TM010A7



Micro 10 mm neodymium gold dome tweeter

Outside Dia29.5 mm Impedance.....8 ohm Power25 W / 6db / 6 KHz Freq. Resp6 KHz - 20 KHz Total Wt10 g Fs......3000 Hz Voice Coil Dia.....10 mm SPL......87 db Depth23 mm Mounting...... Post or Hidden Min. X-over6 KHz / 6 db

Each

Each

Ferrofluid Cooled

TW010F1



10 mm polymer dome tweeter

\$16.75

Outside Dia	74 mm
Impedance	8 ohm
Power2	5 W / 6db / 6 KHz
Freq. Resp	6 KHz - 22 KHz
Magnet Wt	
Fs	
Voice Coil Dia	10 mm
SPL	90 db
Depth	14.4 mm
Baffle Opening	
Mtg. Cntr	60 mm BC x 4
Min. X-over	

Ferrofluid Cooled

TW010I3



10 mm polymer dome tweeter

\$8.55

Outside Dia74 mm Freq. Resp 6 KHz - 22 KHz Magnet Wt17.1 g Fs3000 Hz Voice Coil Dia.....10 mm SPL.....91 db Depth14.4 mm Baffle Opening......49 mm Mtg. Cntr.....60 mm BC x 3 Min. X-over6 KHz / 6 db

Each \$12.26

Ferrofluid Cooled

\$13.85

(I) PIONEER®

FB26KP34-51D



10 mm polymer dome tweeter

Outside Dia	73 mm
Impedance	6 ohm
Power25	W / 6 db / 6 KHz
Freq. Resp	6 KHz - 20 KHz
Magnet Wt	0.6 oz
Fs	n/a
Voice Coil Dia	10 mm
SPL	90 db
Depth	20 mm
Baffle Opening	48 mm
Mtg. Cntr	60 mm BC x 3
Min. X-over	6 KHz / 6 db

Each

TW014B5



14 mm polymer dome tweeter - 4 ohm

Outside Dia	49.5 mm
Impedance	4 ohm
Power45	W / 12 db / 4.8 KHz
Freq. Resp	4.1 KHz - 20 KHz
Magnet Wt	53 g
Fs	2050 Hz
Voice Coil Dia	14 mm
SPL	94 db
Depth	24.3 mm
	n/a
Mounting	Post or Hidden
Min. X-over	4.1 KHz / 12 db

\$19.74

Ferrofluid Cooled

Each

Ferrofluid Cooled

TW014F1



Ferrofluid Cooled

14 mm polymer dome tweeter

\$8.64

Outside Dia
Min. X-over4.1 KHz / 12 db

PHILIPS AD00402T8FF



Ferrofluid Cooled

E	M40.0 E
Min. X-over	4.1 KHz / 12 db
Mtg. Cntr	
Baffle Opening	
Depth	19.5 mm
SPL	91 db
Voice Coil Dia	
Fs	
Magnet Wt	
Freq. Resp	.4.1 KHz - 20 KHz
Power45 W	
Impedance	
Outside Dia	
Outcide Dia	71 mm

Each \$13.85

18 mm soft poly

Outside Dia120 mm

Freq. Resp4 KHz - 20 KHz

Total Wt390 g

Fs2000 Hz Voice Coil Dia.....18 mm

SPL.....91 db

Depth21.2 mm

Baffle Opening.....86 mm

Mtg. Cntr.....102 mm BC x 4

Min. X-over4 KHz / 12 db

\$24.54

Each

dome tweeter

PHILIPS

AD00403/T6FF



18 mm titanium dome tweeter

Outside Dim90 x 120 mm Freq. Resp2.2 KHz - 20 KHz Total Wt470 g Voice Coil Dia.....18 mm SPL.....89 db Depth32.7 mm Baffle Opening......78 x 85 mm Mtg. Cntr......66 x 106 mm x 4 Min. X-over2.2 KHz / 12 db

Each \$35.06

Ferrofluid Cooled

TWEETERS

PHILIPS

AD00973/T8FF

Shielded 18 mm neodymium mag. polygrid dome tweeter



Outside Dim40 x 60 mm Impedance8 ohm
Power 70 W / 12 db / 4.5 KHz
Freq. Resp2.8 KHz - 20 KHz
Total Wt38 g
Fsn/a
Voice Coil Dia18 mm
SPL88 db
Depth12 mm
Baffle Opening40 mm
Mtg. Cntr50 mm BC x 2
Min. X-over2.8 KHz / 12 db

Each \$26.65

 Outside Dim
 91 x 91 mm

 Impedance
 8 ohm

 Power
 50 W / 12 db / 5 KHz

 Freq. Resp
 2 KHz - 20 KHz

 Magnet Wt
 4.7 oz

 Fs
 n/a

 Voice Coil Dia
 19 mm

 SPL
 90 db

 Depth
 28 mm

 Baffle Opening
 69 mm

 Mtg. Cntr
 65 x 65 mm x 4

 Min. X-over
 2 KHz / 12 db

3/4" textile

dome tweeter

Ferrofluid Cooled

∰ PIONEER°

FADD64-58F



Ferrofluid Cooled

Each \$19.63

Polydax 1" pure titanium dome tweeter

DTI-01



Outside Dia114.3 mm
Impedance8 ohm
Power55 W / 12 db / 2.5 KHz
Freq. Resp2.4 KHz - 27 KHz
Magnet Wt240 g
Fs1700 Hz
Voice Coil Dia25 mm
SPL94 db
Depth22.8 mm
Baffle Opening73 mm
Mtg. Cntr103.2 mm BC x 4
Min. X-over2.4 KHz / 12 db
Each \$42.76

(!) PIONEER®

ADD64-56F



3/4" soft dome tweeter

Outside Dia	
Impedance	8 ohm
Power45	W / 12 db / 5 KHz
Freq. Resp	2 KHz - 20 KHz
Magnet Wt	
Fs	n/a
Voice Coil Dia	19 mm
SPL	
Depth	30 mm
Baffle Opening	
Mtg. Cntr	82.5 mm BC x 4
Min. X-over	2 KHz / 12 db
Each	\$17.14

Ferrofluid Cooled

∰ PIONEER®

FBDD69-51F



3/4" horn loaded dome tweeter

Outside Dia	8 ohm V / 12 db / 5 KHz2 KHz - 20 KHz2.4 oz
Mtg. Cntr Min. X-over	91 mm BC x 4
Each	\$15.49

Ferrofluid Cooled

<u>AUDAX</u>

TM025C1



Ferrofluid Cooled

1" shielded neodymium mag. soft dome tweeter

 $\frac{2}{1}$ mag. soft of

Each \$28.40

1" shielded neodymium mag. soft dome tweeter

TM025F1



Ferrofluid Cooled

Impedance Power70 Freq. Resp Magnet Wt Magnet Matl Voice Coil Dia Fs Xmax SPL Depth Baffle Opening .	70 mm8 ohm W / 12 db / 2.8 KHz2.5 KHz - 20 KHz
Mounting	62 mm BC x 4 2.5 KHz / 12 db

Outside Dia	70 mm
Impedance	8 ohm
	/ 12 db / 2.8 KHz
Freq. Resp	.2.5 KHz - 20 KHz
	54 g
Magnet Matl	Neodymium
	25 mm
Fs	1250 Hz
	0.05 mm
SPL	92 db
Depth	32.5 mm
Baffle Opening	51 mm
Mounting	62 mm BC x 4
Min. X-over	2.5 KHz / 12 db

Each \$31.69

Ferrofluid Cooled

1" shielded neodymium mag. soft dome tweeter

TM025F13



1" shielded neodymium mag. soft dome tweeter

TM025F15



Ferrofluid Cooled

Outside Dim54 x 70 mm

Impedance8 ohm	
Power70 W / 12 db / 2.8 KHz	
Freq. Resp2.8 KHz - 20 KHz	
Magnet Wt64 g	
Magnet MatlNeodymium	
Voice Coil Dia25 mm	
Fs1500 Hz	
Xmax0.05 mm	
SPL94 db	
Depth32.5 mm	
Baffle Opening51 mm	
Mounting62 mm BC x 4	
Min. X-over2.8 KHz / 12 db	

Each \$34.80

Ferrofl

1" shielded neodymium mag. titanium dome tweeter

TM025F7



uid Cooled	Cooled	uid
------------	--------	-----

	70 mm
Impedance	8 ohm
	/ 12 db / 2.7 KHz
Freq. Resp	.2.7 KHz - 20 KHz
Magnet Wt	54 g
	Neodymium
Voice Coil Dia	25 mm
Fs	1400 Hz
Xmax	0.05 mm
SPL	91 db
Depth	32.5 mm
Baffle Opening	51 mm
Mounting	62 mm BC x 4
	2.7 KHz / 12 db
Each	\$34.01
Lacii	Ψυ4.υ ι

TM025F9



Ferrofluid Cooled

1" shielded neodymium mag. soft dome tweeter	
Outside Dim	54 x 70 mm

Outside Dim	54 x 70 mm
Impedance	8 ohm
Power70 W	/ 12 db / 2.7 KHz
Freq. Resp	2.4 Hz - 20 KHz
Magnet Wt	
Magnet Matl	
Voice Coil Dia	
Fs	
Xmax	
SPL	
Depth	
Baffle Opening	
Mounting	
Min. X-over	

Each \$31.69

TW025A0



1" soft dome tweeter

Impedance.....8 ohm Power......55 W / 12 db / 2.5 KHz Freq. Resp1.8 KHz - 20 KHz Magnet Wt240 g Voice Coil Dia.....25 mm SPL.....90 db Depth23.5 mm Baffle Opening......75 mm

Outside Dia100 mm

Mtg. Cntr.....86 mm BC x 4 Min. X-over1.8 KHz / 12 db

Each \$32.37



TWEETERS

<u> AUDAX</u>

1" soft dome tweeter

TW025L0



Outside Dim	
Impedance	
Power55 W	
Freq. Resp	1.8 KHz - 20 KHz
Magnet Wt	
Fs	900 Hz
Voice Coil Dia	
SPL	90 db
Depth	23.5 mm
Baffle Opening	75 mm
Mtg. Cntr	60 x 100 mm x 4
Min. X-over	1.8 KHz / 12 db

Each \$33.73

AUDAX

1" soft dome tweeter

TW025M1



Outside Dia Impedance70 W Freq. Resp	8 ohm / 12 db / 2.5 KHz .2.4 KHz - 20 KHz
Magnet Wt	240 g
Fs	1200 Hz
Voice Coil Dia	25 mm
SPL	92 db
Depth	23.5 mm
Baffle Opening	75 mm
Mtg. Cntr	86 mm BC x 4
Min. X-over	

Each

\$34.01

Ferrofluid Cooled

McBride

1" soft dome tweeter

DT163T8



Outside Dia	93.7 mm
Impedance	8ohm
	/ / 12 db / 2.8 KHz
Freq. Resp	2.8 KHz - 20 KHz
Magnet Wt	5.6 oz
Voice Coil Dia	25 mm
	1400 Hz
	7.0 ohms
	93 db
Depth	25 mm
	67 mm
	85 mm BC x 3
Min. X-over	2.8 KHz / 12 db

Each \$16.58

MG

DMT-700



1" Polycarbonate dome tweeter

Each \$16.79



PHILIPS

1" soft dome tweeter

AD0141T8



Outside Dia	94.2 mm
Impedance	8 ohm
Power100 \	N / 12 db / 5 KHz
Freq. Resp	2.9 Hz - 20 KHz
Magnet Wt	100 g
Voice Coil Dia	25 mm
Fs	
Re	6.3 ohm
SPL	94 db
Depth	24.5 mm
Baffle Opening	62 mm
Mounting	87 mm BC x 3
Min. X-over	

Each \$17.81

PHILIPS

AD11400T8



Impedance
Freq. Resp 3 KHz - 20 KHz
Total Wt 290 g
10to1 11t 111111111111111111111111111111
Fs1500 Hz
Voice Coil Dia25 mm
SPL91 db
Depth24.7 mm
Baffle Opening74 mm
Mtg. Cntr64 x 64 mm x 4
Min. X-over3 KHz / 12 db

1" soft dome tweeter

Each \$17.51

PHILIPS

1" soft dome tweeter

Each

Each

AD11600T8



Outside Dim	
Impedance	
Power 100 W / 12	
Freq. Resp2.6 KI	Hz - 20 KHz
Total Wt	570 g
Fs	1300 Hz
Voice Coil Dia	25 mm
SPL	
Depth	30.6 mm
Baffle Opening	
Mtg. Cntr76 x	76 mm x 4
Min. X-over2.6	KHz / 12 db

\$19.50



1" Polygrid dome tweeter

Outside Dim	95 x 95 mm
Impedance	8 ohm
Power 100 W /	12 db / 2.5 KHz
Freq. Resp	2.5 KHz - 20 KHz
Total Wt	560 g
Fs	n/a
Voice Coil Dia	25 mm
SPL	
Depth	27.5 mm
Baffle Opening	85 mm
Mtg. Cntr	
Min. X-over	

Each \$28.04

Ferrofluid Cooled

PHILIPS

AD11810T8

PHILIPS

AD11610T8



1" polycarbonate dome tweeter

96 x 96 mm
8 ohm
/ 12 db / 5 KHz
2 KHz - 20 KHz
570 g
1600 Hz
25 mm
95 db
30.6 mm
86 mm
76 x 76 mm x 4
3.2 KHz / 12 db

1" polycarbonate dome tweeter

Each \$18.50

\$20.25

(!) PIONEER

1" soft dome tweeter

FBDE75-52F



Outside Dim	8 ohm V / 12 db / 5 KHz3 KHz - 20 KHz6.3 oz/a
Mtg. Cntr Min. X-over	110 mm BC x 4
Each	\$18.73

(I) PIONEER®

FDDE59-51F



1" titanium dome tweeter

	100 mm
Impedance	8 ohm
	W / 12 db / 5 KHz
Freq. Resp	1.8 KHz - 20 KHz
Magnet Wt	4.1 oz
Voice Coil Dia	25 mm
	900 Hz
Re	6.6 ohms
SPL	90 db
Depth	22.8 mm
Baffle Opening	61 mm
	86 mm BC x 4
	1.8 KHz / 12 db

Each \$28.26

Ferrofluid Cooled

(I) PIONEER®

FGDE70-51F



1" titanium dome tweeter

Outside Dia	m Iz Iz Iz Iz Ib m m
Mtg. Cntr91 mm BC x Min. X-over3 KHz / 12 d	

\$29.15

Ferrofluid Cooled

Sammi®

Ferrofluid Cooled

ADT25B60



1" aluminum dome tweeter

Outside Dim11	3.5 x 113.5 mm
Impedance	8 ohm
Power75 W	/ 12 db / 5 KHz
Freq. Resp	.3 KHz - 20 KHz
Magnet Wt	13 oz
Voice Coil Dia	25 mm
Fs	1500 Hz
SPL	93 db
Depth	
Baffle Opening	86 mm
Mounting	120 mm BC x 4
Min. X-over	
Each	\$15.25

DT25B40



1" soft dome tweeter

Each

Each

Outside Dia		
Power		
Freq. Resp 2 KHz - 20 KH Magnet Wt 8 c Fs 1000 H Voice Coil Dia 25 mr SPL 91 d Depth 27 mr Baffle Opening 71 mr Mtg. Cntr 95 mm BC x	Impedance	8 ohm
Magnet Wt	Power50	W / 12 db / 5 KHz
Fs	Freq. Resp	2 KHz - 20 KHz
Voice Coil Dia	Magnet Wt	8 oz
SPL 91 d Depth 27 mr Baffle Opening 71 mr Mtg. Cntr 95 mm BC x	Fs	1000 Hz
Depth27 mi Baffle Opening71 mi Mtg. Cntr95 mm BC x	Voice Coil Dia	25 mm
Baffle Opening71 mr Mtg. Cntr95 mm BC x	SPL	91 db
Mtg. Cntr95 mm BC x	Depth	27 mm
Mtg. Cntr95 mm BC x	Baffle Opening	71 mm
Min. X-over2 KHz / 12 d		
	Min. X-over	2 KHz / 12 db

Sammi®

TDT25B50

1" titanium dome tweeter

Outside Dim79.5 x 101.5 mm Impedance.....8 ohm

	Power	50 W / 12 db/ 5 KHz
	Freq. Resp	3 KHz - 20 KHz
_	Magnet Wt	8.8 oz
	Voice Coil Dia	25 mm
	Fs	1500 Hz
-	SPL	94 db
-	Depth	33 mm
	Baffle Opening	73 x 80 mm
	Mounting	64 x 86 mm x 4
	Min. Xover	3 KHz / 12 db
	Cook	01C EO

\$20.98

TWEETERS

AUDAX

TW034X0



34 mm soft dome tweeter

Outside Dia	
Min. X-over Each	A== = 4

PHILIPS

AD11700RT8



Circular isophase (ribbon) tweeter

	95 x 95 mm
	8 ohm
	0 W /12 db / 4.7 KHz
	4.7 KHz - 20 KHz
Total Wt	625 g
Fs	n/a
	Non-inductive
SPL	92 db
Depth	25.5 mm
	j83 mm
Mtg. Cntr	72 x 72 mm x 4
Min. X-over	4.7 KHz / 12 db
Fach	\$123.89

FB45DP70-06F



1-3/4" phenolic ring cone tweeter

Outside Dia	
Each	\$14.24

Ferrofluid Cooled

$\textcircled{PIONEER}^{\circ}$

FD66AP45-13F



2-1/2" paper cone tweeter

Outside Dia79	mm
Impedance8	ohm
Power60 W / 12 db / 5	KHz
Freq. Resp2 KHz - 20	KHz
Magnet Wt	
Fs	n/a
Voice Coil Dia13	mm
SPL93	3 db
Depth25	mm
Baffle Opening64	mm
Mtg. Cntr76 mm BC	
Min. X-over2 KHz / 12	
Each \$7.5	22

Ferrofluid Cooled

∰ PIONEER®

FP66AP45-54F



2-1/2" paper cone tweeter

Jutside Dim	/3 x /3 mm
mpedance	8 ohm
ower60 V	V / 12 db / 5 KHz
req. Resp	2 KHz - 20 KHz
Magnet Wt	2 oz
s	
/oice Coil Dia	
SPL	93 db
Depth	32 mm
Baffle Opening	64 mm
۹tg. Cntr	79 mm BC x 4
Min. X-over	2 KHz / 12 db
Each	\$6.49

Ferrofluid Cooled

TWEETERS

(I) PIONEER®

FC77AP45-21F



3" paper cone tweeter

Outside Dia	102 mm
Impedance	8 ohm
Power60 W	/ 12 db / 5 KHz
Freq. Resp	
Magnet Wt	2 oz
Fs	n/a
Voice Coil Dia	13 mm
SPL	92 db
Depth	29 mm
Baffle Opening	78 mm
Mtg. Cntr	91 mm BC x 4
Min. X-over	2 KHz / 12 db
Each	\$7.22

MG

BT-1



98 mm round bullet tweeter

Outside Dim	97.8 mm
Impedance	8 ohm
Power80 W /	
Freq. Resp	2 KHz - 20 KHz
Magnet Wt	
Voice Coil Dia	25 mm
Fs	1000 Hz
Re	6.4 ohm
SPL	102 db
Depth	66.3 mm
Baffle Opening	72 mm
Mounting	85.7 mm BC x 4
Min. Xover	
Each	\$24.68

Ferrofluid Cooled

Ferrofluid Cooled

MG

BT-2



87 mm square bullet tweeter

Outside Dim87 x 87 mm
Impedance8 ohm
Power80 W / 12 db / 2.5 KHz
Freq. Resp2 KHz - 20 KHz
Magnet Wt6 oz
Voice Coil Dia25 mm
Fs1000 Hz
Re6.4 ohm
SPL102 db
Depth66 mm
Baffle Opening72mm
Mounting84 to 101 mm BC x 4
Min. Xover2 KHz / 12 db

Ferrofluid Cooled

\$24.68

Each

∰ PIONEER°

AHE60-51F



3-1/2" exponential horn tweeter

Outside Dim	89 x 89 mm
Impedance	8 ohm
Power50 V	V / 12 db / 5 KHz
Freq. Resp	2 KHz - 20 KHz
Magnet Wt	2.9 oz
Fs	n/a
Voice Coil Dia	
SPL	100 db
Depth	65 mm
Baffle Opening	
Mtg. Cntr	
Min. X-over	2 KHz / 12 db
Each	\$15.86

Ferrofluid Cooled

Sammi® HF200A



3" pro bullet tweeter

Outside Dim	
Each	\$73.27

Sammi® HF250



3" pro slot tweeter

COMPONENTS direct mail order

Sammi® 4-1/4" x 6-1/2" bi-radial bullet tweeter

HF200BR



Outside Dim	
Impedance	8 ohm
	10 Wrms @ 5 KHz
Freq. Resp	.2.5 KHz - 20 KHz
Magnet Wt	10 oz
Voice Coil Dia	38 mm
SPL	107 db
Dispersion	60 ^o H x 30 ^o V
Depth	
Baffle Opening	91 x 106 mm
	.92 x 145 mm x 4
	2.5 KHz / 12 db
Each	\$73.27

FOSTER

025N47



3-1/2" pro bullet tweeter

Outside Dim88.9 x 88.9 mm Impedance	
Each \$47.33	

FOSTER



4" pro horn tweeter

025N27

Outside Dim	110 x 110 mm
Impedance	8 ohm
Power120	W / 12 db / 4 KHz
Freq. Resp	4 KHz - 15 KHz
	8 oz
Voice Coil Dia	25 mm
Fs	2 KHz
	110 db
Depth	116.7 mm
Baffle Opening	90 mm
	150 mm BC x 4
Min. Xover	4 KHz / 12 db
Each	\$46.34

FOSTER

025N30



4" x 10" pro horn tweeter

FOSTER

H025N08



6" x 7" pro horn tweeter

Outside Dim156 x 195 mm	
Impedance8 ohm	
Power120 W / 12 db / 5 KHz	
Freq. Resp 3 KHz - 20 KHz	
Magnet Wt11 oz	
Voice Coil Dia25 mm	
Fs1.5 KHz	
Re6.8 ohms	
SPL106 db	
Depth130 mm	
Baffle Opening123 x 166 mm	
Mtg. Cntr80 x 180 mm x 8	
Min. Xover3 KHz / 12 db	

Each \$56.76

MOTOROLA PIEZO TWEETERS

MOTOROLA

KSN1139A



1-1/2" cone tweeter

51 x 51 mm
at low frequency
50 W
6 KHz - 24 KHz
ceramic bimorph
91 db
13 mm
46 mm
60 mm BC x 4

MOTOROLA

KSN1078A



2" cone tweeter

Each \$5.27

MOTOROLA

KSN1193A



2" surface mount tweeter

\$4.93

	51 mm n at low frequency
Power	50 W
Freq. Resp	6 KHz - 30 KHz
Voice Coil	ceramic bimorph
SPL	88 db
	21 mm
Baffle Opening	Flush mount
Mtg. Cntr	36.5 mm BC x 2
- ·	A47.07

Pair \$17.97

MOTOROLA

KSN1036A



2-1/2" cone tweeter with flat screen

95.3 mm
at low frequency
75 W
3 KHz - 40 KHz
.ceramic bimorph
90 db
19.1 mm
64 mm
85.7 mm BC x 4

Each \$8.07

MOTOROLA

KSN1001A



3" recessed flange super horn tweeter

Outside Dim	84.8 x 84.8 mm
Impedancehigh	n at low frequency
Power	75 W
Freq. Resp	4 KHz - 27 KHz
Voice Coil	ceramic bimorph
SPL	92 db
Recess Depth	12.5 mm
Total Depth	74 mm
Baffle Opening	79 mm
Mtg. Cntr	100 mm BC x 4

Each \$8.79

MOTOROLA

KSN1005A



3" super horn tweeter

Outside Dim........84.8 x 84.8 mm Impedance ...high at low frequency Power75 W Freq. Resp4 KHz - 27 KHz Voice Coil........ceramic bimorph SPL94 db Depth74 mm Baffle Opening79 mm Mtg. Cntr100 mm BC x 4

Each \$7.26

MOTOROLA PIEZO TWEETERS

MOTOROLA

KSN1167A



2-1/2" exponential bullet tweeter

Outside Dim	87.3 x 87.3 mm
Impedancehigh	at low frequency
Power	
Freq. Resp	.3.8 KHz - 30 KHz
Voice Coil	ceramic bimorph
SPL	92 db
Depth	50 mm
Baffle Opening	73 mm
Mtg. Cntr70	0.8 x 70.8 mm x 4

Each \$11.31

MOTOROLA

KSN1038A



3-3/4" exponential horn tweeter

Outside Dia	95.3 mm
Impedancehigh	n at low frequency
Power	75 W
Freq. Resp	4 KHz - 27 KHz
Voice Coil	ceramic bimorph
SPL	92 db
Depth	60.3 mm
Baffle Opening	71.3 mm
	85.7 mm BC x 4

Each \$9.49

MOTOROLA

KSN1133A



Cellular horn tweeter

Impedancehigh Power Freq. Resp Voice Coil SPL Depth Baffle Opening	89 x 95 mm n at low frequency 75 W 4 KHz - 25 KHz ceramic bimorph 92 db 58 mm 55 x 75 mm 76 x 83 mm x 4
Each	\$11.70

MOTOROLA KSN1148A



1-1/2" x 3-1/4" slot tweeter

Outside Dim67.7 x 95.3 mm
Impedancehigh at low frequency
Power75 W
Freq. Resp 4 K Hz - 25 KHz
Voice Coilceramic bimorph
SPL90 db
Depth70 mm
Baffle Opening*44 x 89 mm
Mtg. Cntr57.8 x 64 mm x 4
-

Each \$8.40

*Careful clearancing in center of baffle opening required to mount tweeter.

MOTOROLA

KSN1165A



3" Powerline bullet tweeter

\$15.32

Outside Dim	110 x 110 mm
Impedancehigh	at low frequency
PowerP	rotected to 400 W
Freq. Resp	1.8 KHz - 30 KHz
	ceramic bimorph
SPL	92 db
Depth	74 mm
Baffle Opening	74 mm
	91 x 91 mm x 4
_	

Each

MOTOROLA KSN1130A



Wide dispersion lens horn tweeter

Each \$13.30

MOTOROLA PIEZO TWEETERS

MOTOROLA

KSN1177A



High output twin drive horn tweeter

Outside Dim	95 x 162 mm
Impedancehigh	at low frequency
Power	100 W
Freq. Resp	.3.8 KHz - 25 KHz
Voice Coil2 x	ceramic bimorph
SPL	99 db
Depth	95 mm
Baffle Opening	55 x 122 mm
Mtg. Cntr	.81 x 145 mm x 6

\$18.91 Each

MOTOROLA

KSN1016B



1-3/4" x 4-3/4" horn tweeter

Outside Dim......67.5 x 145 mm Impedance...high at low frequency Power75 W Freq. Resp3 KHz - 40 KHz Voice Coilceramic bimorph SPL.....92 db Depth53 mm Baffle Opening......51 x 109 mm Mtg. Cntr.....54 x 132 mm x 4

Each \$8.50

MOTOROLA

KSN1141B KSN1025B



2" x 6" Powerline horn tweeter

Outside Dim	.79.4 x 187.3 mm
Impedancehigh	at low frequency
Powerp	rotected to 400 W
	.1.8 KHz - 30 KHz
Voice Coil	.ceramic bimorph
SPL	92 db
Depth	108 mm
Baffle Opening	55 x 148 mm
Mtg. Cntr63.	5 x 171.5 mm x 6

Each \$16.57

Also available: KSN1025B

The KSN1025B is the non-Powerline version of the KSN1141B. Specs are the same except for power rating of 75 W.

Each \$11.62

MOTOROLA KSN1142A



1" throat Powerline compression driver

Outside Dia64 mm
Length71 mm
Impedancehigh at low frequency
Powerprotected to 400 W
Freq. Resp1.8 KHz - 30 KHz
Voice Coilceramic bimorph
SPL92 db
Mounting1-3/8" x 18 UNEF

\$16.40 Each

MOTOROLA KSN1197A



1" throat compression driver

	53.5 mm
Impedancehigh	n at low frequency
Power	75 W
Freq. Resp	4 KHz - 27 KHz
Voice Coil	ceramic bimorph
SPL	90 db
Depth	53 mm
Mounting	.1-3/8" x 18 UNEF
Each	\$7.45

MOTOROLA

KSN1188A



1" throat Powerline compression driver

Outside Dia	97.8 mm
Length	77.8 mm
Impedancehigh	at low frequency
Powerp	rotected to 400 W
Freq. Resp	800 Hz - 20 KHz
	.ceramic bimorph
SPL	93 db
Mounting	.1-3/8" x 18 UNEF

Each \$37.66

MIDRANGES

∰ PIONEER®

FADF87-53F



1-1/2" soft dome midrange

Outside Dim	8 ohm // 12 db / 2 KHz L.2 KHz - 15 KHz7.2 oz/a38 mm92 db26 mm94 mm
Mtg. Cntr1	
_	
Each	\$28.64

Ferrofluid Cooled

∰ PIONEER°

FD10DP61-06F



4" paper cone midrange

Outside Dia 131 Impedance 8 c Power 75 W / 12 db / 2 Freq. Resp 700 Hz - 7 Magnet Wt 3. Fs 20 Voice Coil Dia 20 SPL 92 Depth 52 Baffle Opening 104 Mtg. Cntr 119 mm BC	ohm KHz KHz 7 oz .n/a mm 2 db mm mm
Each \$11.9	

Ferrofluid Cooled

Sammi® SR100A50-4



4" cast frame pro midrange - 4 ohm

-
Outside Dia119 mm
Impedance4 ohm
Power75 W
Freq. Resp190 Hz - 17 KHz
Magnet Wt13 oz
Fs190
Qts0.95
Qes1.21
Qms4.41
Vas1.0 litres
Voice Coil Dia30 mm
SPL94 db
Depth47 mm
Baffle Opening108 mm
Mtg. Cntr119 mm BC x 4
Each \$33.30

<u> AUDAX</u>

HM100Z0



Vented Voice Coil

4" HD-A cone mid with phase plug

Outside Dim	110 x 110 mm
Impedance	8 ohm
Power	
Freq. Resp	250 Hz - 9 KHz
Magnet Wt	350 g
Fs	250 Hz
Qts	0.81
Qes	0.99
Qms	4.26
Vas	
Xmax	1.25 mm
Voice Coil Dia	25 mm
SPL	
Depth	52 mm
Baffle Opening	95 mm
Mtg. Cntr1	13.6 mm BC x 4
Each	\$81.86

(I) PIONEER®

FE10BP45-25F



4" paper cone midrange

Outside Dia	131 mm
Impedance	8 ohm
Power60	W / 12 db / 2 KHz
Freq. Resp	750 Hz - 10 KHz
	2 0z
	n/a
Voice Coil Dia	14.3 mm
SPL	90 db
Depth	32 mm
Baffle Opening	104 mm
	119 mm BC x 4
Each	\$8.64

Ferrofluid Cooled

∰ PIONEER°

B11EC80-02F



4-1/2" paper cone midrange

	134.5 mm
mpedance	8 ohm
ower80	W / 12 db / 2 KHz
req. Resp	320 Hz - 6 KHz
4agnet Wt	7 oz
	n/a
oice Coil Dia	25 mm
	94 db
Depth	75 mm
Baffle Opening	108 mm
Atg. Cntr	128 mm BC x 4
	MOF 70

Each \$25.78

Ferrofluid Cooled

MIDRANGES

(!) PIONEER®

FB11EC14-51F



Ferrofluid Cooled

McBride

IMAGE MID

midrange

Outside Dia	135 mm
Impedance	8 ohm
Power75	W / 12 db / 2 KHz
Freq. Resp	500 Hz - 14 KHz
Magnet Wt	14 oz
Fs	n/a
Voice Coil Dia	25 mm
SPL	90 db
Depth	61 mm
Baffle Opening	106 mm
	119 mm BC x 4
_	

5" paper cone midrange

Outside Dia128 mm

	impedance	0 011111
	Power100 \	N / 12 db / 500 Hz
	Freq. Resp	500 Hz - 9 KHz
		10 oz
	Fs	350 Hz
	Voice Coil Dia	25 mm
	SPL	92 db
	Depth	47 mm
7	Baffle Opening	108 mm
	Mtg. Cntr	120 mm BC x 4
	Pair	\$58.38

4-1/2" paper cone

Outside Dia	135 mm
Impedance	8 ohm
Power75 \	N / 12 db / 2 KHz
Freq. Resp	500 Hz - 14 KHz
Magnet Wt	
Fs	n/a
Voice Coil Dia	25 mm
SPL	90 db
Depth	61 mm
Baffle Opening	106 mm
Mtg. Cntr	
Each	\$27.40

McBride

ACC-5M



5" poly cone midrange

Outside Dia	128 mm
Impedance	8 ohm
Power100 W	
Freq. Resp	500 Hz - 9 KHz
Magnet Wt	
Fs	350 Hz
Voice Coil Dia	25 mm
SPL	92 db
Depth	
Baffle Opening	108 mm
Mtg. Cntr	
Pair	\$61.96

∰ PIONEER®

FD12EC65-01F



Ferrofluid Cooled

5" paper cone . midrange

	137 x 137 mm
	8 ohm
	W / 12 db / 2 KHz
	600 Hz - 7 KHz
Magnet Wt	4.6 oz
Fs	n/a
Voice Coil Dia	25 mm
	90 db
Depth	52 mm
Baffle Opening	104 mm
Mtg. Cntr	123 mm BC x 4
Each	\$18.02

(I) PIONEER®

FW12ER14-51F



Ferrofluid Cooled

5" cast frame black poly cone midrange

Outside Dim	130 x 130 mm
Impedance	8 ohm
Power100 V	V / 12 db / 1 KHz
Freq. Resp	500 Hz - 9 KHz
Magnet Wt	
Fs	500 Hz
Re	
Qts	1.207
Qes	2.832
Qms	2.104
Voice Coil Dia	
SPL	90.3 db
Depth	56 mm
Baffle Opening	
Mounting	
3	

Each \$37.84

COMPONENTS direct mail order

∰ PIONEER®

FB12EU14-51F



6" high power poly cone midrange

Outside Dia	8 ohm / 12 db / 2 KHz 500 Hz - 6 KHz14 oz
Mtg. Cntr13	7.5 mm BC x 4
Each	\$31.18

Ferrofluid Cooled

<u> AUDAX</u>

PR170Z0



6-1/2" cast frame HD-A cone midrange

Outside Dia	190 mm
Impedance	
Power	100 W
Freq. Resp	185 Hz - 8 KHz
Magnet Wt	
Fs	
Re	
Qts	
Qes	
Qms	
Vas	3.4 litres
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mounting	
riouning	171.0 HIIII DC AT

<u> AUDAX</u>

HT210T0



8" paper cone pro midrange

\$129.60

Each

Each

209 mm
8 ohm
80 W
170 Hz - 6 KHz
880 g
170 Hz
6.5 ohm
0.79
1.14
2.60
7.1 litres
40 mm
1.5 mm
99 db
91 mm
185 mm
.199 mm BC x 4

AUDAX

PR170M0



6-1/2" cast frame paper cone pro mid

Outside Dia	
Impedance	8 ohm
Power	
Freq. Resp	117 Hz - 8 KHz
Magnet Wt	880 g
Fs	
Re	6.2 ohm
Qts	0.51
Qes	0.61
Qms	3.16
Vas	5.52 litres
Xmax	0.50 mm
Voice Coil Dia	
SPL	100 db
Depth	76 mm
Baffle Opening	
Mtg. Cntr1	

Sammi®

AW165A100



Vented Voice Coil

6-1/2" cast frame paper cone pro midrange

\$112.27

\$70.61

Each

Outside Dia	
Impedance	8 ohm
Power	
Freq. Resp77	Hz - 10 KHz
Magnet Wt	
Fs	77 Hz
Qts	0.47
Qes	
Qms	2.65
Vas	
Voice Coil Dia	40 mm
SPL	
Depth	65.5 mm
Baffle Opening	
Mtg. Cntr150	

EMINENCE 8" pro sound midrange - 100 W

Each

utside Dia	203.2 mm
mpedance	
ower	
req. Resp	
lagnet Wt	
s	
e	
e	0.37 mH
ts	
es	
ms	
as	
max	
oice Coil Dia	38 mm
PL	
epth	82 mm
affle Opening	
lounting	196.9 mm BC x 4
3	

Each \$49.10

\$73.22



MIDRANGE HORNS

MG HM-100

4" x 10-1/2" exponential midrange horn



Outside Dim
Freq. Resp1 KHz - 11 KHz Magnet Wt10 oz Fsn/a
Voice Coil Dia25 mm SPL104 db
Depth185 mm Baffle Opening81 x 242 mm Mtg. Cntr93 x 256 mm x 10

\$46.87

COMPONENTS direct mail order

3" rubber edge paper cone woofer - full range

HT080G0



Outside Dia	
Baffle Opening Mtg. Cntr	79 mm
Each	\$31.27

0M080TH



Outside Dia	96 mm
Impedance	8 ohm
Power	20 W
Freq. Resp	
Magnet Wt	
Fs	
Re	5.9 ohm
Qes	
Qms	
Vas	
Xmax	1.5 mm
Voice Coil Dia	
SPL	86 db
Depth	50 mm
Baffle Opening	
Mtg. Cntr	84 mm BC x 4
Each	\$27.37

3" foam edge paper cone woofer - full range

4" cast frame rubber edge carbon fiber cone bass-mid

HM100C0



Vented Voice Coil

Outside Dim	
Impedance	8 onm
Power	40 W
Freq. Resp	54 Hz - 11 KHz
Magnet Wt	
Fs	54 Hz
Re	6.4 ohm
Qts	
Qes	
Qms	
Vas	6.4 litres
Xmax	
Voice Coil Dia	25 mm
SPL	89 db
Depth	
Baffle Opening	
Mtg. Cntr	
Each	\$84.55

Each

HM100G0



Vented Voice Coil

4" cast frame rubber edge

paper cone bass-mid Outside Dim......110 x 110 mm Impedance.....8 ohm

Magnet Wt	345 g
Fs	55 Hz
Re	
Qts	0.25
Qes	0.27
Qms	3.34
Vas	6.2 litres
Xmax	2.1 mm
Voice Coil Dia	25 mm
SPL	89 db
Depth	57 mm
Baffle Opening	95 mm
Mtg. Cntr113.6	6 mm BC x 4

Each \$56.45

HT100F0

4" rubber edge fiberglass cone bass-mid



Outside Dia	119 mm
Impedance	8 ohm
Power	
Freq. Resp	
Magnet Wt	
Fs	
Re	
Qts	
Qes	0.52
Qms	1.87
Vas	5.03 litres
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	92 mm
Mtg. Cntr	

Each \$42.90

HT100K0



4" rubber edge Kevlar cone bass-mid

	119 mm
mpedance	8 ohm
ower	
reg. Resp	58 Hz - 10 KHz
√lagnet Wt	
	58 Hz
₹e	
)ts	
es	
Qms	
as	5.21 litres
(max	
oice Coil Dia	
SPL	
Depth	
Baffle Opening	
Ata Catr	106 mm BC x 4
g. ond	100 mm DC X T

Each \$50.75

COMPONENTS direct mail order

<u> AUDAX</u>

HT100M0



4" foam edge paper cone bass-mid

Outside DiaImpedance	
Power	30 W
Freq. Resp	60 Hz - 15 KHz
Magnet Wt	240 g
Fs	60 Hz
Re	5.6 ohm
Qts	0.34
Qes	
Qms	1.67
Vas	
Xmax	3.0 mm
Voice Coil Dia	
SPL	
Depth	52 mm
Baffle Opening	92 mm
Mtg. Cntr	
J	

Each \$34.82

PHILIPS

AD4061W4



4" foam edge paper cone woofer - 4 ohm

Outside Dim	.102 x 102 mm
Impedance	4 ohm
Power	30 W
Freq. Resp	75 Hz - 10 KHz
Magnet Wt	
Fs	75 Hz
Qts	0.47
Qes	
Qms	3.41
Vas	5.27 litres
Voice Coil Dia	
SPL	88 db
Depth	46.8 mm
Baffle Opening	
Mtg. Cntr8	
_	

\$25.42

(I) PIONEER®

W10ER75-51F



4" shielded cast frame black poly cone woofer

Outside Dim Impedance Power	8 ohm
Freq. Resp80).7 Hz - 10 KHz
Magnet Wt	6.5 oz
Voice Coil Dia	25 mm
Fs	80.7 Hz
Re	7.0 ohms
Qts	0.588
Qes	0.838
Qms	
Vas	
Xmax	2.85 mm
SPL	
Depth	66.8 mm
Baffle Opening	96 mm
Mounting	
Each	\$29.52

∰ PIONEER°

A11EC80-02F



4-1/2" cloth edge paper cone full range

Each

Outside Dim	128 x 128 mm
Impedance	8 ohm
Power	30 W
Freq. Resp	70 Hz - 15 KHz
Magnet Wt	9.3 oz
Fs	
Re	
Qts	
Qes	
Qms	
Vas	
Xmax	1.1 mm
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	105 mm
Mtg. Cntr	118 mm BC x 4
Each	\$18.73

McBride

LINEAR B 4.5



4-1/2" foam edge black poly cone woofer

Outside Dia	126 mm
Impedance	8 ohm
Power	30 W
Freq. Resp	67 Hz - 15 KHz
Magnet Wt	6 oz
Fs	67 Hz
Qts	0.55
Qes	0.69
Qms	2.71
Vas	7.21 litres
Voice Coil Dia	
SPL	90 db
Depth	
Baffle Opening	106 mm
Mtg. Cntr	

Each \$25.66

AUDAX

HM130C0



Vented Voice Coil

5-1/4" cast frame rubber edge carbon fiber cone bass-mid

	136 x 136 mm
	8 ohm
	50 W
req. Resp	46 Hz - 10 KHz
	345 g
S	46 Hz
₹e	6.2 ohm
)ts	0.31
es	0.34
)ms	3.6
/as	18.1 litres
	3.0 mm
oice Coil Dia	25 mm
	90 db
Depth	65 mm
	117 mm
	139 mm BC x 4
_	

Each \$92.53

WOOFERS

HM130G14 New with Positive Roll Surround



Vented Voice Coil

5-1/4" cast frame rubber edge paper cone bass-mid

Outside Dim	136 x 136 mm
Impedance	8 ohm
Power	
Freq. Resp	57 Hz - 5 KHz
Magnet Wt	
Fs	57 Hž
Re	
Qts	
Qes	
Qms	
Vas	8.74 litres
Xmax	2.3 mm
Voice Coil Dia	
SPL	
Depth	65 mm
Baffle Opening	
Mtg. Cntr	

5-1/4" rubber edge fiberglass cone bass-mid

Each

\$66.07

HT130F0



Outside Dia	
Impedance	8 ohm
Power	40 W
Freq. Resp	48 Hz - 9 KHz
Magnet Wt	550 q
Fs	
Re	6.5 ohm
Qts	0.25
Qes	0.28
Qms	2.01
Vas	11.1 litres
Xmax	
Voice Coil Dia	25 mm
SPL	90 db
Depth	62 mm
Baffle Opening	
Mtg. Cntr	
Each	\$59.60
Luvii	Ψ00.00

5-1/4" foam edge paper cone full range



McBride

LINEAR B 5.5

Outside Dim	134 x 134 mm
Impedance	8 ohm
Power	35 W
Freq. Resp	63 Hz - 18 KHz
Magnet Wt	
Fs	63 Hz
Qts	0.40
Qes	0.42
Qms	7.77
Vas	
Voice Coil Dia	25 mm
SPL	90.5 db
Depth	61 mm
Baffle Opening	124 mm
Mtg. Cntr	140 mm BC x 4
Each	\$33.31

HM130Z4



Specs given with voice coils connected in parallel

5-1/4" cast frame rubber edge

HD-A cone DVC bass-mid

(I) PIONEER®

B13EU14-53F



5-1/4" polylaminate paper cone woofer

Outside Dim134 x 134 mm
Impedance8 ohm
Power50 W
Freq. Resp70 Hz - 8 KHz
Magnet Wt14 oz
Fs70 Hz
Re7.1 ohm
Qts
Qes0.46
Qms2.11
Vas4.53 litres
Xmax1.4 mm
Voice Coil Dia25 mm
SPL91 db
Depth65 mm
Baffle Opening123 mm
Mta. Cntr140 mm BC x 4

Each \$31.73

WOOFERS

W13ER14-51F




(I) PIONEER[®] 5-1/4" cast frame rubber edge poly cone woofer

Outside DimImpedance	
Power	
Freq. Resp	
Magnet Wt	14 oz
Fs	50 Hz
Re	7.0 ohms
Qts	0.564
Qes	0.731
Qms	2.467
Vas	11.341 litres
Xmax	4.02 mm
Voice Coil Dia	25 mm
SPL	88 db
Depth	77 mm
Baffle Opening	
Mounting	144 mm BC x 4

Each \$44.78

5-1/4" rubber edge polylam.

CWR136B40-4





Outside Dim	4 ohm 40 W .54 Hz - 10 KHz 13 oz
QtsQesQms	0.51 0.60
Vas Voice Coil Dia SPL	14.6 litres 25 mm
Depth Baffle Opening Mtg. Cntr	123 mm
Each	\$19.98

6-1/2" cast frame rubber edge paper cone bass-mid

HM170G0



Vented Voice Coil

Outside Dim166 x 166 mm Impedance.....8 ohm Power60 W Freq. Resp42 Hz - 7 KHz Magnet Wt550 g Voice Coil Dia.....30 mm SPL.....90 db Depth76 mm Baffle Opening.....146 mm Mtg. Cntr172 mm BC x 4

\$77.94 Each

Sammi® CW136B40R-8



5-1/4" rubber edge paper cone woofer

Outside Dim	136 x 136 mm
Impedance	8 ohm
Power	
Freq. Resp	40 Hz - 8 KHz
Magnet Wt	
Fs	
Qts	0.335
Qes	0.378
Qms	
Vas	
Voice Coil Dia	25 mm
SPL	89 db
Depth	62 mm
Baffle Opening	123 mm
Mtg. Cntr	138 mm BC x 4
Each	\$19.98

HM170C0



Vented Voice Coil

6-1/2" cast frame rubber edge carbon fiber cone bass-mid

Outside Dim	8 ohm
Power	
Freq. Resp Magnet Wt	
Fs	
Re	
Qts	0.37
Qes	
Qms	
Vas	30.6 litres
Xmax	
Voice Coil Dia	
SPL	90 db
Depth	
Baffle Opening	
Mtg. Cntr	172 mm BC x 4

\$113.55

6-1/2" cast frame rubber edge HD-A cone bass-mid

Each

HM170Z0



Vented Voice Coil

Outside Dim	8 ohm 60 W 40 Hz - 4 KHz 310 g 40 Hz 6.2 ohm .0.40
Çes	
Qms	6.15
/as	45.3 litres
(max	
oice Coil Dia	30 mm
SPL	
Depth	
Baffle Opening	
4tg. Cntr	

Each \$131.02

McBride 6ACC



6-1/2" foam edge poly cone woofer

Outside Dia167 mm
Impedance8 ohm
Power60 W
Freq. Resp57 Hz - 3 KHz
Magnet Wt20 oz
Fs57 Hz
Qts
Qes
Qms4.18
Vas20 litres
Voice Coil Dia25 mm
SPL91 db
Depth74 mm
Baffle Opening144 mm
Mtg. Cntr155 mm BC x 4
Each \$35.71

McBride

LINEAR B 6.5



6-1/2" foam edge paper cone woofer - full range

167 mm
8 ohm
35 W
Hz - 18 KHz
10 oz
49 Hz
0.56
0.69
3.01
23.2 litres
25 mm
88 db
71 mm
143 mm
mm BC x 4
\$33.72

McBride

MC640



Vented Voice Coil

6-1/2" cloth edge polylam. paper cone woofer

Outside Dia	
Baffle Opening Mtg. Cntr	144 mm

Each \$61.15

MG 6020HC



6-1/2" foam edge paper cone woofer

Outside Dia	
Impedance	
Power	50 W
Freq. Resp	45 Hz - 8 KHz
Magnet Wt	20 oz
Fs	
Re	7.4 ohms
Qts	0.611
Qes	
Qms	
Vas	21.8 litres
Voice Coil Dia	
SPL	87.2 db
Depth	
Baffle Opening	152 mm
Mounting	
_	

Each \$22.43

WOOFERS

(I) PIONEER®

C16EU20-52D



6-1/2" foam edge poly cone woofer - 6 ohm

Outside Dia	
Impedance	6 ohm
Power	
Freq. Resp	
Magnet Wt	
Fs	
Re	5.6 ohms
Qts	0.23
Qes	
Qms	
Vas	22.9 litres
Xmax	0.9 mm
Voice Coil Dia	
SPL	93 db
Depth	71 mm
Baffle Opening	
Mtg. Cntr	
Each	\$33.16

\$33.16

(!) PIONEER®

C16LR20-51F



Vented Voice Coil

6-1/2" rubber edge paper cone woofer

Outside Dia	
Impedance	8 ohm
Power	80 W
Freq. Resp	49 Hz - 5 KHz
Magnet Wt	
Fs	
Re	7.1 ohms
Qts	
Qes	0.18
Qms	4.26
Vas	
Xmax	1.7 mm
Voice Coil Dia	32 mm
SPL	92.8 db
Depth	71 mm
Baffle Opening	
Mtg. Cntr	156 mm BC x 4
E a a la	A07.04

Each \$37.81

(I) PIONEER®

C16LU20-51F



Vented Voice Coil

6-1/2" foam edge polylam. cone woofer

Outside Dia	165 mm
Impedance	8 ohm
Power	80 W
Freq. Resp	57 Hz - 7 KHz
Magnet Wt	20 oz
Fs	
Re	7.1 ohms
Qts	0.22
Qes	
Qms	
Vas	
Xmax	
Voice Coil Dia	32 mm
SPL	93 db
Depth	71 mm
Baffle Opening	
Mtg. Cntr	156 mm BC x 4
Each	\$36.59

\$36.59

PHILIPS fiberglass cone woofer 7" foam edge

AD70623W8



Vented Voice Coil

Outside Dim1 Impedance	
Power	50 W
Freq. Resp	45 Hz - 5 KHz
Total Wt	
Fs	45 Hz
Qts	0.41
Qes	0.46
Qms	3.50
Vas	
Voice Coil Dia	25 mm
SPL	87.1 db
Depth	72.5 mm
Baffle Opening	
Mtg. Cntr	

Each \$61.37

∰ PIONEER°

W16LR20-51F



6-1/2" cast frame rubber edge poly cone woofer

Outside Dim......159.5 x 159.5 mm Impedance.....8 ohm

inpedance	
ower	70 W
req. Resp	
Magnet Wt	20 oz
s	
Re	7.0 ohms
Qts	0.239
Qes	0.258
Öms	3.266
vas	21.183 litres
Xmax	
Voice Coil Dia	32 mm
SPL	90 db
Depth	86.5 mm
Baffle Opening	
Mounting	

Each \$53.32

HM210C0



Vented Voice Coil

8" cast frame rubber edge carbon fiber cone bass-mid

Outside Dim.....210 x 210 mm Impedance.....8 ohm Power70 W Freq. Resp31 Hz - 5.9 KHz Magnet Wt550 g Fs......31 Hz Re6.5 ohm Qms.....5.17 Xmax.....4.15 mm Voice Coil Dia.....40 mm SPL.....90 db Depth89 mm Baffle Opening......188 mm Mtg. Cntr.....217.7 mm BC x 4

\$137.49 Each

COMPONENTS direct mail order

HM210G0



Vented Voice Coil

8" cast frame rubber edge paper cone bass-mid

Outside Dim	210 x 210 mm
Impedance	
Power	
Freq. Resp	30 Hz - 6 KHz
Magnet Wt	
Fs	
Re	
Qts	
Qes	
Qms	2.70
 Vas	
Xmax	4.15 mm
Voice Coil Dia	40 mm
SPL	
Depth	89 mm
Baffle Opening	
Mtg. Cntr	

8" foam edge

McBride 8ACC

poly cone woofer



Outside DiaPowerFreq. Resp	8 ohm 75 W 43 Hz - 3 KHz
Fs	
Qts	0.43
Qes	0.50
Qms	3.16
Vas	36.7 litres
Voice Coil Dia	38 mm
SPL	
Depth	85 mm
Baffle Opening	184 mm
Mtg. Cntr1	95 mm BC x 8

\$56.34

McBride

LINEAR B 8.0



8" foam edge paper cone woofer - full range

Each

Each

Outside Dia	208 mm
Impedance	8 ohm
Power	40 W
Freq. Resp	41 Hz - 18 KHz
Magnet Wt	
Fs	41 Hz
Qts	0.71
Qes	0.93
Qms	
Vas	70.5 litres
Voice Coil Dia	25 mm
SPL	89 db
Depth	84 mm
Baffle Opening	184 mm
Mtg. Cntr	195 mm BC x 8

HM210Z0



Vented Voice Coil

8" cast frame rubber edge HD-A cone bass-mid

Outside Dim	210 x 210 mm
Impedance	8 ohm
	70 W
	30 Hz - 2.9 KHz
	550 g
	30 Hz
Re	6.3 ohm
Qts	0.31
	0.32
Oms	6.45
Vas	108.1 litres
Xmax	
Voice Coil Dia	
	91 db
Depth	89 mm
Baffle Opening	188 mm
	.217.7 mm BC x 4
-	

\$155.12 Each

McBride IMAGE 8



8" foam edge paper cone woofer

Outside Dia	208 mm
Impedance	
Power	
Freq. Resp	
Magnet Wt	
Fs	46 Hz
Qts	
Qes	
Qms	
Vas	
Voice Coil Dia	38 mm
SPL	93 dh
Depth	
Baffle Opening	
Mtg. Cntr	.195 mm BC x 8
_	
Each	\$51.35

McBride

MC840



Vented Voice Coil

8" hi-power cloth edge polylam. cone woofer

Outside Dia	208 mm
Impedance	8 ohm
Power	100 W
Freq. Resp	40 Hz - 4 KHz
Magnet Wt	
Fs	41 Hz
Qts	
Qes	0.33
Qms	
Vas	47 litres
Voice Coil Dia	38 mm
SPL	92 db
Depth	
Baffle Opening	184 mm
Mtg. Cntr	
_	

Each \$69.02

\$40.45

COMPONENTS direct mail order

MG 820PP



8" foam edge black poly cone woofer

Outside Dia	
Impedance	8 ohm
Power	
Freq. Resp	40 Hz - 8 KHz
Magnet Wt	30 oz
Fs	44 Hz
Re	7.59 ohms
Qts	0.964
Qes	1.436
Qms	2.938
Vas	
Voice Coil Dia	25 mm
SPL	
Depth	
Baffle Opening	183 mm
Mounting19	
-	

PHILIPS

AD80100W8



8" foam edge paper cone woofer

Outside Dia	208 mm
Impedance	
Power	
Freq. Resp	41 Hz - 4 KHz
Magnet Wt	
Fs	
Qts	0.325
Qes	0.351
Qms	
Vas	
Voice Coil Dia	38 mm
SPL	
Depth	83 mm
Baffle Opening	183 mm
Mtg. Cntr	195 mm BC x 8
Each	\$46.90

PHILIPS

AD80629W8DC



Vented Voice Coil

8" foam edge doped paper cone woofer

Each

\$25.63

Outside Dia 191.6 x 191.6 mm Impedance
Mtg. Cntr198 mm BC x 4
Each \$51.73

(!) PIONEER®

B20EU90-51F



8" foam edge paper cone woofer

Outside Dia	
Impedance	8 ohm
Power	50 W
Freq. Resp	44 Hz - 3 KHz
Magnet Wt	
Fs	44 Hz
Re	6.5 ohm
Qts	0.35
Qes	0.40
Qms	2.76
Vas	81 litres
Xmax	0.8 mm
Voice Coil Dia	
SPL	94 db
Depth	82 mm
Baffle Opening	185 mm
Mtg. Cntr	195 mm BC x 4
Each	\$31.54

(I) PIONEER®

B20FU14-54F



8" foam edge poly cone woofer

Outside Dia	205 mm
Impedance	8 ohm
Power	75 W
Freq. Resp	
Magnet Wt	
Fs	
Re	7.1 ohm
Qts	0.35
Qes	0.39
Qms	3.03
Vas	36.8 litres
Xmax	
Voice Coil Dia	
SPL	90 db
Depth	87 mm
Baffle Opening	184 mm
Mtg. Cntr	
-	

Each \$35.15

(I) PIONEER®

B20FU20-51D



8" foam edge poly cone woofer - 6 ohm

Outside Dia	205 mm
mpedance	
ower	
req. Resp	
lagnet Wt	
S	
₹e	
)ts	
es	
)ms	2.86
/as	
(max	
oice Coil Dia	
SPL	
Depth	
Baffle Opening	184 mm
4tg. Cntr	

Each \$44.14

COMPONENTS direct mail order

(I) PIONEER®

B20FU20-54F



8" foam edge paper cone woofer

Outside Dia	205 mm
Impedance	8 ohm
Power	
Freq. Resp	
Magnet Wt	
Fs	40 Hz
Re	6.9 ohm
Qts	0.26
Qes	0.29
Qms	2.50
Vas	
Xmax	
Voice Coil Dia	38 mm
SPL	
Depth	91 mm
Baffle Opening	
Mtg. Cntr	195 mm BC x 4
ritgi citti iiiiiiiiiii	1133 IIIII BC X I

Each \$41.26

8" cast frame rubber

W20GR30-51F

(I) PIONEER®



Vented Voice Coil

ed	ge poly co	one woofer
	Impedance Power Freq. Resp Magnet Wt	223 x 233 mm 8 ohm 80 W 32 Hz - 3 KHz 30 oz
		32 Hz 7.0 ohms
	Qts	0.320
	Qms	1.999 43.28 litres
		4.6 mm

\$83.52 Each

Voice Coil Dia.....51 mm SPL.....90 db Depth104 mm Baffle Opening186 mm Mounting227.5 mm BC x 4

<u>Sammi®</u> CWR200B50



8" rubber edge paper cone woofer

-	Outside Dia	208 mm
		8 ohm
		50 W
		24 Hz - 4 KHz
		13 oz
		24 Hz
	Ots	0.584
	Oes	0.682
	Oms	4.07
		93 litres
		25 mm
		85 db
		89 mm
		182 mm
		198 mm BC x 4
1	Mtg. Chu	190 HIIII DC X 4

Each \$26.64

(I) PIONEER

B20GR30-51F



Vented Voice Coil

8" hi-power rubber edge paper cone woofer

Outside Dia	205 mm
Impedance	8 ohm
Power	120 W
Freq. Resp	31 Hz - 7 KHz
Magnet Wt	30 oz
Fs	31 Hz
Re	5.8 ohm
Qts	0.26
Qes	0.27
Qms	
Vas	
Xmax	
Voice Coil Dia	
SPL	91 db
Depth	96 mm
Baffle Opening	184 mm
Mtg. Cntr	195 mm BC x 4
ritg. Cita	133 Hill DC X 4
Each	\$66.49

Sammi® CWR200B20U



8" foam edge paper cone woofer

Outside Dia	8 ohm 20 Wrms Hz - 3.5 KHz 10 oz 37.7 Hz 0.664 5.35 57.9 litres 25 mm 88 db
Depth	71 mm 187 mm
Each	\$17.99

HT240M0



10" foam edge paper cone woofer

Outside Dia	
Impedance	8 ohm
Power	80 W
Freq. Resp	28 Hz - 5 KHz
Magnet Wt	
Fs	
Re	6.3 ohm
Qts	0.37
Qes	
Qms	1.81
Vas	223.1 litres
Xmax	4.5 mm
Voice Coil Dia	37 mm
SPL	92 db
Depth	101 mm
Baffle Opening	
Mtg. Cntr	237 mm BC x 4

Each \$81.63



McBride

10ACC



10" foam edge poly cone woofer

Outside Dia	
Impedance	8 ohm
Power	100 W
Freq. Resp	28 Hz - 2.5 KHz
Magnet Wt	28 oz
Fs	
Qts	0.35
Qes	
Qms	3.94
Vas	135.5 litres
Voice Coil Dia	38 mm
SPL	
Depth	109 mm
Baffle Opening	234 mm
Mtg. Cntr	248 mm BC x 8
-	

Each \$66.76

McBride

CAR1040-4



Vented Voice Coil

10" black poly cone car subwoofer - 4 ohm

Outside Dia	256 mm
Impedance	4 ohm
Power	
Freq. Resp	30 Hz - 1 KHz
Magnet Wt	40 oz
Fs	33 Hz
Re	
Qts	0.393
Qes	
Qms	
Vas	40.44 litres
Voice Coil Dia	51 mm
Xmax	9.52 mm
SPL	87.3 db
Depth	124 mm
Baffle Opening	
Mounting	
5	

Each \$77.50

McBride

LINEAR B 10.0



10" foam edge paper cone woofer

Outside Dia	256 mm
Impedance	8 ohm
Power	
Freq. Resp	30 Hz - 2.5 KHz
Magnet Wt	20 oz
Fs	
Qts	0.54
Qes	0.64
Qms	3.28
Vas	
Voice Coil Dia	38 mm
SPL	90 db
Depth	105 mm
Baffle Opening	
Mtg. Cntr	

Each \$53.08

McBride

MC1040



Vented Voice Coil

10" hi-power cloth edge polylam. cone woofer

Outside Dia	256 mm
Impedance	8 ohm
Power	125 W
Freq. Resp	32 Hz - 2.5 KHz
Magnet Wt	
Fs	32 Hz
Qts	0.32
Qes	0.38
Qms	2.07
Vas	
Voice Coil Dia	38 mm
SPL	93 db
Depth	110 mm
Baffle Opening	
Mtg. Cntr	
3	

PHILIPS

AD10240W8



10" foam edge paper cone woofer

Outside Dia	256 mm
Impedance	8 ohm
Power	
Freq. Resp	
Magnet Wt	
Fs	
Qts	0.31
Qes	0.34
Qms	
Vas	
Voice Coil Dia	51 mm
SPL	91 db
Depth	108 mm
Baffle Opening	234 mm
Mtg. Cntr	

Each \$77.35

∰ PIONEER®

A25FU14-57F



10" foam edge poly cone woofer

Each

\$73.52

Outside Dia	256 mm
Impedance.	8 ohm
Power	70 W
Freq. Resp.	28 Hz - 2.5 KHz
	14 02
	28 Hz
Re	7.4 ohm
Qts	0.49
Qes	0.55
	4.28
	121.2 litres
	3.4 mm
	ia38 mm
	89 dt
	104 mm
Baffle Open	ing236 mm
Mtg. Cntr	248 mm BC x 4

Each \$38.75

COMPONENTS direct mail order

∰ PIONEER°

A25FU20-53F



10" foam edge paper cone woofer

Outside Dia	256 mm
Impedance	8 ohm
Power	70 W
Freq. Resp	35 Hz - 3.5 KHz
Magnet Wt	20 oz
Fs	35 Hz
Re	7.0 ohm
Qts	0.27
Qes	0.30
Qms	
Vas	124.9 litres
Xmax	
Voice Coil Dia	38 mm
SPL	
Depth	109 mm
Baffle Opening	
Mtg. Cntr	248 mm BC x 4
<u> </u>	

Each \$47.76

∰ PIONEER°

A25GU30-51F



10" foam edge paper cone woofer

Outside Dia	256 mm
Impedance	8 ohm
Power	100 W
Freq. Resp	28 Hz - 2 KHz
Magnet Wt	
Fs	
Re	6.0 ohm
Qts	
Qes	0.20
Qms	1.74
Vas	
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mtg. Cntr	
	A=0 ()

Each \$59.11

∰ PIONEER®

W25GR40-51F



Vented Voice Coil

10" cast frame rubber edge poly cone woofer

	279 x 279 mm
impedance	8 ohm
Power	100 W
Freq. Resp	30 Hz - 3 KHz
Magnet Wt	40 oz
	30 Hz
	7.0 ohms
Qts	0.450
Qes	0.534
Qms	2.858
Vas	68.95 litres
	4.6 mm
Voice Coil Dia	51 mm
SPL	90 db
Depth	122 mm
Baffle Opening	234 mm
	.281.5 mm BC x 4

Each \$115.20

∰ PIONEER®

A25FU30-51D



10" foam edge poly cone woofer – 6 ohm

Outside Dia	256 mm
Impedance	6 ohm
Power	85 W
Freg. Resp	26 Hz - 2.5 KHz
	30 oz
Fs	26 Hz
	5.5 ohm
	0.20
	0.21
	3.36
	171.9 litres
Xmax	2.9 mm
	38 mm
	93 db
	113 mm
Baffle Opening	236 mm
Mtg. Cntr	248 mm BC x 4
Each	\$60.72

∰ PIONEER®

W25GR31-51F



Vented Voice Coil

10" hi-power rubber edge paper cone woofer

Outside Dia	256 mm
Impedance	8 ohm
Power	120 W
Freq. Resp	26 Hz - 2.5 KHz
Magnet Wt	
Fs	
Re	6.9 ohm
Qts	0.34
Qes	0.36
Qms	
Vas	
Xmax	
Voice Coil Dia	51 mm
SPL	90 db
Depth	
Baffle Opening	238 mm
Mtg. Cntr	246 mm BC x 4
Each	\$77.81

Sammi® CWR250B30U



10" foam edge paper cone woofer

	263 mm
mpedance	8 ohm
	30 Wrms
reg. Resp	37 Hz - 3 KHz
	14 oz
	37.5 Hz
)ts	0.495
es	0.549
	5.02
/as	132.2 litres
	25 mm
SPL	92.8 db
	87 mm
Baffle Opening	231 mm
	249 mm BC x 4
_	

Each \$33.74

COMPONENTS direct mail order

McBride

12ACC



12" foam edge poly cone woofer

Outside Dia	310 mm
Impedance	8 ohm
Power	120 W
Freq. Resp	21 Hz - 2 KHz
Magnet Wt	
Fs	
Qts	0.17
Qes	0.18
Qms	
Vas	
Voice Coil Dia	51 mm
SPL	
Depth	127 mm
Baffle Opening	
Mtg. Cntr	

Vented Voice Coil

12" black poly cone **McBride** car subwoofer - 4 ohm CAR1240-4



Vas67.08 litres Xmax.....9.52 mm Voice Coil Dia.....51 mm Depth137 mm Baffle Opening283 mm Mounting......301 mm BC x 8

Outside Dia310 mm Impedance.....4 ohm

Each \$87.50

McBride

IMAGE 12



12" foam edge paper cone woofer

\$81.68

Each

Outside Dia	310 mm
Impedance	8 ohm
Power	
Freq. Resp	.29 Hz - 2 KHz
Magnet Wt	
Fs	
Qts	0.33
Qes	
Qms	3.24
Vas	229 litres
Voice Coil Dia	51 mm
SPL	94 db
Depth	127 mm
Baffle Opening	283 mm
Mtg. Cntr3	801 mm BC x 8
Each	\$88.30

McBride LINEAR B 12.0



12" foam edge paper cone woofer

Outside Dia	310 mm
Impedance	8 ohm
Power	60 W
Freq. Resp	
Magnet Wt	
Fs	27.3 Hz
Qts	
Qes	
Qms	
Vas	
Voice Coil Dia	
SPL	
Depth	116 mm
Baffle Opening	283 mm
Mtg. Cntr	301 mm BC v 8
rity. Cita	JOI HILL DC X 0
Each	\$59.03

McBride

MC1240



Vented Voice Coil

12" cloth edge polylam. cone woofer

Outside Dia Impedance Power	8 ohm
Freq. Resp	31 Hz - 2.1 KHz
Fs	31.5 Hz
Qts Qes	0.47
Qms Vas	3.99
Voice Coil Dia	38 mm
SPL Depth	
Baffle Opening Mtg. Cntr	

Each \$78.43

McBride

VHP1200



12" foam edge paper cone woofer

Outside Dia	
Impedance	8 ohm
Power	150 W
Freq. Resp	27 Hz - 2 KHz
Magnet Wt	56 oz
Fs	27 Hz
Re	
Qts	0.27
Qes	0.28
Qms	7.97
Vas	298 litres
Xmax	3.7 mm
Voice Coil Dia	51 mm
SPL	
Depth	129 mm
Baffle Opening	283 mm
Mta. Cntr	

Each \$84.23



PHILIPS

AD12240W8



12" foam edge paper cone woofer

Outside Dia	310 mm
Impedance	8 ohm
Power	120 W
Freq. Resp	26 Hz - 2 KHz
Magnet Wt	40 oz
Fs	
Qts	0.30
Qes	0.33
Qms	
Vas	289 litres
Voice Coil Dia	
SPL	
Depth	128 mm
Baffle Opening	
Mtg. Cntr3	

Each \$87.14

(!) PIONEER®

A30FU20-52F



12" foam edge paper cone woofer

Outside Dia	306 mm
Impedance	8 ohm
Power	90 W
Freq. Resp	30 Hz - 2.5 KHz
Magnet Wt	20 oz
Fs	
Re	
Qts	0.31
Qes	0.36
Qms	
Vas	289.1 litres
Xmax	2.4 mm
Voice Coil Dia	
SPL	95 db
Depth	122 mm
Baffle Opening	
Mtg. Cntr	
Cook	ΦE0.70

Each \$58.76

(I) PIONEER®

A30FU20-53F



12" foam edge poly cone woofer

Outside Dia	306 mm
Impedance	8 ohm
Power	90 W
Freq. Resp	28 Hz - 2 KHz
Magnet Wt	20 oz
Fs	
Re	
Qts	0.31
Qes	0.34
Qms	3.71
Vas	
Xmax	2.4 mm
Voice Coil Dia	38.1 mm
SPL	94 db
Depth	122 mm
Baffle Opening	279 mm
Mtg. Cntr	298 mm BC x 8
	A-0 4-

Each \$59.47

(!) PIONEER®

A30GU30-54F



12" foam edge paper cone woofer

Outside Dia	306 mm
Impedance	8 ohm
Power	100 W
Freq. Resp	27 Hz - 2.5 KHz
Magnet Wt	30 oz
Fs	27 Hz
Re	5.9 ohm
Qts	0.26
Qes	0.31
Qms	1.67
Vas	250 litres
Xmax	0.5 mm
Voice Coil Dia	
SPL	94 db
Depth	126 mm
Baffle Opening	279 mm
Mtg. Cntr	298 mm BC x 8
Each	\$74.80

Each

(I) PIONEER®

A30GU40-51D



12" foam edge poly cone woofer – 6 ohm

Outside Dia	306 mm
Impedance	6 ohm
Power	
Freq. Resp	23 Hz - 1.5 KHz
Magnet Wt	
Fs	23 Hz
Re	5.2 ohm
Qts	0.16
Qes	0.18
Qms	1.86
Vas	359 litres
Xmax	2.5 mm
Voice Coil Dia	51 mm
SPL	96 db
Depth	
Baffle Opening	
Mtg. Cntr	298 mm BC x 8
. reg. one minimum	MESO MINI DO A O

Each \$82.34

(!) PIONEER®

A30IR50-51F



Vented Voice Coil

12" hi-power rubber edge paper cone woofer

Outside Dia	308 mm
mpedance	8 ohm
ower	160 W
	19 Hz - 1.5 KHz
Magnet Wt	50 oz
Ξς	19 Hz
	6.9 ohm
	0.25
des Des	0.27
Oms	4.37
Jas	337.3 litres
	3.1 mm
	63.5 mm
	91 db
	137 mm
	279 mm
Mta Catr	293 mm BC x 8
11y. Cita	233 HIIII DC X 0

Each \$107.65

COMPONENTS direct mail order

(I) PIONEER®

L30FC14-51F



12" square frame paper cone woofer

Outside Dim	302 x 302 mm
Impedance	8 ohm
Power	
Freq. Resp	
Magnet Wt	
Fs	34 Hz
Re	
Qts	
Qes	
Qms	
Vas	
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mtg. Cntr	318 mm BC x 4

<u>Sammi®</u> CWR300B150R

12" rubber edge polylam. cone woofer

\$60.10

Each



Outside Dia	310 mm
Impedance	8 ohm
Power	150 W
Freq. Resp	
Magnet Wt	
Fs	
Qts	0.28
Qes	0.32
Qms	
Vas	487 litres
Voice Coil Dia	38 mm
SPL	
Depth	132 mm
Baffle Opening	277 mm
Mtg. Cntr2	92 mm BC x 8
Each	\$69.26

PHILIPS

AD15240W8



15" foam edge paper cone woofer

Outside Dia	384 mm
Impedance	8 ohm
Power	
Freq. Resp	22 Hz - 2 KHz
Magnet Wt	40 oz
Fs	22 Hz
Qts	0.25
Qes	0.27
Qms	4.70
Vas	578.6 litres
Voice Coil Dia	51 mm
SPL	95.5 db
Depth	156 mm
Baffle Opening	354 mm
Mtg. Cntr	

Each

∰ PIONEER®

W30IR50-51F



Vented Voice Coil

12" cast frame rubber

edge poly cone woofer

Outside Dim	328 x 328 mm
mpedance	8 ohm
ower	
req. Resp	20 Hz - 2 KHz
Magnet Wt	50 oz
s	20 Hz
Re	7.0 ohms
Qts	0.214
Qes	0.238
Qms	
√as	199.91 litres
Xmax	4.55 mm
Voice Coil Dia	64 mm
SPL	91 db
Depth	132 mm
Baffle Opening	277.5 mm
Mounting	331.5 mm BC x 8
	644004

Each \$149.04

McBride

VHP1500



15" foam edge paper cone woofer

Outside Dia	384 mm
Impedance	8 ohm
Power	150 W
Freq. Resp	24 Hz - 2 KHz
Magnet Wt	56 oz
Fs	24.8 Hz
Re	6.2 ohm
Qts	0.35
Qes	0.37
Qms	
Vas	657.4 litres
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mtg. Cntr	
ricg. Ond	3/3 Hill DC X 0

Each \$103.07

(!) PIONEER®

A38GU40-52D



15" foam edge poly cone woofer - 6 ohm

Outside Dia	387.5 mm
Impedance	6 ohm
Power	
Freq. Resp	24 Hz - 2.5 KHz
Magnet Wt	40 oz
Fs	
Re	
Qts	
Qes	
Qms	
Vas	
Xmax	
Voice Coil Dia	51 mm
SPL	95 db
Depth	
Baffle Opening	
Mtg. Cntr	377 mm BC x 8

Each \$93.71

\$103.24



WOOFERS

∰ PIONEER®

A38GU40-52F



15" foam edge paper cone woofer

Outside Dia	387.5 mm
Impedance	8 ohm
Power	120 W
Freq. Resp	20 Hz - 3 KHz
Magnet Wt	40 oz
Fs	
Re	6.5 ohm
Qts	0.24
Qes	0.27
Qms	2.44
Vas	799 litres
Xmax	3.8 mm
Voice Coil Dia	51 mm
SPL	
Depth	152 mm
Baffle Opening	357.5 mm
Mtg. Cntr	377 mm BC x 8
Each	\$91.92
Laon	Ψ01.02

∰ PIONEER°

A38IR50-51F



Vented Voice Coil

15" rubber edge paper cone woofer

Outside Dia	387 mm
Impedance.	8 ohm
 Power	150 W
Freg. Resp .	42 Hz - 3 KHz
	50 oz
	42 Hz
	7.4 ohm
Qts	0.908
	1.063
Qms	6.224
Vas	118.5 litres
Xmax	3.1 mm
Voice Coil D	ia64 mm
SPL	91.3 db
	165 mm
Baffle Openi	ing357.5 mm
	377 mm BC x 8
	644470

VOICE COIL SUBWOOFERS

5-1/4" cast frame rubber edge HD-A cone DVC bass-mid

HM130Z4



Specs given with voice coils connected in parallel.

Outside Dim 136 x 136 mm Impedance 2 x 8 ohm Power 50 W Freq. Resp 46 Hz - 4.5 KHz Magnet Wt 350 g Fs 46 Hz Re 2 x 6.0 ohm Qts 0.23 Qes 0.24 Qms 5 20 Vas 10.2 litres Xmax 3.25 mm Voice Coil Dia 25 mm SPL 91 db Depth 60 mm Baffle Opening 117 mm
Baffle Opening117 mm Mtg. Cntr139 mm BC x 4

Each

\$113.06

HT170G8



Specs given with voice coils

6-1/2" rubber edge damped paper cone DVC woofer

Outside Dim1	
Impedance	2 x 8 ohm
Power	50 W
Freq. Resp	
Magnet Wt	310 q
Fs	
Re	2 x 7.0 ohm
Qts	0.49
Qes	0.55
Qms	4.93
Vas	
Xmax	3.5 mm
Voice Coil Dia	30 mm
SPL	90 db
Depth	70 mm
Baffle Opening	143 mm
Mtg. Cntr	
Each	\$49.98
_~~.	Ψ.υ.υυ

connected in parallel.

8" foam edge black **♥ PIONEER®** poly cone DVC woofer

B20FU20-52D



Specs given with voice coils connected in parallel.

Outside Dia205 mm

• • • • • • • • • • • • • • • • • • • •	
Impedance	2 x 6 ohm
Power	
Freq. Resp	32 Hz - 800 Hz
Magnet Wt	
Fs	
Re	
Qts	
Qes	0.23
Qms	
Vas	
Xmax	3.5 mm
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mtg. Cntr	
_	

Each \$46.51

HM170Z2



Specs given with voice coils connected in parallel.

HM210Z2

6-1/2" cast frame rubber

edge HD-A cone DVC woofer

Outside Dim	166 x 166 mm
Impedance	2 x 8 ohm
Power	60 W
Freq. Resp	35 Hz - 4 KHz
Magnet Wt	310 g
	35 Hž
	2 x 5.4 ohm
	0.35
Qes	
	7.60
Vas	
Xmax	3 75 mm
Voice Cail Dia	20 mm
Voice Coil Dia	00 db
3rL	89 db
Deptn	70 mm
Baffle Opening	146 mm
Mtg. Cntr	172 mm BC x 4
Each	\$130.93
	7.30.00

8" cast frame rubber edge HD-A cone DVC woofer

Outside Dim.....210 x 210 mm

\$158.35

• • • • • • • • • • • • • • • • • • • •	
Impedance	2 x 8 ohm
Power	70 W
	28 Hz - 3.5 KHz
	550 g
	28 Hž
Re	2 x 6.0 ohm
Qts	0.31
Qes	0.32
Qms	9.08
Vas	63.1 litres
Xmax	
Voice Coil Dia	40 mm
	89 db
Depth	89 mm
	188 mm

Specs given with voice coils connected in parallel.

(I) PIONEER®

A25GU25-51D



Specs given with voice coils connected in parallel.

10" foam edge black poly cone DVC woofer

Each

Mtg. Cntr.....217.7 mm BC x 4

Outside Dia mpedance	
ower	
req. Resp	
lagnet Wt	
S	
₹e	2 x 6.0 ohm
)ts	0.21
)es	0.22
)ms	3.89
/as	90 litres
(max	
oice Coil Dia	51 mm
SPL	91 db
Depth	113 mm
Baffle Opening	
1tg. Cntr	

Each \$60.91



DUAL VOICE COIL SUBWOOFERS

∰ PIONEER°

12" foam edge black poly cone DVC woofer

Each

A30GU30-55D



Specs given with voice coils connected in parallel.

Outside Dia	306 mm
Impedance	2 x 6 ohm
Power	2 x 75 W
Freq. Resp24 I	Hz - 1.5 KHz
Magnet Wt	30 oz
Fs	24 Hz
Re	2 x 6.0 ohm
Qts	0.21
Qes	0.22
Qms	4.05
Vas	277 litres
Xmax	3.1 mm
Voice Coil Dia	51 mm
SPL	94 db
Depth	122 mm
Baffle Opening	279 mm
Mtg. Cntr298	mm BC x 8

\$76.96

∰ PIONEER®

A38GU40-51E



Specs given with voice coils connected in parallel.

15" foam edge paper cone DVC woofer

Impedance	0.44
Baffle Opening	152 mm 357.5 mm 377 mm BC x 8



4 OHM CAR SPEAKERS AND SUBWOOFERS

Sammi®

CX501



5-1/4" rubber edge polylam cone co-ax. - 4 ohm

Outside Dim	136 x 136 mm
Impedance	
Power	
Freq. Resp	
Magnet Wt	
Fs	
Qts	0.410
Qes	0.503
Òms	
Vas	
Voice Coil Dia	25 mm
SPL	
Depth	67 mm
Baffle Opening	
Mtg. Cntr	
3	

\$32.56

\$77.50

Sammi® CX601



6-1/2" rubber edge polylam cone co-ax. - 4 ohm

Outside Dia	165 mm
Impedance	4 ohm
Power	30 W
Freq. Resp	65 Hz - 20 KHz
Magnet Wt	
Fs	
Qts	0.85
Qes	1.32
Qms	
Vas	
Voice Coil Dia	25 mm
SPL	89 db
Depth	66.5 mm
Baffle Opening	146 mm
Mtg. Cntr	
Each	\$36.46
	ΨΟΟ

McBride

CAR1040-4



Vented Voice Coil

10" black poly cone car subwoofer - 4 ohm

Each

Each

Outside Dia	4 ohm 175 WRMS 30 Hz - 1 KHz 40 oz 33 Hz 3.5 ohms 0.393 0.409
Qms Vas	40.44 litres
Xmax	51 mm 87.3 db 124 mm 234 mm

McBride

CAR1240-4



Vented Voice Coil

12" black poly cone car subwoofer - 4 ohm

Outside Dia	310 mm
Impedance	4 ohm
Power	
Freq. Resp	30 Hz - 1 KHz
Magnet Wt	
Fs	
Re	3.3 ohms
Qts	
Qes	0.572
Qms	
Vas	67.08 litres
Xmax	
Voice Coil Dia	51 mm
SPL	
Depth	137 mm
Baḟfle Opening	
Mounting	
-	

\$87.50

Each



PASSIVE RADIATORS

(I) PIONEER®

Flat cone passive radiators



DC-	·04G	
cizo		

Mtg. Cntr	236 mm BC x 4
Baffle Opening	185 mm
Depth	
Effective vent dia	165.1 mm
Moving mass	15 a
Outside Dim	221 x 221 mm
Nominal size	8 inch

Each \$12.43

DC-03G

Nominal size	10 inch
Outside Dim	277 x 277 mm
Moving mass	25 g
Effective vent dia	210.1 mm
Depth	15.2 mm
Baffle Opening	236 mm
Mtg. Cntr	.282 mm BC x 4

Each \$17.14

DC-02G

Nominal size	12 inch
Outside Dim	328 x 328 mm
Moving mass	
Effective vent dia	
Depth	
Baffle Opening	
Mtg. Cntr	333 mm BC x 4

Each \$21.80

TREMORS by Stanford Acoustics

TREMORS


STANFORD ACOUSTICS TM-4 TREMORS



The TM-4 TREMORS is now available from Stanford Acoustics. This device will shake whatever its mounted to in time with the music or any low frequency energy in the soundtrack (explosions, crashes, earthquakes etc.).

The bone jarring, high energy vibrations created by Tremors are great for a diverse range of special effect applications, such as interactive amusement rides or arcade games, commercial sound, personal home theatre or autosound. Tremors are easily mounted to walls, floors, chairs, couches or ???.

Connect to your amplifier and let the good times shake, rattle and roll!




Bolt Circle Mtg. Depth Housing	
Unit Weight Power	13 oz 50 W rms / 100 W peak
Freq. Resp Impedance	20 Hz - 10 KHz 16 ohm x 2 (dual coils)
Each	\$35.94

<u> AUDAX</u>

AW010E1

10 mm shielded polymer dome tweeter







Sammi®

MT-15

1/2" shielded polymer dome tweeter

Outside Dim53 x 53 mm
Impedance8 ohm
Power40 W / 12 db / 5 KHz
Freq. Resp4 KHz - 20 KHz
Magnet Wt2 oz
Fs2000 Hz
Voice Coil Dia14 mm
SPL92 db
Depth25 mm
Baffle Opening48 mm
Mtg. Cntr60 mm BC x 4
Min. X-over4 KHz / 12 db

Each \$9.98

PHILIPS AD00973/T8FF

18 mm shielded neodymium mag. polygrid dome tweeter



Outside Dim	40 x 60 mm
Impedance	8 ohm
Power 70 W	/ 12 db / 4.5 KHz
Freq. Resp	2.8 KHz - 20 KHz
Total Wt	38 g
Fs	n/a
Voice Coil Dia	18 mm
SPL	88 db
Depth	12 mm
Baffle Opening	40 mm
Mtg. Cntr	50 mm BC x 2
Min. X-over	2.8 KHz / 12 db

\$26.65

Ferrofluid Cooled

<u> AUDAX</u>

1" shielded neodymium mag. soft dome tweeter

TM025C1



Outside Dia40 mm
Impedance8 ohm
Power70 W / 12 db / 2.9 KHz
Freq. Resp2.5 KHz - 20 KHz
Magnet Wt43 g
Magnet MatlNeodymium
Voice Coil Dia25 mm
Fs1250 Hz
Xmax0.05 mm
SPL89 db
Depth30.3 mm
Baffle Opening37 mm
MountingSnap-in
Min. X-over2.5 KHz / 12 db
11111 / OTC 1111111111213 (112 / 12 do
Each \$28.40
Each \$28.40

Ferrofluid Cooled

AUDAX

1" shielded neodymium mag. soft dome tweeter

Each

TM025F1



Ferrofluid Cooled

Outside Dia	70 mm
	8 ohm
Power70 W	/ 12 db / 2.8 KHz
Freq. Resp	.2.5 KHz - 20 KHz
Magnet Wt	54 g
	Neodymium
Voice Coil Dia	25 mm
Fs	1250 Hz
	0.05 mm
SPL	92 db
	32.5 mm
Baffle Opening	51 mm
	62 mm BC x 4
Min. X-over	2.5 KHz / 12 db
	404.00



<u> AUDAX</u>

1" shielded neodymium mag. soft dome tweeter

TM025F13



Each \$34.80

Ferrofluid Cooled

<u> AUDAX</u>

1" shielded neodymium mag. titanium dome tweeter

TM025F7



Ferrofluid Coole

<u> AUDAX</u>

TM025F15



Impedance70 W Freq. Resp	
	64 g
	Neodymium
	25 mm
Fs	1500 Hz
	0.05 mm
SPL	94 db
Depth	32.5 mm
	51 mm
	62 mm BC x 4
	2.8 KHz / 12 dh

\$34.80

Each

1" shielded neodymium mag. soft dome tweeter

Ferrofluid Cooled

AUDAX

TM025F9



1" shielded neodymium mag. soft dome tweeter

Ferrofluid Cooled

Sammi® MSF77B20U-4

3" shielded foam edge paper cone woofer - 4 ohm


Each



	82 x 82 mm
	20 W
	116 Hz - 10 KHz
	8 oz
	116 Hz
	0.505
	0.578
	3.97
	1.53 litres
	20 mm
	88 db
	51 mm
	73 mm
Itg. Cntr	85 mm BC x 4

\$19.52

AP100G0





Outside Dia	
Impedance	6 ohm
Power	30 W
Freq. Resp	75.7 Hz - 10 KHz
Magnet Wt	205 q
Fs	75.7 Hz
Re	5.7 ohm
Qts	0.60
Qes	
Qms	
Vas	3.37 litres
Xmax	2.7 mm
Voice Coil Dia	
SPL	84.5 db
Depth	67 mm
Baffle Opening	91 mm
Mounting1	107.5 mm BC x 4
Each	\$41.01

4" shielded polymer frame paper cone bass-mid

AP100M0



	117 mm
	6 ohm
	30 W
Freq. Resp	82.5 Hz - 6 KHz
Magnet Wt	205 g
Fs	82.5 Hz
Re	5.6 ohm
Qts	0.58
	0.76
Qms	2.50
	3.07 litres
Xmax	2.7 mm
Voice Coil Dia	25 mm
SPL	85.4 db
Depth	67 mm
	91 mm
	107.5 mm BC x 4
-	

4" shielded polymer frame HD-A cone bass-mid

AP100Z0



\$44.73 Each

∰ PIONEER®

W10ER75-51F



rubber edge poly cone woofer		
		106 x 106 mm 8 ohm
		35 W

4" shielded cast frame

\$36.04

\$29.52

Each

Each

Judiue Dilli	100 x 100 mm
mpedance	8 ohm
ower	
req. Resp	
Magnet Wt	6.5 oz
Voice Coil Dia	
s	80.7 Hz
Re	
Qts	0.588
Qes	
Qms	1.966
√as	3.782 litres
Xmax	2.85 mm
SPL	85.6 db
Depth	66.8 mm
Baffle Opening	96 mm
Mounting	115 mm BC x 4

(I) PIONEER®

A11EC80-53F



4-1/2" shielded paper cone woofer - fullrange

Outside Dim	
Impedance	8 ohm
Power	
Freq. Resp	70 Hz - 15 KHz
Magnet Wt	
Fs	
Re	7.4 ohm
Qts	0.404
Qes	0.552
Qms	1.513
Vas	5.712 litres
Xmax	
Voice Coil Dia	25 mm
SPL	90 db
Depth	67.3 mm
Baffle Opening	
Mounting	

Each \$24.16

AUDAX frame polylam. cone bass-mid

AP130G2



Outside Dia	
Mounting Each	.134 mm BC x 4
	Ψ

5-1/4" shielded polymer frame HD-A cone bass-mid

AP130Z0



Outside Dia Impedance Power Freq. Resp Magnet Wt Standard Vt Standard Standard Vt Standard Vt Standard Stand	
Mounting	134 mm BC x 4
Luon	Ψ-7.00

6-1/2" shielded polymer frame paper cone woofer

AP170M0



Outside Dia Impedance Power	8 ohm 45 W
Freq. Resp	
Magnet Wt Fs	
Re	
Qts	0.80
Qes	1.06
Qms	
Vas	17.62 litres
Xmax	
Voice Coil Dia	25 mm
SPL	87.3 db
Depth	83 mm
Baffle Opening	145 mm
Mounting	164 mm BC x 4
Each	\$43.98

<u> AUDAX</u>

5-1/4" shielded polymer frame paper cone bass-mid

AP130M0



Outside Dia	143 mm
Impedance	6 ohm
Power	40 W
Freq. Resp	
Magnet Wt	345 g
Fs	68 Hz
Re	6.2 ohm
Qts	0.56
Qes	0.73
Qms	
Vas	8.77 litres
Xmax	3.5 mm
Voice Coil Dia	25 mm
SPL	
Depth	73.5 mm
Baffle Opening	113 mm
Mounting	134 mm BC x 4
Each	\$40.64

AUDAX

6-1/2" shielded polymer frame polylam. cone woofer

AP170G2



Outside Dia	
Baffle Opening Mounting	145 mm 164 mm BC x 4
Each	\$48.46

AUDAX

6-1/2" shielded polymer frame HD-A cone woofer

AP170Z0



Outside Dia	
mpedance	6 ohm
ower	
req. Resp	
lagnet Wt	
S	
ke	
)ts	0.38
es	0.50
)ms	1.61
as	
max	3.0 mm
oice Coil Dia	30 mm
PL	
Depth	
affle Opening	
lounting	104 mm BC X 4

Each \$52.17



Sammi®

MSF165B30R1



6-1/2" shielded paper cone woofer

Outside Dia	165 mm
Impedance	8 ohm
Power	50 W
Freq. Resp	36 Hz - 6 KHz
Magnet Wt	
Fs	
Re	
Qts	0.404
Qes	0.455
Oms	
Vas	33.41 litres
Voice Coil Dia	25 mm
SPL	87.4 db
Depth	
Baffle Opening	
Mounting	

Each \$25.47

AP210G6



8" shielded polymer frame polylam. cone woofer

Outside Dia	
Impedance	6 ohm
Power	
Freq. Resp	33 Hz - 4 KHz
Magnet Wt	
Fs	33.7 Hž
Re	5.6 ohm
Qts	
Qes	0.30
Qms	3.68
Vas	79.73litres
Xmax	2.5 mm
Voice Coil Dia	
SPL	91.9 db
Depth	
Baffle Opening	186 mm
Mounting	208 mm BC x 4
C a a la	ተ ረሳ ሰላ

Each \$60.89

8" shielded polymer frame paper cone woofer

AP210M0



Outside Dia	
Impedance	8 ohm
Power	
Freq. Resp	46 Hz - 6 KHz
Magnet Wt	345 a
Fs	46.4 Hz
Re	
Qts	
Qes	
Qms	
Vas	
Xmax	
Voice Coil Dia	
SPL	90.2 db
Depth	95.5 mm
Baffle Opening	186 mm
Mounting	
Each	\$48.70

MG 820PPSH

8" shielded foam edge black poly cone woofer Outside Dia



Outside Dia	201 mm
Impedance	8 ohm
Power	50 W
Freq. Resp	
Magnet Wt	
Fs	44 Hz
Re	
Qts	1.165
Qes	1.731
Qms	3.564
Vas	40.02 litres
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	183 mm
Mounting	194 5 mm BC x 4
mounting	134.3 Hill DC X 4
Each	\$35.60

AP210Z0



8" shielded	polymer
frame HD-A con-	e woofer

Outside Dia	
Impedance	6 ohm
Power	70 W
Freq. Resp	29 Hz - 3.5 KHz
Magnet Wt	555 q
Fs	
Re	
Qts	0.32
Qes	0.36
Qms	
Vas	92.23 litres
Xmax	
Voice Coil Dia	30 mm
SPL	89.8 db
Depth	
Baffle Opening	
Mounting	208 mm BC x 4
Each	\$64.60

Sammi®

MDWR200B60



Vented Voice Coil

8" shielded foam edge poly cone DVC woofer

Outside Dia	210 mm
Impedance	2 x 6 onm
Power	2 x 60 W
Freq. Resp	34 Hz - 2.5 KHz
Magnet Wt	28 oz
Fs	34 Hz
Qts	0.489
Qes	0.720
Qms	
Vas	
Voice Coil Dia	38 mm
SPL	85.4 db
Depth	96.5 mm
Baffle Opening	
Mtq. Cntr	198 mm BC x 4

Each \$70.21

PRO SOUND TWEETERS

MG BT-1



98 mm round bullet tweeter

Outside Dia	97.8 mm
Impedance	8 ohm
Power80 W /	
Freq. Resp	2 Hz - 20 KHz
Magnet Wt	
Voice Coil Dia	25 mm
Fs	1000 Hz
Re	6.4 ohm
SPL	
Depth	66.3 mm
Baffle Opening	
Mounting	.85.7 mm BC x 4
Min. Xover	
Each	\$24.68

Ferrofluid Cooled

3" recessed flange super horn tweeter



MOTOROLA

KSN1001A

	84.8 x 84.8 mm at low frequency
	75 W
Freq. Resp	4 KHz - 27 KHz
	ceramic bimorph
SPL	94 db
Depth	74 mm
Baffle Opening	79 mm
Mtg. Cntr	100 mm BC x 4
Each	\$8.79

MG

BT-2



87 mm square bullet tweeter

87 x 87 mm
8 ohm
2 db / 2.5 KHz
2 Hz - 20 KHz
6 oz
25 mm
1000 Hz
6.4 ohm
102 db
66 mm
72mm
01 mm BC x 4
.2 KHz / 12 db
\$24.68

Ferrofluid Cooled

MOTOROLA

KSN1005A



3 " super horn tweeter

	84.8 x 84.8 mm
Impedancehigh	n at low frequency
	75 W
	4 KHz - 27 KHz
Voice Coil	ceramic bimorph
SPL	94 db
	74 mm
Baffle Opening	79 mm
Mtg. Cntr	100 mm BC x 4
Each	\$7.26

Sammi® HF200A



3 " bullet tweeter

Outside Dim	100 x 100 mm
Impedance	
Power30	
Freq. Resp	3 KHz - 20 KHz
Magnet Wt	10 oz
Voice Coil Dia	38 mm
SPL	
Dispersion	50 ⁰ conical
Depth	55 mm
Baffle Opening	90 mm
Mtg. Cntr	
Min. X-over	
Each	\$73.27

Sammi® HF250



3" slot tweeter

	100 x 100 mm
Impedance	8 ohm
	.30 Wrms @ 5 KHz
Freq. Resp	2.5 KHz - 20 KHz
	10 oz
Voice Coil Dia	38 mm
SPL	100 db
Dispersion	120 ⁰ H x 40 ⁰ V
	55 mm
	90 mm
Mtg. Cntr	107 mm BC x 4
Min. X-over	2.5 KHz / 12 db
Each	\$74.79

PRO SOUND TWEETERS

Sammi® 4-1/4" x 6-1/2" bi-radial bullet tweeter

HF200BR



Outside Dim	108 x 166 mm
Impedance	8 ohm
Power40	Wrms @ 5 KHz
Freq. Resp2	.5 KHz - 20 KHz
Magnet Wt	10 oz
Voice Coil Dia	38 mm
SPL	107 db
Dispersion	60 ⁰ H x 30 ⁰ V
Depth	72 mm
Baffle Opening	91 x 106 mm
Mtg. Cntr9	2 x 145 mm x 4
Min. X-over	2.5 KHz / 12 db
Each	\$73.27

MOTOROLA

KSN1016B



1-3/4" x 4-3/4" horn tweeter

Outside Dim	67.5 x 145 mm
Impedancehigh	nat low frequency
Power	75 W
Freq. Resp	3 KHz - 40 KHz
Voice Coil	ceramic bimorph
SPL	92 db
Depth	53 mm
	51 x 109 mm
	54 x 132 mm x 4
-	

\$8.50 Each

MOTOROLA

KSN1025B



Outside Dim79.4 x 187.3	mm
Impedancehigh at low freque	ency
Power7	5 W
Freq. Resp1.8 KHz - 30	KHz
Voice Coilceramic bimo	orph
SPL92	2 db
Depth108	mm
Baffle Opening55 x 148	
Mtg. Cntr63.5 x 171.5 mm	
•	

2" x 6" horn tweeter

Each \$11.62

MOTOROLA

KSN1141B



2" x 6" Powerline horn tweeter

Outside Dim......79.4 x 187.3 mm Impedance...high at low frequency Power.....protected to 400 W Freq. Resp1.8 KHz - 30 KHz Voice Coilceramic bimorph SPL.....92 db Depth108 mm Baffle Opening55 x 148 mm Mtg. Cntr.......63.5 x 171.5 mm x 6

Each \$16.57

FOSTER

025N47



3-1/2" pro bullet tweeter

Outside Dim	8 ohm N / 12 db / 5 KHz5 KHz - 20 KHz5 CHz5 KHz5 KHz100 db70 mm80.5 mm98.4 mm BC x 4
Min. Xover	

\$47.33 Each

FOSTER

025N27



4" pro horn tweeter

Outside Dim110 x 110 mm Impedance.....8 ohm Power120 W / 12 db / 4 KHz Freq. Resp4 KHz - 15 KHz Magnet Wt.....8 oz Voice Coil Dia.....25 mm Fs.....4 KHz Depth116.7 mm Baffle Opening......90 mm Mtg. Cntr.....150 mm BC x 4 Min. Xover.....4 KHz / 12 db

Each \$46.34

PRO SOUND TWEETERS

FOSTER

025N30



4" x 10" pro horn tweeter

Outside Dim	
Min. Xover	
Each	\$77.84

FOSTER

H025N08



6" x 7" pro horn tweeter

Each \$56.76

MIDRANGE HORNS

MG HM-100



4" x 10-1/2" exponential midrange horn

Outside Dia	107 x 268 mm
Impedance	8 ohm
Power	50 W / 12 db / 1 KHz
Freq. Resp	1 KHz - 11 KHz
	10 oz
Voice Coil D)ia25 mm
SPL	104 db
Depth	185 mm
Baffle Open	ing81 x 242 mm
Mtg. Cntr	93 x 256 mm x 10
	1 KHz / 12 db

Each \$46.87

COMPRESSION DRIVERS

MOTOROLA

KSN1197A



1" throat compression driver

Outside Dia	53.5 mm
Impedancehigh	at low frequency
Power	75 W
Freq. Resp	4 KHz - 27 KHz
Voice Coil	.ceramic bimorph
SPL	90 db
Depth	53 mm
Mounting	1-3/8" x 18 UNEF

Each

\$7.45

MOTOROLA

KSN1142A



1" throat Powerline compression driver

Outside Dia	64 mm
	71 mm
Impedance.	high at low frequency
Power	protected to 400 W
Freq. Resp.	1.8 KHz - 30 KHz
Voice Coil	ceramic bimorph
SPL	92 db
Mounting	1-3/8" x 18 UNEF
Cook	¢16.40

Each \$16.40

MOTOROLA

KSN1188A



1" throat Powerline compression driver

Outside Dia	97.8 mm
	77.8 mm
	igh at low frequency
	protected to 400 W
	800 Hz - 20 KHz
	ceramic bimorph
SPL	93 db
Mounting	1-3/8" x 18 UNEF

Each \$37.66

Sammi® SU-20M



Screw-on 1" throat compression driver

Outside Dia	80 mm
Impedance	8 ohm
Power25 W	/ / 12 db / 1.5 KHz
Freq. Resp	1.5 KHz - 15 KHz
	6.8 ohm
Magnet Wt	8 oz
Voice Coil Dia	25 mm
SPL (on horn)	104 db
Depth	84 mm
Mounting	.1-3/8" x 18 UNEF
	1.5 KHz / 12 db
Each	\$42.62

Sammi® SM35T



Screw-on 1" throat compression driver

Outside Dia	90 mm
Impedance	
Power35 W	/ 12 db / 1.5 KHz
Freq. Resp	.1.5 KHz - 16 KHz
Magnet Wt	
Voice Coil Dia	35 mm
SPL (on horn)	104 db
Depth	
Mounting	1-3/8" x 18 UNEF
Min. X-over	
Each	\$55.96

EMINENCE

MD2001-8 MD2001-16



Bolt-on 1" throat compression driver

Outside Dia	133 mm
Impedance	8 or 16 ohm
Throat Size	1 inch (25.4 mm)
Power40 V	VRMS @ 1.0 KHz
Freq. Resp	1 KHz - 15 KHz
Magnet Wt	
Voice Coil Dia	50.8 mm
Voice Coil Former	Kapton
Diaphragm Matl	Titanium
Fs	
SPL (1mW in PWT))105 db
Depth	54 mm
Min. Xover	1 KHz / 12 db
Mounting2 x 1/	4"-20 on 3" B.C.
3 x 1/4"-	20 on 2.25" B.C.

Each \$102.05

Specify 8 or 16 ohm when ordering.

COMPRESSION DRIVERS

EMINENCE

MD2001S-8 MD2001S-16



Screw-on 1" throat compression driver

Outside Dia	133 mm
Impedance	8 or 16 ohm
Throat Size1	inch (25.4 mm)
Power40 W	RMS @ 1.0 KHz
Freq. Resp	.1 KHz - 15 KHz
Magnet Wt	
Voice Coil Dia	50.8 mm
Voice Coil Former	Kapton
Diaphragm Matl	Titanium
Fs	550 Hz
SPL (1mW in PWT).	105 db
Depth	
Min Xover	1 KHz / 12 db
Mounting1-	

Each \$104.51

Specify 8 or 16 ohm when ordering.

EMINENCE

PSD2002-8 PSD2002-16



Bolt-on 1" throat compression driver

	Outside Dia	133 mm
	Impedance	8 or 16 ohm
	Throat Size	1 inch (25.4 mm)
ı	Power80 Wrms	@ 1.6 KHz/18 db
	Freq. Resp	1.5 KHz - 20 KHz
	Magnet Wt	
	Voice Coil Dia	
	Voice Coil Former	
	Diaphragm Matl	
	Fs	
	SPL (1mW in PWT)105 db
	Depth	
	Min. Xover	
	Mounting2 x 1/	
		20 on 2.25" B.C.
	J / =/ .	

Each

\$117.20

Specify 8 or 16 ohm when ordering.

EMINENCE

PSD2002S-8 PSD2002S-16



Screw-on 1" throat compression driver

Outside Dia133 mm
Impedance8 or 16 ohm
Throat Size1 inch (25.4 mm)
Power80 Wrms @ 1.6 KHz/18 db
Freq. Resp1.5 KHz - 20 KHz
Magnet Wt34 oz Voice Coil Dia50.8 mm
Voice Coil FormerKapton
Diaphragm MatlTitanium
Fs550 Hz
SPL (1mW in PWT)105 db
Depth56 mm
Min. Xover1.5 KHz / 18 db
Mounting1-3/8" x 18 UNEF

Each \$118.52

Specify 8 or 16 ohm when ordering.

EMINENCE

PSD3003-8 PSD3003-16



2" throat compression driver

Outside Dia	ZV3 MM
Impedance	8 or 16 ohm
Throat Sixe2	inch (50.8 mm)
Power100 V	
	RMS / 1,000 Hz
Freq. Resp5	00 Hz - 18 KHz
Fs	
Voice Coil Dia	76.2 mm
V.C. MatlCopper	
V.C. Former Matl	Kapton
DiaphragmFiber rei	
SPL (on horn)	
Magnet Wt	80 oz.
Depth	
Min Xover	500 Hz / 12 db
Mounting4 of 1/4'	

Each \$277.08

Specify 8 or 16 ohm when ordering.

HORN LENSES

Sammi®

ADPRT-1

Screw-on compression driver adapter

Outside Dia91 mm Depth12 mm



Driver mounting: 1-3/8" x 18 UNEF internal for screw on drivers.

Horn mounting: 2 and 3 bolt pattern, both on 3" dia. B.C. Holes tapped 1/4" x 20 UNC.

Construction: Die cast zinc alloy.

Each \$10.66

Sammi® SH150



Screw-on bi-radial horn lens

Outside Dia	150 x 150 mm
Depth	75 mm
Material	Glass filled ABS
Throat size	1 inch
Horn mounting	130 x 130 mm
Cutoff Freq	1.5 KHz
Dispersion	90° H x 90° V
Driver mounting.	Screw-on
Thread	1-3/8" x 18 UNEF
Each	\$38.46

MOTOROLA

KSN1151A



Constant directivity horn lens

Outside Dia	112 x 267 mm
Depth	167 mm
Throat size	1 inch
Cutoff Freg	1.8 KHz
	100° H x 40° V
	ABS plastic
Baffle Opening	84 x 234 mm
	96 x 250 mm x 6
Driver mounting.	1-3/8" x 18 UNEF

Each \$20.35

Sammi® SH230



Bolt-on bi-radial horn lens

Outside Dia	230 x 230 mm
Depth	166 mm
Material	Glass filled ABS
Throat size	1 inch
Cutoff Freq	
Dispersion	90° H x 90° V
Baffle Opening	
Mtg. Cntr2	205 x 205 mm x 6
Driver mounting:	2.25" BC x 3
	and 3.0" BC x 2

Each \$59.84

Sammi® SH350



Bolt-on exponential horn lens

Outside Dia	198 x 318 mm
Depth	211 mm
Material	Glass filled ABS
Throat size	1 inch
Cutoff Freq	600 Hz
Dispersion	120° H x 90° V
Baffle Opening	164 x 262 mm
Mtg. Cntr	179 x 298 mm x 8
Driver mounting.	3.0" BC x 2
-	and 3.0" BC x 3

Each \$55.28

Sammi® SH360



Bolt-on constant directivity horn lens

Outside Dia	160 x 360 mm
Depth	165 mm
Material	
Throat size	1 inch
Cutoff Freq	
Dispersion	90° H x 40° V
Baffle Opening	120 x 312 mm
Mtg. Cntr13	
Driver mounting:	2.25" BC x 3
_	and 3.0" BC x 2

Each \$64.11



HORN LENSES

MOTOROLA

Screw-on exponential horn lens

KSN1196A



Outside Dia Depth	
Throat size	
Cutoff Freq	800 Hz
Dispersion	1000 H x 400 V
Material	
Baffle Opening	
Mtg. Cntr113.	
Mounting holes	
Driver mounting	1-3/8" x 18 UNEF

Each \$21.09

Sammi® SH402



Bolt-on constant directivity horn lens

Outside Dia	175 x 450 mm
Depth	164 mm
Material	Glass filled ABS
Throat size	1 inch
Cutoff Freq	500 Hz
Dispersion	120° H x 80° V
Baffle Opening	134 x 382 mm
Mtg. Cntr15	7 x 430 mm x 10
Driver mounting	2.25" BC x 3
Each	\$55.56
	Ψ00.00

MG PH-800

Screw-on exponential horn lens

Outside Dia	158 x 418 mm
Depth	241 mm
Throat size	1 inch
Cutoff Freq	800 Hz
Dispersion	1000 H x 400 V
Material	ABS plastic
Baffle Opening	124 x 384 mm
Mtg. Cntr1	139 x 400 mm x 6
Driver mounting	1-3/8" x 18 UNEF

Each \$64.44





2" throat bolt-on constant directivity horn lens

.250 x 450 mm
230 mm
Glass filled ABS
2 inch
500 Hz
900 H x 400 V
.205 x 402 mm
x 430 mm x 10
4.0" BC x 4

Each \$97.91

PRO MIDRANGE DRIVERS

Sammi® SR100A50-4



4" cast frame pro midrange - 4 ohm

Outside Dia	119 mm
Impedance	4 ohm
Power	75 W
Freq. Resp	190 Hz - 17 KHz
Magnet Wt	
Fs	
Qts	0.95
Qes	1.21
Qms	4.41
Vas	1.0 litres
Voice Coil Dia	30 mm
SPL	
Depth	47 mm
Baffle Opening	108 mm
Mtg. Cntr	.119 mm BC x 4
Each	\$33.30

<u>AUDAX</u>

PR170M0



6-1/2" cast frame paper cone pro midrange

Outside Dia	190 mm
Impedance	8 ohm
Power	
Freq. Resp	
Magnet Wt	
Fs	
Re	
Qts	0.51
Qes	0.61
Qms	
Vas	5.52 litres
Xmax	0.5 mm
Voice Coil Dia	40 mm
SPL	100 db
Depth	
Baffle Opening	146 mm
Mtg. Cntr	

Each \$112.27

<u> AUDAX</u>

PR170Z0



6-1/2" cast frame HD-A cone midrange

Outside Dia	100 mm
Impedance	0 011111
Power	
Freq. Resp	185 Hz - 8 KHz
Magnet Wt	880 q
Fs	185 Hz
Re	6.2 ohm
Qts	
Qes	0.49
Qms	2.19
Vas	3.4 litres
Xmax	0.50 mm
Voice Coil Dia	40 mm
SPL	99 db
Depth	76 mm
Baffle Opening	
Mounting	171.8 mm BC x4

Sammi® AW165A100



Vented Voice Coil

6-1/2" cast frame paper cone pro midrange

Outside Dia	172.5 mm
Impedance	
Power	
Freq. Resp	66 Hz - 9 KHz
Magnet Wt	
Fs	
Re	
Qts	
Qes	0.395
Qms	11.50
Vas	10 14 litres
Xmax	1 0 mm
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mtg. Cntr	
rity. Cita	130 Hilli DC X 4

\$70.61

EMINENCE

ALPHA-8MRA



HT210T0

8" paper cone pro midrange

\$129.60

Each

Each \$73.22

E 8" pro sound midrange - 100 W

Each



mpedance	8 ohm
	500 Hz - 5 KHz
	20 oz
s	545 Hz
Re	7.43 ohm
.e	0.37 mH
)ts	2.07
es	2.78
)ms	8.17
as	0.61 Litres
(max	0.0 mm
oice Coil Dia	38 mm
PL	102 db
Depth	82 mm
Baffle Opening	187.3 mm
	196.9 mm BC x 4

Each \$49.10



EMINENCE LOUDSPEAKERS



EMINENCE ALPHA-6A



Vented Voice Coil

6-1/2" pro sound speaker - 100 W

Outside Dia	167.4 mm
Impedance	8 ohm
Power	100 WRMS
Freq. Resp	.110 Hz - 10 KHz
Magnet Wt	20 oz
Fs	118 Hz
Re	7.2 ohm
Le	
Qts	0.54
Qes	0.60
Qms	5.68
Vas	5.8 litres
Xmax	
Voice Coil Dia	38.1 mm
SPL	97 db
Depth	
Baffle Opening	143.5 mm
Mounting	154 mm BC x 4
3	

Each \$48.89

EMINENCE ALPHA-8A



Vented Voice Coil

8" pro sound speaker - 100 W

Outside Dia	8 ohm 100 WRMS .65 Hz - 5 KHz 20 oz .76 Hz .5.27 ohm .0.65 mH .0.53 .0.60 .4.5 .14.1 litres .3.2 mm
Xmax	3.2 mm 97 db 91 mm 181 mm

Each \$51.26

HT240T0



10" pro sound speaker - 80 W

Outside Dia	247 mm
Impedance	8 ohm
Power	80 W
Freq. Resp	
Magnet Wt	
Fs	
Re	
Qts	0.66
Qes	0.90
Qms	2.44
Vas	34.3 litres
Xmax	
Voice Coil Dia	40 mm
SPL	
Depth	103 mm
Baffle Opening	223 mm
Mtg. Cntr	237 mm BC x 4
-	

Each \$90.50

EMINENCE BETA-8A



Vented Voice Coil

(I) PIONEER®

A25GC40-51F

8" pro sound speaker - 150 W

Outside Dia	209 2 mm
Impedance	
Dowor	1 E O M/DMC
Power	
Freq. Resp	
Magnet Wt	34 oz
Fs	58 Hz
Re	6.36 ohm
Le	0.65 mH
Qts	0.34
Qes	0.36
Qms	6.54
Vas	35.4 litres
Xmax	3.0 mm
Voice Coil Dia	
SPL	97 db
Depth	
Baffle Opening	
Mounting19	
•	

Each

Each

10" pro sound – bass guitar speaker - 100 W

\$66.07

\$74.96



Vented Voice Coil

Outside Dia	8 ohm 100 Wrms 38 Hz - 3 KHz 40 oz 38 Hz
Qes	
Ve3	
Qms	1.907
Vas	88.32 litres
Xmax	3.3 mm
Voice Coil Dia	51 mm
SPL	
Depth	122 mm
Baffle Opening	
Mtg. Cntr2	244 mm BC x 4

EMINENCE ALPHA-10A



Vented Voice Coil

10" pro sound speaker - 100 W

Outside Dia	256.8 mm
Impedance	8 ohm
	100 WRMS
Freg. Resp	45 Hz - 5 KHz
Magnet Wt	20 oz
	50 Hz
Re	5.31 ohm
Le	0.66 mH
Qts	0.59
	0.66
Òms	5.21
	82.2 litres
Xmax	3.2 mm
Voice Coil Dia	38.1 mm
SPL	97 db
Depth	99 mm
Baffle Opening	231.8 mm
Mounting	.243.8 mm BC x 8

EMINENCE BETA-10A



Vented Voice Coil

10" pro sound speaker - 150 W

Outside Dia	256.8 mm
Impedance	8 ohm
Power	150 WRMS
Freq. Resp	50 Hz - 4 KHz
Magnet Wt	
Fs	
Re	
Le	
Qts	0.49
Qes	0.52
Qms	
Vas	60.1 litres
Xmax	3.0 mm
Voice Coil Dia	
SPL	98 db
Depth	
Baffle Opening	
Mounting	
3	

Each \$72.35

EMINENCE GAMMA-10A



Vented Voice Coil

10" pro sound speaker - 200 W

Outside Dia Impedance Power	8 ohm 200 WRMS
Freq. Resp	
Magnet Wt	42 OZ
Fs	63 Hz
Re	5.43 ohm
Le	0.84 mH
Qts	
Qes	
Qms	
Vas	
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mounting2	45.4 mm BC x 8

Each \$85.89

EMINENCE

DELTA-10A-8 DELTA-10B-16



Specify 8 or 16 ohm when ordering.

10" pro sound speaker - 300 W

Outside Dia	256.2 mm
Impedance	8 or 16 ohm
Power	300 WRMS
	65 Hz - 3.5 KHz
Magnet Wt	56 oz
Fs	66 Hz
Re	.5.42 or 11.4 ohm
	0.74 mH
Qts	0.33
Qes	0.35
Qms	6.53
Vas	30.5 litres
Xmax	1.6 mm
Voice Coil Dia	63.5 mm
SPL	99 db
	108 mm
	229.7 mm
	.245.4 mm BC x 8
•	

Each \$93.70

EMINENCE GAMMA PRO-10A



Vented Voice Coil

10" pro sound speaker cast frame - 200 W

Impedance	8 ohm 200 WRMS
	60 Hz - 3.5 KHz
	56 oz
	63 Hz
	5.3 ohm
	0.60 mH
	0.35
Λος	0.39
Ome	4.10
Vac	35 litres
Vmay	3.2 mm
	63.5 mm
	100 db
	108 mm
	231.8 mm

Each \$135.64

EMINENCE

KAPPA PRO-10A



Vented Voice Coil

10" pro sound speaker cast frame - 400 W

Outside Dia Impedance Power	8 ohm
Freq. Resp	
Magnet Wt	
Fs	
Re	6.5 ohm
Le	
Qts	0.20
Qes	
Qms	10.1
Vas	52.2 litres
Xmax	
Voice Coil Dia	76.2 mm
SPL	97 db
Depth	110 mm
Baffle Opening	231.8 mm
Mounting24	4.5 mm BC x 8

Each \$139.70



Sammi® ME300B100



Vented Voice Coil

12" pro sound speaker - 100 W

Outside Dia Impedance Power	8 ohm
Freq. Resp	
Magnet Wt	
Fs	
Qts	0.37
Qes	0.388
Qms	7.97
Vas	
Voice Coil Dia	51 mm
SPL	98 db
Depth	121 mm
Baffle Opening	
Mtg. Cntr	

Each	\$89.92

(I) PIONEER®

A30GC50-52F



Vented Voice Coil

12" pro sound speaker - 150 W

Outside Dia	
Impedance	8 ohm
Power	
Freq. Resp	50 Hz - 5 KHz
Magnet Wt	50 oz
Fs	50 Hz
Re	
Qts	0.43
Qes	0.49
Qms	3.62
Vas	100.8 litres
Xmax	3.3 mm
Voice Coil Dia	51 mm
SPL	96 db
Depth	
Baffle Opening	279 mm
Mtg. Cntr	293 mm BC x 8

Each \$92.82

EMINENCE ALPHA-12A



12" pro sound speaker - 100 W

Outside Dia	
Impedance	8 ohm
Power	100 WRMS
Freq. Resp	
Magnet Wt	20 oz
Fs	49 Hz
Re	6.3 ohm
Le	0.79 mH
Qts	0.77
Qes	
Qms	6.53
Vas	121.5 litres
Xmax	2.4 mm
Voice Coil Dia	
SPL	
Depth	120 mm
Baffle Opening	
Mounting29	
3	

Each \$63.66

EMINENCE BETA-12A



Vented Voice Coil

12" pro sound speaker - 150 W

Impedance	310.9 mm 8 ohm 150 WRMS
	50 Hz - 5 KHz
Magnet Wt	34 oz
Fs	50 Hz
Re	7.07 ohm
Le	0.84 mH
Qts	0.52
Qes	0.57
Qms	5.82
Vas	114.7 litres
Xmax	0.8 mm
	50.8 mm
SPL	100 db
Depth	113.5 mm
	278.6 mm
	.295.3 mm BC x 8

Each \$74.50

EMINENCE 12" pro sound twin cone speaker - 150 W

BETA-12LTA



Vented Voice Coil

Outside Dia	305.2 mm
Impedance	8 ohm
Power	150 WRMS
Freq. Resp	
Magnet Wt	
Fs	
Re	7.37 ohm
Le	0.83 mH
Qts	0.51
Qes	
Qms	6.44
Vas	
Xmax	0.8 mm
Voice Coil Dia	50.8 mm
SPL	99 db
Depth	113.5 mm
Baffle Opening	278.6 mm
Mounting	295.3 mm BC x 8

Each \$76.23

EMINENCE

GAMMA-12A



Vented Voice Coil

12" pro sound speaker - 200 W

Outside Dia Impedance Power Freq Resp Fs Re Le	8 ohm 55 Hz - 5 KHz 55 Hz - 5 KHz 57 Hz 6.52 ohm 0.95 mH
Qts	0.67
Qes	
Qms	
Vas	
Xmax	1.6 mm
Voice Coil Dia SPL	
Depth	
Baffle Opening Mounting	278.6 mm

Each \$90.35

PRO WOOFERS MUSICAL INSTRUMENT

EMINENCE

DELTA-12A-8 DELTA-12B-16



Specify 8 or 16 ohm when ordering.

12" pro sound speaker - 300 W

305.2 mm
8 or 16 ohm
300 WRMS
55 Hz - 5 KHz
56 oz
55 Hz
6.3 or 11.4 ohm
0.74 mH
0.43
0.46
5.27
81.3 litres
1.6 mm
63.5 mm
100 db
118.3 mm
278.6 mm
295.3 mm BC x 8

Each	\$97.93
⊏aUII	Φ97.93

EMINENCE DELTA-12LFA



Vented Voice Coil

12" pro sound bass speaker - 300 W

	305.2 mm
Impedance	8 ohm
Power	300 WRMS
Freq. Resp	35 Hz - 3 KHz
Magnet Wt	56 oz
Fs	45 Hz
Re	6.06 ohm
Le	1.45 mH
	0.42
Qes	0.45
Qms	7.28
Vas	95.5 litres
Xmax	4.8 mm
Voice Coil Dia	63.5 mm
SPL	97 db
Depth	118.3 mm
Baffle Opening	280.7 mm
Mounting	295.3 mm BC x 8

Each \$113.69

EMINENCE KAPPA-12A



Vented Voice Coil

12" pro sound speaker - 400 W

Outside DiaImpedancePower	8 ohm
Freq. Resp	40 Hz - 4 KHz
Magnet Wt	80 oz
Fs	45 Hz
Re	5.41 ohm
Le	0.77 mH
Qts	
Qes	
Qms	
Vas	
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mounting2	
- · · · · · · · · · · · · · · · · · · ·	

Outside Dia	311.7 mm
Impedance	8 ohm
Power	400 WRMS
Freq. Resp	.40 Hz - 4 KHz
Magnet Wt	80 oz
Fs	45 Hz
Re	5.41 ohm
Le	0.77 mH
Qts	0.27
Qes	
Qms	
Vas	
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	280 mm
Mounting296	5.8 mm BC x 8
· · · · · · · · · · · · · · · · · · ·	

Each \$145.46

EMINENCE

GAMMA PRO-12A



Vented Voice Coil

12" pro sound speaker cast frame - 200 W

Outside Dia Impedance Power	8 ohm
Freq. Resp	
Magnet Wt	56 oz
Fs	54 Hz
Re	5.7 ohm
Le	0.75 mH
Qts	0.45
Qes	0.48
Qms	6.56
Vas	86 litres
Xmax	3.2 mm
Voice Coil Dia	63.5 mm
SPL	100 db
Depth	
Baffle Opening	283.2 mm
Mounting29	

Each \$162.79

EMINENCE

GAMMA PRO-12CXA



*Note: High frequency driver not included. Eminence recommends using a PSD-2002S (8 ohm) compression driver and a px-ii 1K6 crossover with this speaker.

12" pro sound co-axial speaker - 200 W

Outside Dia	314.3 mm
	8 ohm
	200 W
	55 Hz - 20 KHz
Magnet Wt	56 oz
Fc	61 Hz
15	0.60 mH
Le	
Re	5.7 ohm
Qts	0.41
Oes	0.43
	6.70
Vas	81 litres
	2.4 mm
	63.5 mm
	100 db
+· =	191 mm
Baffle Opening	283.2 mm
Mounting	293.7 mm BC x 8

Each

EMINENCE

KAPPA PRO-12A



Vented Voice Coil

12" pro sound speaker cast frame - 400 W

Outside Dia	314.3 mm
Impedance	8 ohm
Power	400 WRMS
Freq. Resp	35 Hz - 2.5 KHz
Magnet Wt	80 oz
Fs	
Re	5.46 ohm
Le	1.22 mH
Qts	0.24
Qes	
Qms	
Vas	
Xmax	4.8 mm
Voice Coil Dia	76.2 mm
SPL	
Depth	
Baffle Opening	
Mounting	

Each \$155.88

\$268.71



EMINENCE LATERA





Vented Voice Coil

12" pro sound speaker twin spider - 400 W

Outside Dia Impedance	8 ohm
Power	400 WRMS
Freq. Resp	44 Hz - 2.8 KHz
Magnet Wt	
Fs	
Le	
Re	
Qts	
Qes	
Qms	
Vas	
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mounting	293.7 mm BC x 8

Sammi® ME380B200



Vented Voice Coil

15" pro sound speaker - 200 W

Outside Dia	
Vas	157.8 litres 99 db 152 mm 357 mm

Each \$93.64

EMINENCE ALPHA-15A



Vented Voice Coil

15" pro sound speaker - 100 W

Outside Dia	384.8 mm
Impedance	8 ohm
Power	100 WRMS
Freq. Resp	40 Hz - 4 KHz
Magnet Wt	25 oz
Fs	41 Hz
Re	5.88 ohm
Le	0.84 mH
Qts	1.26
	1.53
Qms	7.23
Vas	260 litres
	3.8 mm
Voice Coil Dia	38.1 mm
SPL	98 db
Depth	148 mm
Baffle Opening	349.6 mm
Mounting	.369.9 mm BC x 8

Each \$74.50

EMINENCE

OMEGA PRO-12A



Vented Voice Coil

12" pro sound speaker cast frame - 600 W

Outside Dia	
Impedance	8 ohm
Power	600 WRMS
Freg. Resp	35 Hz - 1.2 KHz
Magnet Wt	109 oz
	39 Hz
Re	
Le	1.39 mH
Qts	0.30
Qes	0.32
Qms	8.08
Vas	88.4 litres
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	281 mm
Mounting	.293.8 mm BC x 8

Each \$242.79

(I) PIONEER®

A38GC50-54F



Vented Voice Coil

15" pro sound speaker - 150 W

Outside Dia	
Impedance	8 ohm
Power	150 Wrms
Freq. Resp	50 Hz - 5 KHz
Magnet Wt	
Fs	40 Hz
Re	7.2 ohm
Qts	0.59
Qes	0.69
Qms	4.09
Vas	241 litres
Xmax	3.3 mm
Voice Coil Dia	
SPL	96 db
Depth	156 mm
Baffle Opening	
Mtg. Cntr	
3	

Each \$117.66

EMINENCE

BETA-15A



Vented Voice Coil

15" pro sound speaker - 150 W

Outside Dia Impedance	
Power	150 WRMS
Freq. Resp	35 Hz - 4 KHz
Magnet Wt	34 02
Fs	35 Hz
Re	6.32 ohm
Le	1.10 mF
Qts	0.58
Qes	0.63
Qms	8.10
Vas	
Xmax	4.0 mm
Voice Coil Dia	
SPL	98 dt
Depth	
Baffle Opening	
Mounting36	9.9 mm BC x 8

Each \$83.79



EMINENCE GAMMA-15A



Vented Voice Coil

15" pro sound speaker - 200 W

Outside Dia	
Impedance	8 ohm
Power	200 WRMS
Freq. Resp	35 Hz - 4.5 KHz
Magnet Wt	
Fs	
Re	
Le	
Qts	0.88
Oes	
Òms	8.36
Vas	
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mounting	
	JOJ.J HIIII DC X U

Each \$98.61

EMINENCE

DELTA-15A-8 DELTA-15B-16



Specify 8 or 16 ohm when ordering.

15" pro sound speaker - 300 W

Outside DiaImpedance	
Power	
Freq. Resp	
Magnet Wt	56 oz
Fs	
Re	6.9 or 11.9 ohm
Le	0.86 mH
Qts	0.49
Qes	0.54
Qms	6.56
Vas	293 litres
Xmax	2.7 mm
Voice Coil Dia	63.5 mm
SPL	101 db
Depth	153.6 mm
Baffle Opening	349.6 mm
Mounting	369.9 mm BC x 8
	A 4 6 6 6 F

Each \$106.35

EMINENCE KAPPA-15A



Vented Voice Coil

15" pro sound speaker - 400 W

Outside Dia384.9 mm
Impedance8 ohm
Power400 WRMS
Freq. Resp30 Hz - 2.5 KHz
Magnet Wt80 oz
Fs36 Hz
Re5.21 ohm
Le1.05 mH
Qts
Qes0.31
Qms10.60
Vas278 litres
Xmax1.6 mm
Voice Coil Dia76.2 mm
SPL103 db
Depth155 mm
Baffle Opening349.6 mm
Mounting369.9 mm BC x 8
Š

Each \$168.79

EMINENCE KAPPA-15LFA



Vented Voice Coil

15" pro sound bass speaker - 400 W

Outside Dia	
Impedance	8 ohm
Power	400 WRMS
Freq. Resp	35 Hz - 3 KHz
Magnet Wt	96 oz
Fs	39 Hz
Re	5.4 ohm
Le	1.27 mH
Qts	0.38
Qes	
Qms	6.08
Vas	159 litres
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mounting36	9.9 mm BC x 8
-	

EMINENCE

KAPPA PRO-15A



Vented Voice Coil

15" pro sound speaker cast frame - 400 W

\$173.63

Each

Outside Dia	389 mm
	8 ohm
ower	400 WRMS
req. Resp	40 Hz - 4 KHz
Magnet Wt	80 oz
s	47 Hz
	5.23 ohm
_e	1.01 mH
Qts	0.38
Qes	0.40
Qms	8.01
/as	167.7 litres
	3.2 mm
/oice Coil Dia	76.2 mm
	103 db
	154 mm
Baffle Opening	355.5 mm
Mounting	369.9 mm BC x 8

Each \$168.58

EMINENCE GAMMA PRO-15CXA



*Note: High frequency driver not included. Eminence recommends using a PSD-2002S (8 ohm) compression driver and a px-ii 1K6 crossover with this speaker.

15" pro sound co-axial speaker - 200 W

	389 mm
Impedance	8 ohm
Power	200 WRMS
	45 Hz - 20 KHz
	56 oz
Fs	47 Hz
Re	5.8 ohm
	0.82 mH
Ots	0.59
	0.65
	6.55
	225 litres
Xmax	4.0 mm
Voice Coil Dia	63.5 mm
	101 db
Depth	210 mm
Baffle Opening	359 mm
Mounting	369.9 mm BC x 8

Each

\$270.19



EMINENCE KAPPA PRO-15LFA



Vented Voice Coil

EMINENCE

OMEGA PRO-15A

15" pro sound bass speaker cast frame-400W

Outside Dia	389 mm
Impedance	8 ohm
Power	400 Wrms
Freq. Resp	.40 Hz - 4 KHz
Magnet Wt	95 oz
Fs	46 Hz
Re	5.5 ohm
Le	
Qts	0.38
Qes	0.39
Qms	7.90
Vas	127.5 litres
Xmax	4.8 mm
Voice Coil Dia	76.2 mm
SPL	100 db
Depth	167 mm
Baffle Opening	
Mounting36	9.9 mm BC x 8

Each \$182.14

15" pro sound speaker cast frame - 600 W



Vented Voice Coil

EMINENCE 18" pro sound speaker - 400 W



Vented Voice Coil

Outside Dia Impedance Power Freq. Resp Magnet Wt Fs	8 ohm25 Hz - 500 Hz25 Hz - 500 Hz28 Hz28 Hz
Le	
Qts	
Qes	0.43
Qms	7.84
Vas	475.7 litres
Xmax	4.8 mm
Voice Coil Dia SPL	97 db
Depth	
Baffle Opening Mounting	

Each \$208.40

EMINENCE

KAPPA PRO-15TSA



Vented Voice Coil

15" pro sound speaker twin spider - 400 W

389 mm
8 ohm
400 W
34 Hz - 3.5 KHz
80 oz
36.7 Hz
6.43 ohm
1.61 mH
0.40
0.41
19.58
163.1 litres
6.00 mm
76.2 mm
95 db
163 mm
355.5 mm
69.9 mm BC x 8
\$191.28

EMINENCE 15" pro sound speaker cast frame - 1,000 W

KILOMAX PRO-15A



Vented Voice Coil

Outside Dia	386.4 mm
Impedance	8 ohm
Power	1.000 WRMS
Freq. Resp	35 Hz - 1.5 KHz
Magnet Wt	109 oz
Fs	41 Hz
Re	
Le	
Qts	0.39
Qes	0.40
Qms	8.80
Vas	154.5 litres
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mounting	369.9 mm BC x 8
Each	\$347.85

EMINENCE

SIGMA PRO-18A



Vented Voice Coil

18" pro sound speaker cast frame - 500 W

Outside Dia	
Qts	0.29
Qes	
Qms	
Vas	441.2 litres
Xmax	6.0 mm
Voice Coil Dia	
SPL	
Depth	207 mm
Baffle Opening	
Mounting4	138.2 mm BC x 8

Each \$257.97



MUSICAL INSTRUMENT

EMINENCE OMEGA PRO-18A

18" pro sound speaker cast frame - 600 W

Outside Dia Impedance Power	8 ohm 600 WRMS
Freq. Resp	25 Hz - 2 KHz
Magnet Wt	109 oz
Fs	28 Hz
Re	5.1 ohm
Le	1.67 mH
Qts	0.24
Qes	0.25
Qms	
Vas	354 litres
Xmax	
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mounting43	
J	



18" pro sound speaker

\$283.36

\$415.06

Each

Each

KILOMAX PRO-18A

EMINENCE



Vented Voice Coil

cast frame - 1,000 W

Outside Dia Impedance Power	8 ohm 1,000 WRMS
Freq. Resp	
Magnet Wt	109 oz
Fs	33 Hz
Re	5.84 ohm
Le	2.38 mH
Qts	0.56
Qes	0.58
Qms	14.24
Vas	239.9 litres
Xmax	9.8 mm
Voice Coil Dia	
SPL	
Depth	
Baffle Opening	
Mounting4	
3	

EMINENCE

OMEGA PRO-18LFA



Vented Voice Coil

18" pro sound bass speaker cast frame-600W

Outside Dia	457.2 mm
Impedance	8 ohm
	600 WRMS
	30 Hz - 2.5 KHz
	109 oz
	33 Hz
	5.67 ohm
	2.13 mH
	0.56
	0.60
•	9.75
	247 litres
	9.8 mm
	101.6 mm
	94 db
	214 mm
	420.5 mm
	.438.2 mm BC x 8
Mounting	430.2 IIIII DC X 0

Each \$283.36

GENUINE EMINENCE RECONE KITS

You asked for them and now we got them. Factory original recone kits for Eminence cast frame loudspeakers. Most cast frame types are represented here but if you don't see yours please give us a call.

For speaker: Recone kit number: **Price GAMMA PRO Series** Gamma Pro-10A Gamma Pro-10ARK \$35.56 ea. Gamma Pro-12ARK Gamma Pro-12A \$44.55 ea. Gamma Pro-12CXA Gamma Pro-12CXARK \$54.04 ea. Gamma Pro-15CXA Gamma Pro-15CXARK \$50.19 ea. **KAPPA PRO Series** Kappa Pro-10A Kappa Pro-10ARK \$38.55 ea. Kappa Pro-12A Kappa Pro-12ARK \$49.82 ea. Kappa Pro-15ARK Kappa Pro-15A \$56.19 ea. Kappa Pro-15LFA Kappa Pro-15LFARK \$54.56 ea.

These kits will ensure that you get the same high quality original parts and the same great performance.

Note: Recone kits carry no warranty after installation.

For speaker:	Recone kit number:	Price	
SIGMA PRO Series			
Sigma Pro-18A	Sigma Pro-18ARK	\$79.79 ea.	
OMEGA PRO Set	ies		
Omega Pro-12A	Omega Pro-12ARK	\$68.97 ea.	
Omega Pro-15A	Omega Pro-15ARK	\$67.65 ea.	
Omega Pro-18A	Omega Pro-18ARK	\$91.65 ea.	
KILOMAX Series			
Kilomax-15A	Kilomax-15ARK	\$71.75 ea.	
Kilomax-18A	Kilomax-18ARK	\$118.51 ea.	



EMINENCE LEGEND GUITAR SPEAKERS



EMINENCE LEGEND GUITAR SPEAKERS

EMINENCE

LEGEND 102-8 LEGEND 102-16



Specify 8 or 16 ohm when ordering.

10" Alnico magnet guitar speaker - 20 W

Outside Dia	254.3 mm
VC Imp/Dia8 or	16 ohm/25.4 mm
	20 WRMS
Coil Wire	Round Copper
	Paper
Surround Matl	Paper
Dust Cap Matl	Felt
Magnet	6 oz ALNICO
Freq. Resp	100 Hz - 6 KHz
Fs	100 Hz
SPL	97 db
Re	.5.87 or 11.3 ohm
Le	0.48 mH
Sd	344.9 sqcm
Xmax	2.0 mm
Baffle Opening	229.9 mm
Mounting	.243.8 mm BC x 8
	123 mm

83.	1	2
	83.	83.1

EMINENCE

LEGEND 105-8 LEGEND 105-16



Specify 8 or 16 ohm when ordering.

10" guitar speaker - 50 W

Outside Dia	256.8 mm
VC Imp/Dia 8 or	16 ohm/38.1 mm
	50 WRMS
Coil Wire	Round Copper
Former Matl	Kapton
Surround Matl	Paper
Dust Cap Matl	Felt
Magnet	16 oz Ceramic
Freq. Resp	100 Hz - 6 KHz
Fs	100 Hz
SPL	98 db
Re	7.49 or 12.3 ohm
Le	0.56 mH
Sd	344.9 sqcm
Xmax	0.0 mm
	235 mm
Mounting	.243.8 mm BC x 8
	103 mm

Each \$61.82

EMINENCE

LEGEND 122-8 LEGEND 122-16



Specify 8 or 16 ohm when ordering.

12" Alnico magnet guitar speaker - 20 W

VC Imp/Dia8 o Power	306.1 mm r 16 ohm/25.4 mm 20 WRMS
	Round Copper
	Paper
Surround Matl	Paper
Dust Cap Matl	Zurette
Magnet	6 oz ALNICO
Freq. Resp	80 Hz - 5.5 KHz
	80 Hz
	97 db
Re	6.86 or 11.1 ohm
	0.58 mH
	506.7 sqcm
	2.0 mm
	280.9 mm
	295.3 mm BC x 8
	145 mm
Depart	

Each \$87.83

EMINENCE LEGEND 121-8



12" guitar speaker - 100 W

Outside Dia	305.2 mm
VC Imp/Dia	8 ohm/50.8 mm
Power	100 WRMS
Coil Wire	
Former Matl	
Surround Matl	
Dust Cap Matl	
Magnet	
Freq. Resp	80 Hz - 5 KHz
Fs	
SPL	
Re	6 95 ohm
Le	0.60 mH
Sd	506.7 cacm
Vmov	0 0 mm
Xmax	270.6
Baffle Opening	2/8.0 [11][1
Mounting	295.3 mm BC x 8
Depth	114 mm

EMINENCE LEGEND 125-8



12" guitar speaker - 50 W

Outside Dia	305.2 mm
VC Imp/Dia	8 ohm/38.1 mm
Power	50 WRMS
Coil Wire	Round Copper
Former Matl	Kapton
Surround Matl	Paper
Dust Cap Matl	Paper
Magnet	34 oz Ceramic
Freq. Resp	80 Hz - 5 KHz
	80 Hz
SPL	102 db
	7.2 ohm
Le	0.70 mH
	506.7 sqcm
	0.50 mm
Baffle Opening	278.6 mm
Mounting	295.3 mm BC x 8
	124 mm

Each \$64.58

EMINENCE

LEGEND V12-8 LEGEND V12-16



12" vintage sound guitar speaker - 80 W

\$97.64

Each

Outside Dia	305.2 mm
VC Imp/Dia8 or	16 ohm/44.5 mm
Power	80 WRMS
Coil Wire	Round Copper
Former Matl	Kapton
	Paper
Dust Cap Matl	Felt
Magnet	38 oz Ceramic
	80 Hz - 4.5 KHz
Fs	80 Hz
	101 db
	6.37 or 11.4 ohm
	0.64 mH
	519.5 sqcm
	0.8 mm
Baffle Opening	278.6 mm
	.295.3 mm BC x 8
Depth	154 mm

Each \$104.47



EMINENCE LEGEND GUITAR SPEAKERS

EMINENCE

LEGEND GB12-8 LEGEND GB12-16



12" green back guitar speaker - 50 W

Outside Dia	305.2 mm
VC Imp/Dia8 o	r 16 ohm/44.5 mm
Power	50 WRMS
Coil Wire	Round Copper
Former Matl	Paper
Surround Matl	Paper
Dust Cap Matl	Zurette
Magnet	38 oz Ceramic
Freq. Resp	80 Hz - 5.5 KHz
	80 Hz
SPL	102 db
Re	6.37 or 11.8 ohm
Le	0.64 mH
Sd	506.7 sqcm
Xmax	8 mm
Baffle Opening	278.6 mm
Mounting	295.3 mm BC x 8
	154 mm

Each \$92.55

EMINENCE

LEGEND M12-8 LEGEND M12-16



12" modern lead guitar speaker - 80 W

Outside Dia	305.2 mm
VC Imp/Dia8 o	r 16 ohm/44.5 mm
Power	80 WRMS
Coil Wire	Round Copper
Former Matl	Kapton
Surround Matl	Paper
Dust Cap Matl	Zurette
Magnet	38 oz Ceramic
	80 Hz - 5 KHz
	80 Hz
SPL	102 db
Re	6.36 or 11.8 ohm
Le	0.59 mH
Sd	506.7 sqcm
Xmax	
Baffle Opening	278.6 mm
Mounting	295.3 mm BC x 8
	154 mm
•	

Each \$89.54

EMINENCE LEGEND 151-8



15" guitar speaker - 100 W

	384.8 mm
VC Imp./Dia	8 ohm/50.8 mm
Power	100 WRMS
	Round Copper
Former Matl	Kapton
Surround Matl	Paper
Dust Cap Matl	Zurette
Magnet	59 oz Ceramic
Freq. Resp	80 Hz - 5 KHz
	80 Hz
SPL	100 db
Re	7.16 ohm
	0.86 mH
Sd	823.7 sqcm
Xmax	0.8 mm
Baffle Opening	349.6 mm
Mounting	369.9 mm BC x 8
Depth	154 mm

Each \$102.09

EMINENCE LEGEND B15-8



Vented Voice Coil

15" bass guitar speaker - 300 W

Outside Dia	384.9 mm
VC Imp./Dia	8 ohm/76.2 mm
	300 WRMS
Coil Wire	Round Aluminum
Former Matl	Kapton
Surround Matl	Ċloth
	Paper
Magnet	95 oz Ceramic
Freq. Resp	48Hz - 4 KHz
Fs	48 Hz
	100 db
Re	6.55 ohm
Le	0.51 mH
	856.3 sqcm
	0.3 mm
Baffle Opening	349.6 mm
Mounting	.369.9 mm BC x 8
	157 mm

Each \$152.53

McBride

LINEAR B 4.5



4-1/2" foam edge black poly cone fullrange

Outside Dia	
Impedance	8 ohm
Power	
Freq. Resp	67 Hz - 15 KHz
Magnet Wt	6 oz
Fs	67 Hz
Qts	0.55
Qes	
Qms	
Vas	7.21 litres
Voice Coil Dia	25 mm
SPL	90 db
Depth	50 mm
Baffle Opening	
Mtg. Cntr	119 mm BC x 4
-	

\$25.66

(!) PIONEER®

A11EC80-02F



4-1/2" cloth edge paper cone fullrange

Outside Dim	128 x 128 mm
Impedance	8 ohm
Power	
Freq. Resp	70 Hz - 15 KHz
Magnet Wt	
Fs	70 Hz
Re	
Qts	0.35
Qes	
Qms	
Vas	
Xmax	1.1 mm
Voice Coil Dia	
SPL	90 db
Depth	55 mm
Baffle Opening	
Mtg. Cntr	
Each	\$18.73

MISCO_®

5" cloth edge paper cone P.A. speaker

Each



Outside Dia	127 mm
Impedance	8 ohm
Power	20 W
Freq. Resp	60 Hz - 12 KHz
Magnet Wt	10 oz
Fs	85 Hz
Voice Coil Dia	25 mm
SPL	93 db
Depth	52.4 mm
Mtg. Cntr	119 mm BC x 4
-	

Each \$21.23

McBride LINEAR A 5.5



5-1/4" fullrange car door speaker - 8 ohm

Outside Dim134 x 134 mm Impedance8 ohm
Power25 W
Freq. Resp30 Hz - 18 KHz
Magnet Wt10 oz
Fs55 Hz
Voice Coil Dia25 mm
SPL90 db
Depth55 mm
Baffle Opening123 mm
Mtg. Cntr139 mm BC x 4
Pair \$61.27

McBride

LINEAR B 5.5



5-1/4" foam edge paper cone fullrange

Outside Dim	134 x 134 mm
Impedance	8 ohm
Power	35 W
Freq. Resp	63 Hz - 18 KHz
Magnet Wt	10 oz
Fs	63 Hz
Qts	0.40
Qes	0.42
Qms	
Vas	
Voice Coil Dia	
SPL	90.5 db
Depth	61 mm
Baffle Opening	123 mm
Mtg. Cntr	

Each \$33.31

Marsland

PACER 6



6" damped edge paper cone fullrange

Outside Dim	
Power	20 W
Freq. Resp	100 Hz - 15 KHz
Magnet Wt	10 oz
Fs	124 Hz
Re	6.1 ohm
Qts	0.876
Qes	1.070
Qms	4.850
Vas	6.17 litres
Voice Coil Dia	25 mm
SPL	92.3 db
Depth	56.5 mm
Baffle Opening	
Mtg. Cntr	

Each \$25.40

McBride

LINEAR B 6.5



6-1/2" foam edge paper cone fullrange

	167 mm
Impedance	8 ohm
	35 W
	49 Hz - 18 KHz
Magnet Wt	10 oz
	49 Hz
Qts	0.56
	0.69
	7.77
Vas	23.2 litres
Voice Coil Dia	25 mm
SPL	88 db
Depth	71 mm
	143 mm
	156 mm BC x 4

\$33.72

\$40.45

McBride

8LS809-14



8" deep frame wide dispersion fullrange

Outside Dia	212 mm
Impedance	8 ohm
Power	20 W
Freq. Resp	.70 Hz - 12 KHz
Magnet Wt	10 oz
Fs	
Re	6.25 ohm
Qts	1.182
Qes	1.324
Qms	
Vas	16.1 litres
Voice Coil Dia	
SPL	93 db
Depth	
Baffle Opening	187 mm
Mtg. Cntr	195 mm BC x 4
Each	\$17.03

McBride

CAVALIER 8



8" foam edge paper cone fullrange

Each

Each

Each

Outside Dia	
Impedance	
Power	30 W
Freq. Resp	40 Hz - 18 KHz
Magnet Wt	10 oz
Fs	40 Hz
Voice Coil Dia	25 mm
SPL	92 db
Depth	82 mm
Baffle Opening	183 mm
Mtg. Cntr	.195 mm BC x 8

McBride LINEAR B 8.0



8" foam edge paper cone fullrange

Outside Dia	208 mm
Impedance	
Power	
Freq. Resp	
Magnet Wt	10 oz
Fs	41 Hz
Qts	
Qes	
Qms	
Vas	
Voice Coil Dia	
SPL	89 db
Depth	84 mm
Baffle Opening	
Mtg. Cntr	195 mm BC x 8
Each	¢40.4E
⊏au⊓	\$40.45

McBride

MCWR8A



8" high power cloth edge paper cone fullrange

Outside Dia	
Impedance	8 ohm
Power	
Freq. Resp	44 Hz - 16 KHz
Magnet Wt	
Fs	44 Hz
Qts	0.38
Qes	0.45
Qms	2.40
Vas	
Voice Coil Dia	38 mm
SPL	92 db
Depth	
Baffle Opening	183 mm
Mtg. Cntr	

McBride PRINCESS 8



8" doped edge paper cone fullrange

	208 mm
Impedance	8 ohm
	20 W
Freq. Resp	70 Hz - 18 KHz
	10 oz
	70 Hz
Voice Coil Dia	25 mm
SPL	93 db
	82 mm
Baffle Opening	183 mm
Mtg. Cntr	195 mm BC x 8
Each	\$28.46

\$52.52

Marsland

SUPER PACER 8WW



8" damped edge	
al cone P.A.	speaker
Outside Dim	191 x 191 mm

Outside Dim	191 x 191 mm
Impedance	8 ohm
Power	20 W
Freq. Resp	50 Hz - 16 KHz
Magnet Wt	10 oz
Fs	70 Hz
Voice Coil Dia	25 mm
SPL	98 db
Depth	74 mm
Mtg. Cntr	193 mm BC x 4
Each	\$26.87

(!) PIONEER

B20FU20-51FW



8" foam edge dual cone fullrange

mm
ohm
50 W
KHz
20 oz
6 Hz
0.25
0.29
1.79
itres
mm
4 db
mm
mm
C x 4
99

McBride

CAVALIER 10



10" foam edge paper cone fullrange

Outcido Dia

	237 111111
Impedance	8 ohm
	30 W
Freq. Resp	35 Hz - 18 KHz
Magnet Wt	12 oz
Fs	35 Hz
Voice Coil Dia	25 mm
	92 db
Depth	106 mm
Baffle Opening	235 mm
Mtg. Cntr	248 mm BC x 8
Each	\$44.96

Sammi® ME08B50



8" twin cone pro sound speaker

Outside Dia	
Impedance	8 ohm
Power	
Freq. Resp	53 Hz - 12 KHz
Magnet Wt	25 oz
Fs	53 Hz
Qts	0.364
Qes	0.387
Qms	6.17
Vas	30.2 litres
Voice Coil Dia	51 mm
SPL	96 db
Depth	82.5 mm
Baffle Opening	
Mtg. Cntr	

Each \$51.28

McBride

MCWR10A



10" high power cloth edge paper cone fullrange

Outside Dia	257 mm
Impedance	8 ohm
Power	
Freq. Resp	37 Hz - 16 KHz
Magnet Wt	20 oz
Fs	37 Hz
Ots	0.41
Qes	0.48
Qms	
Vas	
Voice Coil Dia	
SPL	98 db
Depth	
Baffle Opening	235 mm
Mtg. Cntr	

Each \$61.43

Marsland

PACER 10



10" paper edge paper cone fullrange

	257 mm
Impedance	8 ohm
Power	20 W
Freq. Resp	75 Hz - 11 KHz
	10 oz
Fs	75 Hz
Voice Coil Dia	25 mm
SPL	96 db
Depth	106 mm
Baffle Opening	235 mm
Mtg. Cntr	248 mm BC x 8
Each	\$37.38



McBride

PRINCESS 10



10" doped edge paper cone fullrange

Outside Dia	257 mm
Impedance	8 ohm
Power	
Freq. Resp	70 Hz - 18 KHz
Magnet Wt	10 oz
Fs	70 Hz
Voice Coil Dia	25 mm
SPL	92 db
Depth	106 mm
Baffle Opening	235 mm
Mtg. Cntr	
Each	\$41.38

McBride

CAVALIER 12



12" foam edge paper cone fullrange

Outside Dia	310.5 mm 8 ohm
	30 W
	30 Hz - 18 KHz
	12 oz
Fs	30 Hz
Voice Coil Dia	25 mm
SPL	90 db
Depth	120 mm
Baffle Opening	282 mm
Mtg. Cntr	298 mm BC x 8
Each	\$52.26

McBride

MCWR12A



12" high power cloth edge paper cone fullrange

Outside Dia	310.5 mm
Impedance	8 ohm
Power	75 W
Freq. Resp	40 Hz - 15 KHz
Magnet Wt	20 oz
Fs	40 Hz
Voice Coil Dia	38 mm
SPL	98 db
Depth	123 mm
Baffle Opening	282 mm
Mtg. Cntr	
Each	\$63.32

Marsland

PACER 12



12" paper edge paper cone fullrange

Outside Dia	8 ohm20 W65 Hz - 11 KHz10 oz65 Hz25 mm25 mm25 db
Depth Baffle Opening Mtg. Cntr	111 mm 282 mm
Each	\$43.28

McBride

PRINCESS 12



12" doped edge paper cone fullrange


Outside Dia	310.5 mm
Impedance	8 ohm
Power	20 W
Freq. Resp	50 Hz - 15 KHz
Magnet Wt	
Fs	60 Hz
Voice Coil Dia	25 mm
SPL	91 db
Depth	114 mm
Baffle Opening	282 mm
Mtg. Cntr	298 mm BC x 8

Each \$47.66



MISCO HIGH POWER SMALL SPEAKERS

MISCO® High Power Small Speakers



Misco is a North American manufacturer of high quality small and industrial loudspeakers. Their patented "SEALED-LINEAR" design protects the voice coil and gap from ferrous and non ferrous particles and insures years of trouble-free service. High power, high temperature voice coils mean these small speakers can withstand abuse that would burn out other small speakers.

Impedance: 8 ohms at 400 Hz. Special 4, 16, 32, or 45 ohm voice coils available in case lots.

Voice coil construction: Precision-wound high temperature copper wire on aluminum formers.

Magnet material: High permeability barium-ferrite.

Cone material: Molded paper.

Model Number	Size/Shape (inches)	Mag. Wt. (oz.)	Program Watts	RMS Watts	Mtg. Dia. (inches)	Depth (inches)	Imp. (ohms)	Frequency Response	SPL 1 W / 1 m	Price each
AC2S	2 square	0.70 cer	8	4	2-3/8	15/16	8	500 to 3.5 KHz	87 db	\$11.93
AC22S	2-1/2 square	0.70 cer	8	4	2-15/16	1-7/32	8	260 to 8 KHz	84 db	\$11.03
DC22S	2-1/2 square	2.50 cer	12	6	2-15/16	1-5/32	8	260 to 8 KHz	89 db	\$13.76
DC23S	2 x 3-3/4 oval	2.50 cer	12	6	1-1/2 x 3-1/4	1-1/8	8	250 to 8 KHz	89 db	\$14.80
AC3S	3 square	0.70 cer	8	4	3-3/8	1-1/4	8	250 to 8 KHz	87 db	\$9.91
DC3S	3 square	2.50 cer	12	6	3-3/8	1-7/32	8	250 to 8 KHz	92 db	\$12.36
AC32S	3-1/2 square	0.70 cer	8	4	3-15/16	1-11/32	8	240 to 10 KHz	88 db	\$10.24
DC32S	3-1/2 square	2.50 cer	12	6	3-15/16	1-5/16	8	220 to 10 KHz	93 db	\$12.36

MISCO WATERPROOF SPEAKERS

MISCO® Waterproof Loudspeakers

Misco waterproof loudspeakers are designed for the toughest environmental conditions. Able to withstand total immersion in water for 96 hours without deterioration of sound quality. Plus the patented "SEALED LINEAR" design protects the voice coil and gap from ferrous and non ferrous particles.

Impedance: 8 ohms at 400 Hz. Special 4, 16, 32, or 45 ohm voice coils available in case lots.

Voice coil construction: Precision-wound high temperature copper wire on aluminum formers.

Magnet material: High permeability barium-ferrite.

Cone material: Waterproof treated linen.

Model Number	Size/Shape (inches)	Mag. Wt. (oz.)	Program Watts	RMS Watts	Mtg. Dia. (inches)	Depth (inches)	Imp. (ohms)	Frequency Response	SPL 1 W / 1 m	Price each
AC22WP	2-1/2 square	0.70 cer	8	4	2-15/16	1-13/16	8	400 to 5 KHz	84 db	\$12.36
DC22WP	2-1/2 square	2.50 cer	12	6	2-15/16	1-15/32	8	300 to 6 KHz	88 db	\$15.48
AC3WP	3 square	0.70 cer	8	4	3-3/8	1-1/4	8	250 to 7 KHz	84 db	\$11.72
DC3WP	3 square	2.50 cer	12	6	3-3/8	1-7/32	8	250 to 7 KHz	87 db	\$14.64
DC32WP	3-1/2 square	2.50 cer	12	6	3-15/16	1-5/16	8	195 to 7 KHz	91 db	\$14.64
DC4WP	4 square	2.50 cer	12	6	4-11/16	1-13/32	8	180 to 6 KHz	93 db	\$14.72
JC5WP	5 round	10.0 cer	30	15	4-11/16	1-7/8	8	120 to 8 KHz	95 db	\$25.45
JC80WP	8 round. co-ax.	10.0 cer	30	15	7-5/8	2-13/16	8	50 to 18 KHz	93 db	\$58.63

COMPONENTS direct mail order

REPLACEMENT SPEAKERS

Top quality replacement loudspeakers. Designed and engineered to industry standards for use in radio, television, stereo, automotive and commercial sound applications.



MC5060

Top quality elliptical speakers. Used in many small appliances, TV's and radios. Ideal for maximizing cone area in cramped spaces.

Designed and constructed to meet industry standards.



8LS3506-23

Model Number	Nom. Size (inches)	Mag.Wt. (oz.)	Voice Coil Dia. (in.)	Voice Coil Imp.	Power (watts)	Price each
25A04Z8	2.5 sq.	0.35 aln	1/2	8	1.5	\$3.50
30C25Z8	3 sq.	2.35 cer	9/16	8	5	\$13.50
8LS301-23	3 sq.	2.8 cer	9/16	8	3.5	\$8.09
3LS422-23	4 sq.	2.8 cer	9/16	3.2	3.5	\$8.09
8LS422-23	4 sq.	2.8 cer	9/16	8	3.5	\$8.09
MC5030	5 Pc.	3.0 cer	3/4	8	5	\$8.09
MC5060	5 Pc.	6.0 cer	3/4	8	10	\$10.22
PACER 6	6 Pc.	10.0 cer	1	8	20	\$25.40
MC6030	6 Pc.	3.0 cer	3/4	8	5	\$10.22
8LS809-14	8 Rd.	10.0 cer	1	8	20	\$17.03

ELLIPTICAL SPEAKERS

Model Number	Nom. Size (inches)	Mag.Wt. (oz.)	Voice Coil Dia. (in.)	Voice Coil Imp.	Power (watts)	Price each
DO133	1.75 x 2.75 Rec	.35 aln	1/2	8	0.5	\$4.50
8LS3506-23	3 x 5 Oval	2.8 cer	9/16	8	3.5	\$8.09
8LS4607-19	4 x 6 Oval	3.0 cer	3/4	8	8	\$18.22
8LS4805-17	4 x 8 Oval	4.8 cer	3/4	8	10	\$17.35
PACER 57	5 x 7 Oval	6.0 cer	1	8	15	\$13.68
PACER 69	6 x 9 Oval	6.0 cer	1	8	15	\$23.98

LOW PROFILE SPEAKERS

SPL

Frequency

	Flat stainless steel	Number	Size	Depth	Resp. (KHz)		Imp.	(watts)	each
	diaphragms, bonded	AZ30R	30 mm rd.	5.0 mm	1.3 to 8	70 db	8	0.4	\$4.64
	ferrite magnets and ABS plastic frames.	AZ30S	30 mm sq.	5.0 mm	1.3 to 8	70 db	8	0.4	\$4.64
CS	·	AZ40R	40 mm rd.	5.0 mm	0.6 to 6	70 db	8	0.4	\$5.11
	CS series: Plastic frame, mylar	AZ40S	40 mm sq.	5.0 mm	0.6 to 6	70 db	8	0.4	\$5.11
C P C	cone speakers.	AZ50R	50 mm rd.	5.0 mm	0.5 to 7	70 db	8	0.4	\$5.23
		AZ50S	50 mm sq.	5.0 mm	0.5 to 7	70 db	8	0.4	\$5.23
samarium	Steel framed with	CS 20A	20 mm rd.	4.0 mm	0.7 to 5	80 db	8	0.07	\$3.95
	samarium cobalt magnets.	CS 29B	29 mm rd.	6.8 mm	0.7 to 5	80 db	8	0.1	\$5.09
	"M" denotes mylar cone.	MSC298M	40.2 mm rd.	7.2 mm	0.4 to 6	80 db	8	0.1	\$6.20
		MSC299M	50.2 mm rd.	7.0 mm	0.4 to 7	80 db	8	0.2	\$6.20
		MSC300	57.2 mm rd.	8.9 mm	0.4 to 7	80 db	8	0.2	\$6.20

Nom.



A7 series.

AZ30S

Model



CS29B



MSC299M



Voice Coil Power Price



LOW POWER SMALL SPEAKERS

Alnico magnet - round frame



					Frequency) Response	Mag. size (Dia x H)		Price each
AO102	`40 ´	15.8	8	0.1	600 to 9 KHz	•		\$3.25
AO103	45	16.4	8	0.1	650 to 9 KHz	13 x 10mm	0.35	\$3.25
AO200	50	18.7	8	0.2	450 to 8.5 KHz	13 x 10mm	0.35	\$2.68
AO201	57	19.5	8	0.25	400 to 8 KHz	13 x 10mm	0.35	\$2.68
AO202	66	21.3	8	0.3	340 to 8 KHz	13 x 10mm	0.35	\$3.10
AO203	70	23.4	8	0.5	250 to 5 KHz	13 x 10mm	0.35	\$3.40
AO300	77	25.7	8	0.5	230 to 7.5 KHz	13 x 10mm	0.35	\$3.90

Alnico magnet - square frame



Model	Dia.	Depth	Voice Coil	Nominal	Frequency	Mag. size	Mag.	Price
Number	(mm)	(mm)	Imp. (ohms)	Power (W)	Response	(Dia x H)	Wt. (oz.)	each
BO200	50	18.7	8	0.2	420 to 9 KHz	13 x 10mm	0.35	\$3.42
BO300	77	26.0	8	0.5	220 to 8.5 KHz	13 x 10mm	0.35	\$4.09
BO302	92	29.2	8	1.0	180 to 10 KHz	13 x 10mm	0.35	\$4.27

Ceramic magnet - round frame



			Voice Coil Imp. (ohms)			Mag. size (Dia x H)		
FE200	50	17.5	8	0.2	420 to 9 KHz	32 x 6mm	0.60	\$2.32
FE201	57	18.9	8	0.25	380 to 8.5 KHz	32 x 6mm	0.60	\$2.32
FE300	77	23.6	8	0.5	230 to 10 KHz	32 x 6mm	0.60	\$3.02
FE302	92	29.0	8	1.0	200 to 10 KHz	32 x 6mm	0.60	\$3.52

Ceramic magnet - square frame



			Voice Coil Imp. (ohms)		Frequency) Response	Mag. size (Dia x H)		
FEB202	66	19.5	8	0.3	340 to 8 KHz	32 x 6mm	0.60	\$2.41
FEB300	77	23.0	8	0.5	240 to 8.5 KHz	32 x 6mm	0.60	\$2.72

SOUND SPEAKERS

McBride

8LS5110-14



5" cloth edge paper cone P.A. speaker

Outside Dia	127 mm
Impedance	8 ohm
	20 W
Freq. Resp	60 Hz - 17.5 KHz
Magnet Wt	10 oz
Fs	73 Hz
Voice Coil Dia	25 mm
SPL	96 db
Depth	58 mm
Mtg. Cntr	119 mm BC x 4
Each	\$17.60

M*ISCQ*® JC5FD

5" cloth edge paper cone P.A. speaker

Outside Dia	
Impedance	8 ohm
Power	
Freq. Resp	60 Hz - 12 KHz
Magnet Wt	10 oz
Fs	85 Hz
Voice Coil Dia	25 mm
SPL	93 db
Depth	52.4 mm
Mtg. Cntr	119 mm BC x 4
Each	\$21.23

M*ISCQ*® JC5WP



5" waterproof P.A. speaker

Impedance Power Freq. Resp Magnet Wt Fs Voice Coil Dia SPL	
	119 mm BC x 4
Each	\$25.45

McBride 810CXB



8" co-axial P.A. speaker

Outside Dia	205 mm
Impedance	8 ohm
Power	20 W
Freq. Resp	55 Hz - 20 KHz
Magnet Wt	10 oz
Fs	55 Hz
Re	
Voice Coil Dia	25 mm
SPL	
Depth	75 mm
Baffle Opening	
Mounting	.195 mm BC x 4
Each	\$20.78

McBride

8" co-axial P.A. speaker with 10W - 70/25 volt trans.

810CXBT



Outside Dia	
Impedance	8 ohm
Power	20 W
Freq. Resp	50 Hz - 20 KHz
Magnet Wt	
Fs	55 Hz
Voice Coil Dia	25 mm
SPL	94 db
Depth	86 mm
Mtg. Cntr	195 mm BC x 4
T C	70/25 1

Transformer70/25 volt Taps ..0.66, 1.25, 2.5, 5 & 10 watts

\$28.48 Each

McBride



8" damped edge dual cone P.A. speaker

8LS814-FY9

Outside Di	m191 x 191 mm
Impedance	e8 ohm
Power	20 W
Freq. Resp	50 Hz - 16 KHz
Magnet W	t10 oz
Fs	72 Hz
Voice Coil	Dia25 mm
SPL	98 db
Depth	74 mm
	193 mm BC x 4
Foob	407.05

Each \$27.25

COMMERCIAL SOUND SPEAKERS

McBride

8LS822-14



8" damped edge dual cone P.A. speaker

Outside Dia	205 mm
Impedance	8 ohm
Power	20 W
Freq. Resp	45 Hz - 18 KHz
Magnet Wt	10 oz
Fs	72 Hz
Voice Coil Dia	25 mm
SPL	94 db
Depth	73 mm
Mtg. Cntr	195 mm BC x 4
Each	\$10.38

McBride

8LS822-19



8" damped edge dual cone P.A. speaker

	205 mm
Impedance	8 ohm
	15 W
Freq. Resp	50 Hz - 15 KHz
	6 oz
Fs	72 Hz
Voice Coil Dia	25 mm
SPL	92 db
Depth	73 mm
Mtg. Cntr	195 mm BC x 4
Fach	\$8.65

Marsland PACER 8



8" damped edge P.A. speaker

Impedance Power Freq. Resp Magnet Wt Fs Voice Coil Dia SPL	191 x 191 mm 8 ohm 50 Hz - 8 KHz 6 oz 70 Hz 25 mm 96 db
Depth	74 mm
Each	193 mm BC x 4 \$22.07

Marsland SUPER PACER 8



8" damped edge P.A. speaker

Outside Dim	191 x 191 mm
Impedance	8 ohm
Power	20 W
Freq. Resp	50 Hz - 8 KHz
Magnet Wt	10 oz
Fs	70 Hz
Voice Coil Dia	25 mm
SPL	98 db
Depth	74 mm
Mtg. Cntr	
Each	\$23.80

Marsland 8" damped edge dual cone P.A. speaker

SUPER PACER 8WW



Outside Dim	191 x 191 mm
Impedance	8 ohm
Power	
Freq. Resp	50 Hz - 16 KHz
Magnet Wt	
Fs	70 Hz
Voice Coil Dia	25 mm
SPL	98 db
Depth	74 mm
Mtg. Cntr	193 mm BC x 4
Each	\$26.87

MG 820CXB



8" Co-Axial P.A. Speaker

Jutside Dia	
mpedance	8 ohm
	40 Wmax
reg. Resp	50 Hz - 18 KHz
√agnet Wt	
S	
Re	6.88 ohm
)ts	
es	
Qms	3.993
/as	
oice Coil Dia	
SPL	90.9 db
Depth	
Baffle Opening	
	196 mm BC x 4
J	

Each \$30.79



COMMERCIAL SOUND SPEAKERS

Sammi® 8" high power rubber edge poly cone co-ax.

CX802



203 mm
8 ohm
50 W
50 Hz - 20 KHz
20 oz
53.3 Hz
0.706
0.955
2.70
30.75 litres
38 mm
89 db
74.5 mm
184 mm
193 mm BC x 4

\$43.84 Each

M*ISCQ*®

JC80F



8" foam edge co-axial P.A. speaker

Outside Dia206.4 mm Impedance.....8 ohm Power20 W Freq. Resp35 Hz - 18 KHz Magnet Wt.....10 oz Fs.....55 Hz Voice Coil Dia.....25 mm SPL.....94 db Depth76.2 mm Mtg. Cntr.....193.7 mm BC x 8

\$40.02 Each

MISCO® JC80WP

8" waterproof co-axial P.A. speaker



Outside Dia	206.4 mm
Impedance	8 ohm
Power	20 W
Freq. Resp	50 Hz - 18 KHz
Magnet Wt	10 oz
Fs	70 Hz
Voice Coil Dia	25 mm
SPL	93 db
Depth	71.5 mm
Mtg. Cntr	

\$58.63 Each

8C10DVPAX



8" dual voice coil P.A. speaker

Outside Dim.....191 x 191 mm Impedance2 x 8 ohm Power20 W Freq. Resp60 Hz - 12 KHz Magnet Wt.....10 oz Fs.....100 Hz Voice Coil Dia.....25 mm SPL.....90 db Depth79.4 mm Mtg. Cntr.....193 mm BC x 4 Each \$22.72

Juam 8C10PAOT

8" weatherproof P.A. speaker



Outside Dim	191 x 191 mm
Impedance	8 ohm
Power	20 W
Freq. Resp	80 Hz - 8 KHz
Magnet Wt	10 oz
Fs	90 Hz
Voice Coil Dia	25 mm
SPL	95 db
Depth	82.6 mm
Mtg. Cntr	193 mm BC x 4
Each	\$19.70

Juam 8C10PAX



8" dual cone P.A. speaker

Impedance Power Freq. Resp Magnet Wt Fs Voice Coil Dia SPL Depth	96 db 76.2 mm
Mtg. Cntr	193 mm BC x 4 \$16.01
_~~.	φ.σ.σ.



COMMERCIAL SOUND SPEAKERS

McBride

MC1603



6-1/2" clip-in flush mount ceiling speaker

Outside Dia185.3 mm
Impedance8 ohm
Power10 WRMS / 20 Wmax
Freq. Resp85 Hz - 20 KHz
Magnet Wt6 oz
Fs85 Hz
Re7.2 ohms
Voice Coil Dia20 mm
SPL94 db
Depth80 mm
Req. Opening166 mm
MountingTorsion clip x 2
Each \$17.77

McBride

MC2002



8" clip-in flush mount ceiling speaker

Outside Dia	233 mm
Impedance	8 ohm
Power15 \	WRMS / 30 Wmax
Freq. Resp	75 Hz - 18 KHz
Magnet Wt	
Fs	75 Hz
Re	6.9 ohms
Voice Coil Dia	
SPL	95 db
Depth	90 mm
Reg. Opening	
Mounting	
	404.00

Each \$21.38



McBRIDE CEILING ASSEMBLIES



Custom Made and Industry Standard Models. Available in any combination – Assembled to your specifications.

All McBride speakers, baffles and transformers may be ordered pre-assembled. Advantages include less labor, quick installation and a faster turn around time. You can also be assured of a top quality, consistent product.

Industry standard assemblies are listed below. If you don't see what you need, please call. All parts are in stock for immediate assembly and delivery.

Part No.	Speaker	Baffle	Trans.	Description	
5110/70/70	8LS5110-14	MC70	MCT70	5" speaker 10 oz. magnet; square baffle; 70 volt 4 watt trans.	\$27.96 ea.
5110/12/70	8LS5110-14	MC12	MC70	5" speaker 10 oz. Magnet; round baffle; 70 volt 4 watt trans.	\$27.90 ea.
C5/B70/W/VK	8C5PAX	BR8W	TBL70	8" speaker with whizzer 5 oz. magnet; round baffle with volume control; 70 volt 4 watt trans.	\$43.02 ea.
8229/11/70	8LS822-19	MC11	MCT70	8" speaker with whizzer 6 oz. magnet; round baffle, 70 volt 4 watt trans.	\$20.89 ea.
8229/11/25	8LS822-19	MC11	MCT25	8" speaker with whizzer 6 oz. magnet; round baffle; 25 volt 4 watt trans.	\$20.89 ea.
8229/11/7025	8LS822-19	MC11	MCT7025	8" speaker with whizzer 6 oz. magnet; round baffle; 70/25 dual volt 5 watt trans.	\$20.89 ea.
8229/25/25	8LS822-19	MC25	MCT25	8" speaker with whizzer 6 oz. magnet; square baffle; 25 volt 4 watt trans.	\$21.25 ea.
8229/25/70	8LS822-19	MC25	MCT70	8" speaker with whizzer 6 oz. magnet; square baffle; 70 volt 4 watt trans.	\$21.25 ea.
8229/25/7025	8LS822-19	MC25	MCT7025	8" speaker with whizzer 6 oz. magnet; square baffle; 70/25 dual volt 5 watt trans.	\$21.25 ea.
8229/25SQ/25	8LS822-19	MC25SQ	MCT25	8" speaker with whizzer 6 oz. magnet; square baffle w/switch cut out; 25 volt 4 watt trans.	\$24.14 ea.
MC1603/7025	MC1603	Built-in	MCT7025	6-1/2" clip-in flush mount ceiling speaker with whizzer; 70/25 dual volt 5 watt trans.	\$24.40 ea.
MC2002/7025 MC2002 Built-in MCT7025		MCT7025	8" clip-in flush mount ceiling speaker with whizzer; 70/25 dual volt 5 watt trans.	\$28.00 ea.	

McBRIDE WALL AND CORRIDOR ASSEMBLIES

Special assemblies for instances where regular ceiling assemblies are not practical. Our MC75CB bi-directional corridor baffle can be either wall or ceiling mounted and

features a 180° dispersion field. The McBride WB-8E sloping wall baffle comes in either light oak or walnut to match any decor. Custom assemblies are available.



8229/75/70



WB822-70

Part No. Speaker **Baffle Trans** Description **Price** 8229/75/70 8LS822-19 MC75CB MCT70 8" speaker with whizzer 6 oz. \$57.53 ea. magnet; bidirectional corridor baffle; 70 volt 4 watt trans. WB8229-70 8LS822-19 WB-8E MCT70 8" speaker with whizzer 6 oz. \$39.29 ea. (oak or magnet; sloping wood grain wall walnut) baffle; 70 volt 4 watt trans.

8229/80/70 8LS822-19 SMC80E MCT70 8" speaker with whizzer 6 oz. \$35.62 ea.

McBRIDE 8" SLOPING WOODEN WALL BAFFL



The McBride sloping wall baffle is the most durable you can buy. Rugged construction not only increases rigidity but also eliminates baffle resonance and sound distortion. Finished in a durable walnut or light oak wood-grain, this baffle will blend smoothly with any decor. The special acoustically transparent grill cloth does not effect sound quality or output.

Optional volume control provides easy adjustment of sound level.

Baffle mounting bracket and speaker mounting hardware included.

magnet; SMC80E enclosure; 70 volt 4 watt trans.

Add prefix "W" to end of part number for walnut finish, "L/O" for light oak. Add prefix "V.C." to end of part number for optional volume control.

Part No.	Part No. Dimensions Depth top Depth bottom		Height	Width	Description	Price
WB8E Oak	5-3/8"	3-7/8"	10-5/8"	9-5/8"	Sloping wooden wall baffle for 8" speakers	\$22.92 ea.
WB8E Walnu	ıt 5-3/8"	3-7/8"	10-5/8"	9-5/8"	with 3/8" dia. hole in bottom for mounting V.C.	\$22.92 ea.



McBRIDE STEEL SPEAKER ENCLOSURES

McBride SMC80E



Round surface mount "cookie tin" style enclosure for 8" speakers. Ideal for exposed truss ceilings or wall mounting.

Each \$20.08

Finish.....Standard polar white baked powdered epoxy.

McBride MC75CB*



Bi-directional corridor baffle

Type	.Corridor baffle.
	Double sloping
7	perforated
	metal sides.
Spkr. Size	.8 inch
Dimensions	.8-3/8" high.
	8-3/16" wide.
	8-1/8" deep base.
	4-3/4" deep top.
Weight	.Approx. 3-1/4 lbs.
Finish	.Rustproof plated,
	painted standard
	polar white.

*Speaker, Transformer and hardware not included.

Each \$44.69

McBRIDE LINE MATCHING TRANSFORMERS

Series 1 Premium Grade

Very low insertion loss 0.5 db, Eff=90%. Super accurate tap impedances (best for large installs) Solder lug terminals – Made in Canada.

Series 2 Contractor Grade

Low insertion loss 0.65 db, Eff=87%. Accurate tap impedances. Pig tail leads for easy hook-up. Industry standard mounting dimensions.



Series 1




	Columbia harg to			randada sa maanting amarina				
	Part No.	INPUT volts	TAPS watts	OUTPUT ohms	PRICE each			
	Series 1							
	MC254*	25	1/4, 1/2 ,1, 2, 4	8	\$8.33			
	MC702	70	1/4, 1/2, 1, 2	8	\$6.98			
	MC704	70	1/4, 1/2, 1, 2, 4	8	\$8.94			
	MC710V	70	2-1/2, 5, 10	8 or 16	\$12.54			
	MC730V	70	3-3/4, 7-1/2, 15, 30	8 or 16	\$17.70			
	MC70100	70	50, 100	4 or 8	\$45.41			
	Series 2							
	MCT25	25	1/4, 1/2, 1, 2, 4	8	\$5.34			
	MCT70	70	1/4, 1/2, 1, 2, 4	8	\$5.34			
	MCT7025	25 & 70	5/8, 1-1/4, 2-1/2, 5	8	\$5.88			
	MCT7025-10	25 & 70	5/8, 1-1/4, 2-1/2, 5, 10	8	\$6.65			
١	MCT25CT*	25	1/4, 1/2, 1, 2, 4	8	\$5.88			
	MCT10T	25 & 70	(70v) 1/4, 1/2, 1, 2, 4, 8, 10 (25v) 1/8, 1/4, 1/2, 1ct*	8	\$6.16			

 $[\]ensuremath{^{\star}}$ or CT denotes the center tap and/or a center tap type transformer.



McBRIDE CEILING AND WALL BAFFLES


- Standard or Automatic Types. Suffix "A" indicates automatic torsion spring mounting.
- Hidden speaker mounting studs.
- Heavy gauge steel construction. Baked powdered epoxy white satin finish.
- Sold complete with speaker mounting nuts and white finished baffle screws or torsion springs.






McBRIDE CEILING AND WALL BAFFL

- Standard type installation.
- · Hidden speaker mounting studs.
- Heavy gauge steel construction. Baked powdered epoxy white satin finish.
- Sold complete with speaker mounting nuts and white finished baffle screws.



MC25SQ



Part No. MC25SQ 12-1/2"

11"

C **Back Box** 3/16"

Square ceiling baffle for 8" speakers with cut-out for MCSW-1 or MCSW-2 call/privacy switch.

One piece construction with

hidden speaker mounting studs.

MC20E

Price \$9.42 ea.






Round (MC12) or Square (MC70) ceiling baffles for 4" and 5" speakers.

One piece construction with hidden speaker mounting studs.



MC70



Part No. MC12

MC70

С

8-9/16" 6-3/8"

В 4-3/4"

4-3/4"

C 3/16"

5/16"

Back Box MC40E

MC40E

Price \$5.99 ea.

\$6.05 ea.



MC15

B

Economy round ceiling baffle for 4" or 5" speakers. Designed for use with MC15E economy back box.

One piece construction with hidden speaker mounting studs.

Part No. MC15

7-3/8"

4-23/32" 7/32"


C **Back Box** MC15E

Price \$5.53 ea.



McBRIDE BACK BOXES

- Rust resistant heavy gauge steel. Inside coated to eliminate mechanical resonance.
- Adjustable mounting straps allow for perfect alignment.
- Four combination 1/2" 3/4" knockouts are provided spaced 90° apart.






McBRIDE BACK BOXES

- Rust resistant heavy gauge steel. Inside coated to eliminate mechanical resonance.
- Adjustable mounting straps for perfect alignment.
- Four combination 1/2"- 3/4" knockouts spaced 90° apart.
- Surface mount boxes finished in satin white baked powdered epoxy.







11-3/4"

MC20E: Square back box for 8" speakers. Use with MC25 or MC25SQ baffles.

MC20EA: Same as above with brackets for square automatic MC25A baffle.

Square back box for 4" and

Use with MC12 or MC70 baffles.


Part No. Α MC20E 11-3/4" В 4" 4"

С Price 11" \$10.41 ea.

N/A \$11.66 ea.







Part No. MC40E

MC20EA

Α 5-9/16"

5" speakers.

В 4-3/4"


C 4-11/16"

Price \$7.36 ea.





SMC20EA



Part No. SMC20E SMC20EA **⊬** B →

Α 12-7/8" 12-7/8"

SMC20E: Square surface mount back box. Use with MC25 or MC25SQ baffles. **SMC20EA:** Same as above with brackets for square automatic MC25A baffle.


> В 4"

C 11" N/A

Price \$16.04 ea. \$19.15 ea.



SMC40E



Part No. SMC40E



for 4" or 5" speakers. White satin finish.

4"

Use with MC12 or MC70 baffles.

Square surface mount back box

Α 6-5/8" В

С 4-3/4"


Price \$13.37 ea.

McBRIDE BACK BOXES

- Rust resistant heavy gauge steel. Inside coated to eliminate mechanical resonance.
- Surface mount boxes finished in satin white baked powdered epoxy.



SMC60SB



Part No. SMC60SB 12-7/8"

C В 6-1/2" 3-1/2"

D 11"

Sloping wooden wall baffle for 8" speakers with 3/8" diameter hole in bottom for mounting volume control.

Square sloping surface mount back box for 8" speakers.

Use with MC25 or MC25SQ baffles.


> **Price** \$41.24 ea.



WB8E Walnut



WB8E Oak



Part No. 9-5/8" WB8E Oak

WB8E Walnut



В

5-1/8"

5-1/8"

C 3-7/8"

D 10-5/8" 3-7/8" 10-5/8"

Price \$22.92 ea. \$22.92 ea.

McBRIDE STEEL SPEAKER ENCLOSURES

McBride SMC80E



Round surface mount "cookie tin" style enclosure for 8" speakers. Ideal for exposed truss ceilings or wall mounting.

Diameter.....10 inches Depth.....4 inches

Spk. Mtg.....4 x concealed studs on 8" spk bolt pattern.

Knock-outs .1/2-3/4" combination 2 on enclosure side,

2 on enclosure back. Mounting2x1/4" holes on back. Weight2-3/4 pounds.

Finish.....Standard polar white baked powdered epoxy.


Each

\$20.08

McBride

9-5/8"

MC75CB*



Bi-directional corridor baffle

Type:.....Corridor baffle. Double sloping perforated metal sides. Spkr. Size:.....8 inch


Dimensions: ...8-3/8" high. 8-3/16" wide. 8-1/8" deep base. 4-3/4" deep top. ..Approx. 3-1/4 lbs. Weight:....

Finish:....Rustproof plated, painted standard polar white.

*Speaker, Transformer and hardware not included.

Each

\$44.69



MC600 / MC800

McBRIDE SOUND MASKING CANS

MC600

Diameter6" Depth.....6" *See note. Description: Sound masking can and lid assembly for 4" and 5" speakers.

Each \$13.92

MC800

Can diameter.....10" Lid diameter.....11"

Depth.....8" *See note. Description: Sound masking can and

lid assembly for 8" speakers.

Each \$21.24

Our sound masking cans are available as is or custom built to your specifications using any of our high quality speakers and transformers. Please allow us to quote on your requirements.

*Please note: The standard depth is listed. Custom depths are available if quantity permits.



CIS₁

SE3GVP

Specifications: **CIS1 Intercom Station**

Finish: Gray baked powdered epoxy. 5.5" high x 7.5" wide x 2.15" deep Dimensions: 3" weatherproof, 2.5 oz. magnet. Speaker/Mic:

SPST normally open Vandal

resistant design.

Flush mounting: Standard 3-gang electrical box. Use Quam SE3GVP enclosure. Surface mounting: 8, 13, 20 or 45 ohm. 25 or 70 volt. System types:

Each \$135.53

VANDAL RESISTANT INTERCOM STATION

The Quam CIS1 intercom station is for use in areas where vandalism must be anticipated. The face plate is 11 gauge steel and the speaker is protected by three independent barrier plates. Call switch travel is limited by mechanical means to prevent damage due to heavy impact. The CIS1 mounts to a standard 3-gang electrical box.

The SE3GVP surface mount enclosure is formed from a single piece of 0.060" steel with welded and bolted seams. Two combination 1/2" - 3/4" knock-outs are provided on the rear.

> Specifications: **SE3GVP Surface Enclosure**

> Finish: Gray baked powdered epoxy.

6.385" high x 8.5" wide x 2.25" deep Dimensions: 0.060" cold rolled steel. 55,000 P.S.I. Material:

tensile strength.

One piece. Seams pressure welded Construction:

and bolted.

Knock-outs: Two 1/2" - 3/4" combo, rear panel.

Station Mounting: Welded nuts, 4 places.

Enclosure Mount: 4 x 3/8" holes. 3.58" x 6.25" pattern.

Each \$45.88



Switch:



BR8VP

Baffle material:

BS8VP

VANDAL PROOF BAFFLES

Quam vandal proof baffles are for use in areas where the possibility of abuse must be anticipated. The two-piece design features a baffle made from 0.075" cold rolled steel and a uniquely designed, acoustically transparent, internal speaker screen. Together they offer unequalled protection to the loudspeaker system.

Square shanked carriage bolts mount the speaker and screen. Tamper resistant security socket-head screws mount the baffle to the enclosure. Hardware and socket tool included.

Specifications:

BR8VP (round)

White baked powdered epoxy. Finish:

Depth: 5/16"

12-3/4" round. Dimensions:

Baffle mounting: 11-1/4" diameter bolt circle, 4 places. White baked powdered epoxy. 5/16"

Model No. BS8VP (square)

11-1/2" square.

10" square between centers, 4 places.

7-5/8" diameter bolt circle, 4 places. Accepts all standard 8" loudspeakers. Speaker mounting:

Speaker protection: Acoustically transparent stamped steel security screen with tamper-proof hardware.

Each \$40.94 Each

0.075" cold rolled carbon steel. Tensile strength: 55,000 P.S.I. Pressure welded seams.

\$43.52





VANDAL PROOF SURFACE ENCLOSURES

Quam SE1WVP (flat) and SE2WVP (sloping) vandal proof surface mount enclosures are for use with the BS8VP square baffle in areas where the possibility of abuse must be anticipated and the situation calls for surface mounted speakers.

Both enclosures are formed from a single piece of 0.060" cold rolled steel. All seams are pressure welded for strength. The thickness and stiffness of the steel eliminates the need for internal damping.

11-5/8" square.

SE2WVP (sloping)

White baked powdered epoxy.

5-1/4" at top sloping to 2-3/4" at bottom.

10" square between centers, 4 places.

Specifications:

SE1WVP (flat)

Finish: White baked powdered epoxy.

Depth:

11-5/8" square. Dimensions:

Baffle mounting: 10" square between centers, 4 places.

0.060" cold rolled carbon steel. Tensile strength: 55,000 P.S.I. Pressure welded seams. Back-box material:

Knock-outs: Single 1" diameter hole located in center of rear panel.


Back-box mounting: 6 holes on 3-3/8" x 3-3/8" pattern and 4 holes on 8-7/8" x 8-7/8" pattern. All holes 1/4" dia.

> Each \$41.48 Each \$50.83



HC-1 Height15" Width15" Depth15"

ColorBlack Each \$51.52



SMC-1 Height15"

Width15" Depth5" ColorWhite

Each \$51.52

McBRIDE VANDAL RESISTANT CAGES

Designed to protect paging horns (HC-1) and surface mounted paging speakers (SMC-1) or other fixtures from damage due to impacts or vandalism. Ideal for schools, gymnasiums, arenas, heavy industrial areas or anywhere abuse must be anticipated.

Both cages are constructed from 1/8" diameter welded steel wire screen with 7/8" openings and 3/16" steel rod reinforcing hoops. All joints are fully welded for strength and durability.

Both cages are finished in a tough chip and rust resistant baked powdered epoxy.

Suitable for outdoor use.

BAFFLE & BACK BOX MOUNTING DEVICES



MC100

MC100 Description: Mounting channel.

Always used in pairs for mounting back boxes to

T-bar ceilings. Length.....23-3/4" Width3/4"

\$1.22 Each

MC200 RMC10

MC200

Description: Mounting frame. One frame per speaker. For mounting 8" baffles (round or square, standard or automatic) to T-bar ceilings.

One piece construction. Length.....23-3/4" Width11-1/2"

Each \$8.41

RMC10

Description: Round plaster ring. Accepts MC10 and

MC11 baffles.

Outside Dia.....11-5/8' Inside Dia.....9-7/8" Depth5/8"

\$4.32 Each

RMC10A

Description: Round plaster ring. Accepts MC10A and MC11A automatic mounting baffles. Outside Dia.....11-5/8'

Inside Dia.....9-7/8" Depth.....5/8"

Each \$6.29

IN-WALL SPEAKERS & BRACKETS



MG


In-wall 2-way architectural loudspeakers

MG architectural in-wall speakers offer an unobtrusive, low visibility source of high fidelity sound that can be installed just about anywhere. Ideal for kitchens, bathrooms, bedrooms, sunrooms or any place high quality sound is desired without speaker cabinets or where floor space is at a premium.

Features include a paintable one piece injection molded speaker frame with snap in grill. Shipped complete with all mounting hardware and wall cut-out template.

All models have mounts for line distribution matching transformers.

Part No.	Power	Imp.	SPL	Freq. Resp.	Description	Dime
FS-4H	10 W	8 ohm	89 db	400Hz - 11KHz	4" flat cone speaker in white plastic frame.	6" sq
MC1603	20 W	8 ohm	94 db	85Hz - 20KHz	6-1/2" dual cone clip-in flush mount speaker.	7.3"
MC2002	30 W	8 ohm	95 db	75Hz - 18KHz	8" dual cone clip-in flush mount speaker.	9.17
IWS-1	35 W	8 ohm	90 db	60Hz - 20KHz	5-1/4" woofer with 1" dome tweeter.	11" h
IWS-2	40 W	8 ohm	89 db	50Hz - 20KHz	6-1/2" woofer with 1" dome tweeter.	12" h
IWS-3	50 W	8 ohm	90 db	40Hz - 20KHz	8" woofer with 1" dome tweeter.	14" ł





MG

New construction brackets for in-wall speakers

Bracket	For in-wall speaker	Price
NCB-1	IWS-1	\$33.26 pr.
NCB-2	IWS-2	\$40.99 pr.
NCB-3	IWS-3	\$46.13 pr.

McBRIDE PRIVACY / CALL SWITCHES





MCSW-1

MCSW-2

MCSW-1

ColourWhite

Description: Heavy duty privacy / call switch. White rocker with

> chromed steel bezel. Large screw terminators.

Each \$8.53

MCSW-2

ColourBlack

Description: Plastic economy privacy / call switch.

\$6.10 Each

These switches are designed for talk back intercom / paging systems. Both are DPDT, center off rocker type design. Privacy position is push-on / push-off. Call position is momentary on.

Both snap into our MC25SQ baffle or MCWP-13SW single gang stainless steel wall plate.



McBRIDE STAINLESS STEEL WALL PLAT

High quality stainless steel wall plates designed for custom installations. Constructed of type 302 brushed stainless steel, they are suitable for hospitals or anywhere appearance and durability are essential.

Available in single or double gang width with either mounting dimension for standard electrical boxes. Supplied complete with all necessary hardware. The MCWP-13SW is supplied pre-punched to accept our privacy / call switches.

Part No.	Material	Type	Mtg Centers	Description	Price
MCWP-13SW	302SS	single gang	3-9/32"	Brushed finish type 302 stainless steel wall plate pre-punched for privacy/call switch.	\$3.55 ea.
MCWP-12	302SS	single gang	2-3/8"	Brushed finish type 302 stainless steel wall plate.	\$2.04 ea.
MCWP-13	302SS	single gang	3-9/32"	Brushed finish type 302 stainless steel wall plate.	\$2.04 ea.
MCWP-22 MCWP-23	302SS 302SS	double gang double gang		Brushed finish type 302 stainless steel wall plate. Brushed finish type 302 stainless steel wall plate.	\$3.78 ea. \$3.78 ea.



AUTOTRANSFORMER ATTENUATORS

- Brushed stainless steel or white plastic designer style wall plates
- Mono or stereo for 70 volt, 25 volt or 8 ohm systems.
- Power ratings up to 100 watts. Priority relays and limited access features on some models.





MCATT-10

MGT7010W

Quality attenuators for stepped attenuation of high level audio signals. Each is mounted on a brushed stainless steel or white plastic designer style wall plate for easy installation. All mount to standard single or double gang electrical boxes (see below).

Available for 70 volt, 25 volt and 8 ohm systems in mono or stereo configurations. Up to 100 watts of speaker load.

Low insertion loss (0.65 db typical, 1.0 db max). Stripped and tinned fly lead connections for quick installation.

Part No.	Power	Туре	Mounting*	Description	Price
MCATT-10	10 watts	70/25 volt mono	3-9/32" SG	10 step with zero off position on stainless steel wall plate.	\$12.06 ea.
TSLA9S	10 watts	70/25 volt stereo	3-9/32" SG	9 step with zero off position on stainless steel wall plate.	\$35.71 ea.
TSLA10S/8	10 watts	8 ohm stereo	3-9/32" SG	10 step with zero off position on stainless steel wall plate.	\$35.71 ea.
TSLA35/70	35 watts	70/25 volt mono	3-9/32" DG	9 step with zero off position on stainless steel wall plate.	\$31.50 ea.
TSLA35/8S	35 watts	8 ohm stereo	3-9/32" DG	9 step with zero off position on stainless steel wall plate.	\$55.08 ea.
MGT7010W	10 watts	70/25 volt mono	3-9/32" SG	10 step with zero off position on white plastic designer style wall plate.	\$18.97 ea.
MGT7050W	50 watts	70/25 volt mono	3-9/32" SG	10 step with zero off position on white plastic designer style wall plate.	\$35.58 ea.
MGT825W	25 watts	8 ohm stereo	3-9/32" SG	9 step with zero off position on white plastic designer style wall plate.	\$45.40 ea.
MGT875W	75 watts	8 ohm stereo	3-9/32" SG	11 step with zero off position on white plastic designer style wall plate.	\$64.39 ea.
QC-10P	10 watts	70/25 volt mono	3-9/32" SG	10 step with zero off position with 24 VDC priority relay.	\$41.87 ea.
QC-10LA	10 watts	70/25 volt mono	3-9/32" SG	10 step with zero off position. Limited access screw driver adjust.	\$22.84 ea.
QC-100	100 watts	70/25 volt mono	3-9/32" DG	10 step with zero off position on brushed stainless steel wall plate.	\$37.30 ea.
QC-4-50	4 watts	Potentiometer	3-9/32" SG	50 ohm potentiometer on brushed stainless steel wall plate.	\$12.77ea.
QC-4-5000	4 watts	Potentiometer	3-9/32" SG	5,000 ohm potentiometer on brushed stainless steel wall plate.	\$12.77 ea.
				*SG = single gang box; DG = double gang box.	

McBRIDE L-PADS ~ HI-FI AND COMMERCIAL













LP15

LP15S

LP50 L

LP50S

LP100

LP100S

Constant input load level controls. Used in stereo enclosures for variable attenuation of tweeters and midranges or in background music systems to control volume of individual speakers.

Sold complete with black plastic knob, mounting plate and hardware. Shaft size: 3/8" threaded x 3/4" long. Stereo types are two L-Pads on a common shaft.

Part No.	Type	Power	Description	Price
LP15	mono	15 watts	8 ohm mono 15 watt L-Pad with plate and knob.	\$6.10 ea.
LP15S	stereo	15 watts	8 ohm stereo 15 watt L-Pad with plate and knob.	\$11.17 ea.
LP50	mono	50 watts	8 ohm mono 50 watt L-Pad with plate and knob.	\$9.14 ea.
LP50S	stereo	50 watts	8 ohm stereo 50 watt L-Pad with plate and knob.	\$18.80 ea.
LP100	mono	100 watts	8 ohm mono 100 watt L-Pad with plate and knob.	\$10.56 ea.
LP100S	stereo	100 watts	8 ohm stereo 100 watt L-Pad with plate and knob.	\$20.93 ea.



45 OHM INTERCOM LOUDSPEAKERS









45LS201-2

AC22S-45

45LS529-23

45LS822-19

Part No.	Size/Shape (inch)	Mag. Wt. (oz.)	Program Watts	RMS Watts	Mt. Dia. (inches)	Depth (inches)	Imp. (ohms)	Frequency Response	SPL 1 W / 1 m	Price each
45LS201-2	2.5" sq.	0.35 aln	3	1.5	2-15/16	7/8	45	180 to 7 KHz	83 db	\$4.75
DC22S-45	2.5" sq.	2.5 cer	12	6	2-15/16	1-5/32	45	260 to 8 KHz	89 db	\$15.31
AC22S-45	2.5" sq.	0.7 cer	8	4	2-15/16	1-1/8	45	260 to 8 KHz	84 db	\$13.57
30A05Z45	3" sq.	0.52 aln	4	2	3-3/8	1-3/16	45	130 to 14 KHz	85 db	\$13.57
AC3S-45	3" sq.	0.7 cer	8	4	3-3/8	1-3/16	45	250 to 8 KHz	87 db	\$13.57
45LS306-2	3 3.5" sq.	2.80 cer	8	4	3-15/16	1-1/4	45	250 to 8 KHz	89 db	\$9.42
AC32S-45	3.5" sq.	0.7 cer	8	4	3-15/16	1-5/16	45	250 to 8 KHz	88 db	\$15.31
45LS422-2	3 4" sq.	2.80 cer	8	4	4-11/16	1-15/32	45	140 to 9 KHz	88 db	\$11.60
45LS529-2	3 5" pc.	2.80 cer	8	4	4-11/16	1-23/32	45	120 to 8 KHz	92 db	\$12.02
45LS822-19	9 8" rd.	6.0 cer	15	10	7-5/8	2-7/8	45	70 to 15 KHz	92 db	\$11.77
8C10Z45	8" pc.	10.0 cer	25	15	7-5/8	3	45	70 to 12 KHz	95 db	\$20.31

Sammi®

PUBLIC ADDRESS HORN DRIVERS

- 50 watt power rating.
- Totally weatherproof, designed for rugged use indoors or outdoors.
- Heavy duty binding post terminations.
- Industry standard 1-3/8" x 18 UNEF external thread for screw on horn mounting.



Sammi public address horn drivers are designed for use with large re-entrant horns typically found in arenas, auditoriums and outdoor venues.

Their rugged weatherproof construction means they are suitable for outdoor and high humidity environments.

*SPL @ 1,500 Hz / 1 watt / 1 meter on axis with 5-3/4 foot re-entrant horn

NSU50B

Part	Power	Frequency	lmp.	SPL*	Dimensions	V. C.	Driver	Price
No.	(watts)	Response	(ohms)	(db)	(mm)	Dia.	Mounting	each
NSU50B	50	250 to 8,000 Hz	8	115*	104 Dia. X 94 H	50 mm	Four 1/4 x 20 UNC holes on 79 mm B.C.	\$80.78

PAGING HORNS



HS-3

Diameter	8 inch
Impedance	8 ohm
Freq. Response	300 Hz - 7 KHz
SPL	118 db / 1 W / 1 m
Color	Dark grey

Each \$32.57

8" Aluminum 25 watt horn.

The HS-3 is a weatherproof 8 inch indoor-outdoor paging horn in a rugged aluminum housing.

The HS-3 is equipped with a swivel bracket and is finished in a tough grey baked enamel.



HS-5P

5 inch
8 ohm
s peak
5 KHz
/ 1 m
White

Each \$13.22

5" White ABS plastic 20 watt horn.

The HS-5P is a weatherproof 5 inch indoor-outdoor paging horn in a high impact ABS plastic housing. Ideal for marine, mobile and siren applications or anywhere a small, high output horn is required.

The HS-5P comes equipped with a swivel mounting bracket.



HS-11P (M58-H)

Size 5 x 8 inch
Impedance8 ohm
Power 40 watts peak
Freq. Response 450 Hz - 10 KHz
SPL118 db / 1 W / 1 m

Each \$26.10

5" x 8" White ABS plastic 30 watt horn.

The HS-11P is a heavy duty weatherproof 5" x 8" indoor-outdoor paging horn with tough ABS plastic housing.

Ideal for siren or marine applications.

The HS-11P is equipped with a pivoting bracket that opens to 90°.



HS-8T

Diameter7.9 inch
Impedance8 ohm direct or 70/25V
Power (70/25V)32 / 16 watts
Freq. Response 350 Hz - 14 KHz
SPL
Depth
25V Power Taps 2, 4, 16, 32 W
70V Power Taps 2, 4, 8, 16, 32 W

Each \$89.50

8" Aluminum 32 watt 70/25V paging horn.

The HS-8T is a weatherproof 8" diameter indoor-outdoor paging / talkback horn. Features include a built-in 70/25 volt transformer with switch selectable power taps and 8 ohm direct hook-up.

The HS-8T is equipped with a swivel bracket and durable aluminum housing. Color is medium gray.



HS-12T

Size	6-1/2 x 11 inch
Impedance 8 (ohm direct or 70/25V
Power (70/25V) .	32 / 16 watts
Freq. Response.	450 Hz - 8 KHz
SPL	. 120 db / 1 W / 1 m
25 V Power taps	2, 4, 8, 16 W
70 V Power taps	2, 4, 8, 16, 32 W

Each \$69.26

6-1/2" x 11" ABS plastic 32 watt 70/25V paging horn.

The HS-12T is a weatherproof 6-1/2" x 11" indoor-outdoor paging / talkback horn. Features include a built-in 70/25 volt transformer with switch selectable power taps and 8 ohm direct hook-up.

The HS-12T is equipped with a swivel bracket and a tough, tan color ABS plastic case.

PAGING HORNS



HS-17T

Diameter 7-1/2 inch
Impedance 8 ohm direct or 70/25V
Power (70/25V) 16 / 8 watts
Freq. Response 350 Hz - 14 KHz
SPL 120 db 1 W / 1 m
25 V Power taps 0.5, 1, 2, 4, 8 W
70 V Power taps 1, 2, 4, 8, 16 W

\$49.31 Each

7-1/2" ABS plastic 16 watt 70/25V paging horn.

The HS-17T is a weatherproof 7-1/2" indoor-outdoor paging / talkback horn. Features include a built-in 70/25 volt transformer with switch selectable power taps and 8 ohm direct hook-up.

The HS-17T comes equipped with a swivel bracket and a tough, tan colored ABS plastic case.

ELECTRONIC SIREN WITH YELP



SS-86

Each \$45.14

5" x 8" Yelp / Steady electronic siren.

The SS-86 is a heavy duty weatherproof 5" x 8" DC powered siren in a white ABS plastic housing. Features two siren modes: yelp or a high pitched steady tone.

Ideal for outdoor or marine applications.

Equipped with pivoting bracket that opens to 90°.



McBRIDE VANDAL RESISTANT CAGES



Height . . . Depth 15" Color.....Black

Each \$51.52



SMC-1

HC-1

Each	\$51.52
Color	White
Depth	5"
Width	15"
Height	15"

Designed to protect paging horns (HC-1) and surface mounted paging speakers (SMC-1) or other fixtures from damage due to impacts or vandalism. Ideal for schools, gymnasiums, arenas, heavy industrial areas or anywhere abuse must be anticipated.

Both cages are constructed from 1/8" diameter welded steel wire screen with 7/8" openings and 3/16" steel rod reinforcing hoops. All joints are fully welded for strength and durability.

Both cages are finished in a tough chip and rust resistant baked powdered epoxy.

Suitable for outdoor use.

EXTENSION LOUDSPEAKERS



WMS-50WB

Each	\$22.50
SPL	92 db
Voice Coil Dia	16 mm
Magnet Wt	3.8 oz
Res. Freq	300 Hz
Freq. Response	300 Hz - 8 KHz
Power	15 watts
Impedance	8 ohm
Size (inches)	. 4" h x 4" w x 2" d

Marine 2-way radio extension speaker.

The MG WMS-50WB is a 3" water resistant mylar cone speaker in a white high impact ABS plastic case that may be wall or bracket mounted. The water resistant design makes the WMS-50WB ideal for marine or outdoor applications.

Supplied with swivel bracket, wall mounting template and mounting hardware.



CS-4

Size (inches) 2" h x 4.6" w x	2.6" d
Impedance	8 ohm
Power	3 watts
Freq. Response 100 Hz - 1	0 KHz
Res. Freq	100 Hz
Magnet Wt	2.5 oz
Voice Coil Dia	14 mm
SPL	. 92 db

Each \$20.50

Low profile weather resistant 2-way radio / cell phone extension speaker.

The MG CS-4 is a 1-1/2" x 3" inch weather and dust resistant treated paper cone speaker in a black high impact ABS plastic case. The CS-4 works with any 2-way radio or cellular phone.

Includes 6 foot cord with 3.5 mm plug, swivel bracket and mounting hardware.



CS-2

Each \$21.49

Deluxe 2-way radio / cell phone extension speaker.

The MG CS-2 is a 3-1/2 inch weather and dust resistant treated paper cone speaker in a black high impact ABS plastic case. The CS-2 works with any 2-way radio or cellular phone.

Includes 5 foot cord with 3.5 mm plug, swivel bracket and mounting hardware.



FS-4H

Each \$22.09

Low profile speaker with 6" square grill.

The MG FS-4H is specially designed for installs where depth behind the loudspeaker is at a premium. The flat 4" square honeycomb construction cone is weather resistant and will not absorb moisture.

White ABS plastic grill included.



PS200

Diameter 8 inches
Depth 10 inches
Impedance8 ohm
Power
Freq. Response 100 Hz - 18 KHz
Magnet Wt 10 oz
Voice Coil Dia 25 mm
SPL
Color Beige

Each \$94.10

Omnidirectional outdoor speaker.

The MG PS200 is an outdoor extension speaker with a 360° sound dispersion pattern. The PS200 employs a 6-1/2" weatherproof fullrange speaker housed in a rugged ABS plastic case with sound diffuser baffle.

Complete with mounting bracket, hardware and instructions.

EXTENSION LOUDSPEAKERS



SB100

Size (inches) 7.5" h x 4.5" w x 4.5" d
Impedance6 ohm
Power
Freq. Response 55 Hz - 22 KHz
Woofer 4" paper cone
Midrange 2" paper cone
Tweeter 1/2" dome
SPL 91 db

Pair \$87.84

3-way shielded mini system.

The MG SB100 is a 3-way mini system with shielded speaker magnets. Ideal for computers or surround sound systems. Die cast metal enclosure with a durable crinkle black finish and perforated metal grill. Sold in pairs.

Adjustable mounting brackets, hook-up wire and hardware included.



SB200B (black) SB200W (white)

Size (inches) 7.4" h x 4.6" w x 4.6" d
Impedance8 ohm
Power
Freq. Response 90 Hz - 20 KHz
Woofer 4" poly cone
Midrange 2" poly cone
Tweeter 3/4" mylar dome
SPL 85 db

Pair \$59.16

3-way indoor/outdoor mini system.

The MG SB200 is a weather resistant 3-way mini speaker system housed in a rugged ABS plastic case. System consists of a 4" woofer; 2" midrange and 3/4" tweeter.

Available in black (SB200B) or white (SB200W). Sold in Pairs.

Adjustable mounting brackets, hook-up wire and hardware included.



SB100TBP (black) SB100TWP (white)

Pair \$136.93

2-way ported mini system with built-in 70/25V transformer.

The MG SB100TBP (black) and SB100TWP (white) are weatherproof 2-way ported mini systems with both 8 ohm and 70/25V inputs. Tap selector switch on rear of enclosure. Rugged ABS plastic case. Sold in pairs.

Adjustable mounting brackets, hook-up wire and hardware included.



SB150B (black) SB150W (white)

Size (inches) 8" h x 5.5" w x 4.5" d
Impedance8 ohm
Power
Freq. Response 70 Hz - 20 KHz
Woofer 5" poly cone
Tweeter 3/4" mylar dome
SPL

Pair \$149.14

Professional 2-way mini speaker system.

The MG SB150 is a top quality weatherproof 2-way mini speaker system housed in a rugged high impact polypropylene composite black plastic case. Available in 8 ohm only. Sold in pairs.

Adjustable mounting brackets, hook-up wire and hardware included.



ATS360B (brown) ATS360G (green)

Overall Size	16" h x 11" dia.
Impedance	8 ohm
Speaker	8" fullrange
Power	25 watts
Freq. Response	70 Hz - 8 KHz
SPL	93 db
Enclosure Matl	Polyethylene
Connections	3/4" conduit v 2

Each \$227.29

In-ground landscape mushroom speaker.

The MISCO ATS-360 is a wide coverage, low visibility, waterproof landscape extension speaker designed for direct burial in gardens etc.

Provides a 360° music source that blends into the landscape.

Available in foliage green (ATS-360G) or bard brown (ATS-360B).

EXTENSION LOUDSPEAKERS



WPS-80

Overall Size 14" Dia x 10.25" D
Height 15.5" with bracket
Impedance8 ohm
Power
Freq. Response 50 Hz - 18 KHz
SPL 93 db
Mounting "U" bracket
Available Colors white, gray or tan

Each \$127.37

Waterproof extension speaker.

The MISCO WPS-80 is a waterproof extension speaker for difficult environments. A JC80WP waterproof 8 inch co-axial speaker provides high reliability and superior sound quality. The molded hemispherical enclosure reduces serious resonances.

Available in white, gray or tan.

McBride MCB10

MCB10 PRO SOUND SYSTEM

The McBride MCB10 is a high performance professional and commercial sound 2-way loudspeaker system designed for pro sound reinforcement, public address, night club, house of worship, disk jockey and arena applications.

Specifications: Power......200 Wrms / 300 W peak

Directo.
HFPiezo Horn
LF10" (254 mm)
Enclosure StyleTrapezoid
Freq. Response60 Hz - 23 KHz
Sensitivity98 db (1 W / 1 m)
Dispersion40° Vert. x 100° Horz.
Crossover Point1.8 KHz
Impedance8 Ohms
Input Connectors 2 x 1/4" acks
Pole SocketYes (1-3/8" diameter)
Dimensions:
Height20.625" (524 mm)
Width Front14.25" (362 mm)
Width Rear8.5" (216 mm)
Depth12.75" (324 mm)
Enclosure Matl3/4" MDF
Grill20 ga. Perf. Steel



Design Features Include:

FinishBlack Texturelac Weight35.5 Lbs. (16.12 kg)

- High efficiency drivers and low loss crossover make the most of every watt from your amplifier.
- Superior projection and high speech intelligibility.
- · Built in pole / stand socket.

Each \$250.00

- High output without distortion for accurate sound reproduction.
- Rigid design and high density materials prevent bass robbing enclosure vibrations.
- Dual 1/4" parallel inputs on recessed steel dish.
- Tough Texturelac finish and full size steel grill to withstand abuse and rough handling.



1228/16

REPLACEMENT DIAPHRAGM ASSEMBLIES

\$182.16 ea.

Please call for diaphragms not listed or if you have any questions.

Some diaphragms are interchangeable with drivers from other manufactures and we also have access to other diaphragms not listed here. Q-Components stocks all the replacement voice coil diaphragms listed here.

> Audax, Eminence, Sammi, MG and Foster are original factory replacement parts. JBL and Altec replacement diaphragms are manufactured by Radian.

Diaphragm Part	No. Diaphragm for driver	Price
<u>AUDA</u>	<u>X</u>	
RW025A0*	TW025A0, TW025A1, TW025K3, TW025L0, TW025L1, TW025M0, TW025M1, AW025M1	\$11.37 ea
RW025A2/4*	Same as above but 4 ohm.	\$11.54 ea
RW025S1	AW025S1	\$21.60 e
RW025S3	AW025S3	\$20.90 e
RW034X0	TW034X0	\$21.37 e
	35° terminal placement when ordering.	
EMINEN	NCE	
MD2001RD-8	02007S, 02001, MD2001, MD2001S. Type 1 compression drivers. 8 ohm.	\$45.53 e
MD2001RD-16	Same as above. Type 1 compression drivers. 16 ohm.	\$45.53 e
PSD2002RD-8	02117, 02058, PSD2002, PSD2002S. Type 2 compression drivers. 8 ohm	\$45.53 e
PSD2002RD-16	Same as above. Type 2 compression drivers. 16 ohm.	\$45.53 e
PSD3003RD-8	PSD3003 2" throat compression driver. 8 ohm.	\$124.19 e
PSD3003RD-16	Same as above. 16 ohm.	\$124.19 e
HFVC** **Please call bef	HF-200A, HF-200BR, HF-250 pro tweeters. 8 ohm. ore ordering to ensure correct version. There are two versions. Both are rep	\$32.45 e laceable.
MG		
VCABT-1	BT-1, BT-2 bullet tweeters. 8 ohm.	\$6.73 e
VCABT-3	BT-3 bullet tweeter. 8 ohm.	\$16.74 e
VCAHM100	HM100 midrange horn. 8 ohm.	\$8.42 e
D.4.05.05		400.00
DA2505	025N27 horn twt, 025N30 4"x10" horn twt, 025N47 bullet twt. 8 ohm.	\$20.92 e
N08	H025N08 6" x 7" horn tweeter. 8 ohm.	\$41.18 e
1225/8	LE85, 376, 2416, 2420, 2421, 2425, 2426, 2427, 2470. 8 ohm.	\$182.16 e
1225/16	Same as above. 16 ohm.	\$182.16 e
1245/16	375H, 2440, 2441, 2445, 2450. 16 ohm.	\$200.64 e
1282/16	2482, 2485. 16 ohm.	\$256.08 e
1228/8	604, 802, 806, 808, 902. 8 ohm.	\$182.16 e
1000/10		

Same as above. 16 ohm.

EMINENCE px SERIES CROSSOVERS

EMINENCE

px crossovers

Designed to work in high-power cabinets, px crossovers are technically superior passive filters. Available as board only or complete with fitted hardware for a smart, economical "factory-fit" finish.


Designed and built for Eminence by the renowned Winslow Industries, **px** crossovers feature advanced circuit design to both preserve the crossover and your HF drivers. A common crossover problem is L-pad failure brought about by winding burnout when maximum attenuation is prolonged.


Full attenuation concentrates the maximum voltage drop in a small winding area – a potentially damaging state even with high-power L-pad devices. With **px** cabinet ready crossovers current is limited when the **HF level** control is set to "0" on its scale (max. -9 db attenuation). A secondary benefit of the design is to form a voltage divider across the HF driver.

The **High-Pass Protection** uses custom-built aerospace lamps as positive temperature coefficient series varistors. The tungsten filaments effectively track the program material, dynamically maintaining a safe maximum current level to the HF driver without introducing distortion. This circuitry provides smooth 3:1 analog compression during input overload conditions over 250 Wrms. At full drive levels approaching clipping, the electrical attenuation to the protected HF driver is -4.5 db.

In every way, Eminence **px** crossovers are a technically superior product.

PX-iii3K5 cabinet ready type.





PX-Biii5K0 board only type.

Part No.	Description	Crossover Frequencies Hz.	lmp. ohms	Watts RMS	Slope Low	Per Mid	Octave Hi	Price each
EMINENCE CROSSOVERS - Board only types.								
PX-B250	Subwoofer crossover	250	8	600	12	-	-	\$54.85 ea.
PX-B500	Subwoofer crossover	500	8	600	12	-	-	\$54.85 ea.
PX-B1K6	High pass crossover	1,600	8	400	-	-	18	\$37.92 ea.
PX-B3K5	High pass crossover	3,500	8	400	-	-	18	\$30.63 ea.
PX-B5K0	High pass crossover	5,000	8	400	-	-	18	\$30.26 ea.
PX-Bii500	2-way crossover	500	8	400	12	-	18	\$58.28 ea.
PX-Bii800	2-way crossover	800	8	400	12	-	18	\$54.85 ea.
PX-Bii1K6	2-way crossover	1,600	8	400	12	-	18	\$49.87 ea.
PX-Bii3K5	2-way crossover	3,500	8	400	12	-	18	\$58.19 ea.
PX-Bii5K0	2-way crossover	5,000	8	400	12	-	18	\$58.19 ea.
PX-Biii1K6	3-way crossover	500 / 1,600	8	400	12	6	18	\$89.83 ea.
PX-Biii3K5	3-way crossover	500 / 3,500	8	400	12	6	18	\$81.48 ea.
PX-Biii5K0	3-way crossover	500 / 5,000	8	400	12	6	18	\$96.92 ea.
EMINENCE (CROSSOVERS - Cabine	et ready types.						
PX-I250	Subwoofer crossover	250	8	600	12	-	-	\$135.64 ea.
PX-II1K6	2-way crossover	1,600	8	400	12	-	18	\$174.12 ea.
PX-II3K5	2-way crossover	3,500	8	400	12	-	18	\$159.26 ea.
PX-II5K0	2-way crossover	5,000	8	400	12	-	18	\$179.22 ea.
PX-III1K6	3-way crossover	500 / 1,600	8	400	12	6	18	\$232.92 ea.
PX-III3K5	3-way crossover	500 / 3,500	8	400	12	6	18	\$218.61 ea.
PX-III5K0	3-way crossover	500 / 5,000	8	400	12	6	18	\$213.58 ea.

READY MADE CROSSOVERS









ADF6/5SP

M738A

MCX352-10

We carry a very large selection of ready made crossovers for just about every application.
All crossovers are constructed with high quality components and assembled on heavy duty fiberglass

P.C. boards with a minimal amount of copper removed for excellent conductivity. Excellent for replacements, upgrading or for the home builder. Also suitable for car audio applications.

Model number	Description	Crossover frequencies (Hz)	Imp. (ohms)	Watts (rms/peak)	Slope low	per mid	octave hi	Price each
AMITRON CI	ROSSOVERS							
AM2W12	2-way high power	2,100	8	150 / 300	6	-	12	\$21.01 ea.
AM3W12	3-way high power	550 / 5,000	8	150 / 300	12	6	12	\$34.72 ea.
AM3W18	3-way high power,	600 / 5,000	8	200 / 375	12	18	12	\$52.15 ea.
AMSUB 2	2 channel sub + 2 sate	llites 110	8	180 / 300	6		6	\$65.59 ea.
AMSUB 4	as above with selectable crossover frequency	le 120 or 240	8	200 / 375	6	-	6	\$95.46 ea.
PHILIPS CRO	OSSOVERS							
ADF2000/8	2-way medium power	2,000	8	50 / 100	6	-	12	\$11.39 ea.
ADF2400/8	2-way medium power	2,400	8	50 / 100	6	-	6	\$12.30 ea.
ADF3000/8	2-way medium power	3,000	8	50 / 100	6	-	12	\$13.30 ea.
ADF6/5SP	3-way medium power	600 / 5,000	8	100 / 200	6	6	12	\$32.14 ea.
ADF7/3SP	3-way medium power	700 / 3,000	8	100 / 200	6	12	12	\$32.14 ea.
ADF3WXSP	3-way high power	360 / 4,200	8	150 / 300	6	12	18	\$56.35 ea.
ADF4WXSP	4-way high power	250 / 2,000 / 6,000	8 (150 / 300	12	12	12	\$52.54 ea.
ADFSUB 1	1 channel sub + 1 sate	llite 120	8	100 / 200	6	-	6	\$34.01 ea.
MARSLAND	CROSSOVERS							
M723A	2-way medium power	2,000	8	60 / 120	6	-	6	\$14.59 ea.
M713A	3-way medium power	600 / 5,000	8	60 / 120	6	6	12	\$26.32 ea.
M738A	3-way high power	600 / 5,000	8	100 / 200	6	6	12	\$26.66 ea.
MCX SERIES CROSSOVERS (See note below)								
MCX352-10	2-way very high power	1,000	See note	350 / 600	12	-	12	\$50.51 ea.
MCX352-25	2-way very high power	2,500	See note	350 / 600	12	-	12	\$44.15 ea.
MCX353-85	3-way very high power	800 / 5,000	See note	350 / 600	12	12	12	\$78.79 ea.

NOTE: All MCX crossovers are designed with **8 ohm low pass** and **16 ohm mid and high pass** sections. MCX crossovers are designed for high output home and pro sound applications. Use high power compression drivers (most of which are 16 ohm) or pairs of 8 ohm midranges and tweeters wired in series to ensure high power handling and SPL output required in these applications. Failure to properly load any passive crossover will result in distortion at best and increases the likelihood of midrange and tweeter burn-out.


Building custom crossovers or need parts for repair?

See our selection of caps, coils and resistors on pages 101 and 102.

Crossover design tables on pages 103 and 104.



BINDING POSTS & TERMINAL CUPS



Give a professional finish to your new enclosures with one of our terminal cups. Terminal cups with binding posts feature industry standard 3/4" post spacing and accept up to 8 gauge wire. The post nuts employ a


TC30

molded-in brass threaded insert, not the all plastic nuts used on inferior posts and terminal cups. Spring loaded terminal cups accept up to 10 ga. wire. **Note:** Maximum panel thickness for TC01 is 7 mm.

TC31

Part No.	Description	Outside Dimensions	Hole Cut	Price
TC01	One pair 5-way binding posts. One red, one black.	*See note above	Drill 5.5 mm	\$2.75 pr.
TC05	Round spring loaded terminal cup.	75 mm dia.	49 mm dia.	\$0.80 ea.
TC07	Rectangular blank terminal cup. Molded ABS.	101.5 x 140.4 mm	79 x 118 mm	\$3.65 ea.
TC19	Square recessed terminal cup. Fits round hole.	79.5 x 79.5 mm	69 mm dia.	\$6.28 ea.
TC21	Recessed 4 post terminal cup with shorting straps.	96 x 122.5 mm	77 x 97 mm	\$6.98 ea.
TC27	Rectangular recessed terminal cup.	92.5 x 79 mm	75 x 56 mm	\$3.00 ea.
TC30	Subwoofer terminal cup. Sub inputs & satellite output	ts. 98.5 x 138 mm	78 x 118 mm	\$3.13 ea.
TC31	Steel recessed dual 1/4 jack dish.	102 x 113 mm	78 x 88 mm	\$3.30 ea.

SPEAKER WIRE





D12/4

Our 10 and 12 gauge "Superflex" audio cable will improve system resolution, minimize line loss and is a must to get the most out of high power systems. For low to mid power systems our 14 and 16 gauge wire is ideal.

Digiflex speaker cable has 4 stranded copper conductors in a tough super flexible black jacket. For bi-amping and 4-pole Neutrik Speakon connectors.

EPC8 has eight 13 gauge stranded copper conductors in tough super flexible black jacket. For use with 8-pole Neutrik Speakon connectors and building speaker snake cables.

Part No.	Description	Price
MC10GA	10 ga. 2 cond. 413 strand x 36 ga. Superflex clear jacket.	\$0.97 ft.
MC12GA	12 ga. 2 cond. 259 strands x 36 ga. Superflex clear jacket.	\$0.82 ft.
MC14GA	14 ga. 2 cond. 41 strands x 30 ga. clear jacket.	\$0.38 ft.
MC16GA	16 ga. 2 cond. 26 strands x 30 ga. clear jacket.	\$0.27 ft.
D14/4	Digiflex 4 cond. 14 ga. stranded speaker cable.	\$0.85 ft.
D12/4	Digiflex 4 cond. 12 ga. stranded speaker cable.	\$1.36 ft.
EPC8	8 cond. 13 ga. stranded speaker cable. Black jacket.	\$1.75 ft.

MICROPHONE AND GUITAR CABLE





MIC-2: Super flexible microphone cable. 2 x 22 gauge stranded conductors with 96% coverage tinned copper braided shield. Twin cotton braids for strength.

Soundflex BR-20: Highest quality super flexible instrument cable. Ideal for all electric instruments. 20 gauge OFC center conductor (41 gauge x 36 strand) in special polyethylene dielectric. 95% coverage braided copper outer shield.

Part No	. Description	Price
MIC-2	Super flexible microphone cable. 6.5 mm O.D. Color: Black	\$0.55 ft.
BR-20	Soundflex instrument cable. 6.2 mm O.D. Color: Black	\$0.55 ft.

WCBAN MCPIN MCLUG

GOLD PLATED AUDIO CONNECTORS


Part No. Description Price **MCBAN** One piece gold plated banana plug for use with binding posts. \$2.40 pr. **MCPIN** One piece gold plated pin for use with spring loaded terminals. \$1.40 pr. **MCLUG** One piece gold plated spade lug for use with screw terminals. \$1.40 pr. MCBAN-2 Gold plated dual banana plug for use with binding posts. \$3.85 ea.




MCBAN-2 (See price above)

Here probably is the neatest and easiest way to connect your wires to your terminal cups, our gold plated dual banana plug. The side entry screw lug terminal means there's no soldering involved. It even accepts up to 8 gauge wire and it's stackable which means you can plug another banana plug into the back of it. Industry standard 3/4" pin centers.

CRIMP-ON CONNECTORS



MCD110





Don't like to solder? Well, here's your answer. These crimp-on quick disconnects come in two different sizes. The MC110 is for the 0.110" wide terminals found on many tweeters and the MC205 is for the 0.205" wide terminals found on mids, woofers and crossovers. Sold in packs of 20 each.

Part No.	Wire Size	Terminal Size	Price
MCD110 (20 pack)	14-16 ga.	0.110" x .020"	\$3.00 pk.
MCD205 (20 pack)	14-16 ga.	0.205" x .020"	\$4.55 pk.




SWITCHCRAFT PLUGS, JACKS & XLR's

Genuine **SWITCHCRAFT** connectors. Famous the world over for top quality and rugged reliability.

	Part No.	Description	Price
A.	SW11	2 conductor 1/4" jack open circuit.	\$2.27 ea.
В.	SW280 2	conductor 1/4" plug. Metal barrel. Industry standard.	\$2.46 ea.
C.	SW184L	As above with large barrel for heavy gauge wire.	\$6.84 ea.
D.	SW226	2 conductor right angle 1/4" plug. Metal barrel.	\$6.41 ea.
E.	SWA3F	3 pin female XLR connector.	\$4.42 ea.
F.	SWA3FB	3 pin female XLR connector. Black finish.	\$4.42 ea.
G.	SWA3M	3 pin male XLR connector.	\$4.05 ea.
Н.	SWA3MB	3 pin male XLR connector. Black finish.	\$4.05 ea.
i.	SWD3F	3 pin female XLR panel mount connector.	\$6.62 ea.
J.	SWD3M	3 pin male XLR panel mount connector.	\$5.94 ea.

NEUTRIK SPEAKON SPEAKER CONNECTORS



Part No.	Description	Price	
NL2FC	Neutrik Speakon 2 pole plug.	\$2.81 ea	ì.
NL2MP	Neutrik Speakon 2 pole chassis/enclosure jack.	\$3.92 ea	ì.
NL4FC	Neutrik Speakon 4 pole plug.	\$6.97 ea	ì.
NL4MPR	Neutrik Speakon 4 pole enclosure jack.	\$4.12 ea	ì.
NL8FC	Neutrik Speakon 8 pole plug.	\$13.52 ea	ì.
NL8MPR	Neutrik Speakon 8 pole enclosure jack.	\$9.50 ea	ì.

ENCLOSURE PORT TUBES

Gives your new vented enclosures a clean, professional, finished appearance. These tubes are constructed of molded ABS with internal diameters of 2", 3" and 4" by 5" long (the 2" ID tube is 4" long). Easily cut to desired length. The oversize lip on the front will hide even the nastiest cut-out.

Part No.	Surface Area	Length	Inside Dia.	Flange Dia.	Mtg. Hole	Price Each
PT2X4	3.142 sqin.	4"	2"	2.8"	2-1/16"	\$1.39
PT3X5	7.069 sqin.	5"	3"	3.8"	3-1/16"	\$1.57
PT4X5	12.566 sqin.	. 5"	4"	4.8"	4-1/16"	\$1.69

ADJUSTABLE LENGTH PORT TUBES

Adjustable length port tubes are great for adjusting the tuning of vented enclosures. These tubes allow you to easily change the port tuning to suit your taste and preference.

Made extra long for boxes requiring a low tuning frequency. Constructed of tough molded ABS plastic.

Part No.	Surface Area	Length	Inside Dia.	Flange Dia.	Hole Cut	
APT66	5.309 sqin.	5.2" to 10.0"	2.6"	3.75"	3-1/16"	\$3.75
APT110	14.730 sqin.	6.0" to 11.25"	4.33"	5.73"	4.9"	\$7.50










2.50"

3 35

STACKING CABINET CORNERS



2.50"


Φ

SPC-1: Small black plastic stacking corner. Ideal for small to medium size enclosures and cabinets. 0.35" inside corner radius.

LPC-1: Large black plastic stacking corner. Ideal for use on large enclosures and cases. 0.51" inside corner radius.

Part No.	Description	Price		
SPC-1	Small black plastic stacking corner.	\$0.72 ea.		
LPC-1	Large black plastic stacking corner.	\$1.01 ea.		

STEEL CABINET BALL CORNERS



BC-2L

BC-3LS

BC-3L

Industry standard heavy duty steel ball corners. Tough 14 gauge steel will withstand a life time of abuse. Bright zinc plated.

BC-2L: 2 legs for speaker enclosure fronts. BC-3LS: 3 legs. Features a stacking dimple. Mates with BC-3L and BC-2L.

BC-3L: 3 leg for regular corners.

ENCLOSURE POLE MOUNTS

Description	Price
Steel 2 leg corner	\$2.12 ea.
Stacking Steel 3 leg corner	\$2.21 ea.
Steel 3 leg corner	\$2.12 ea.

0.75 2.50"-79 5 13 **SM35 SM38**


0.75'

BC-2L

4 mtg holes Ø 5.5 / .22 (coursetoned 2.0 / .31)

SH-1

RH-1



I mig holes @ 5.5 / .22

PH-1

High quality enclosure pole mount sockets designed for rugged use. Produced from top engineered resin for high strength and durability. Available for 1-3/8" or 1-1/2" industry standard pole diameters. Color: Black.

Part No.	Description	Price
SM35	Speaker pole mount. 1-3/8" (35 mm) opening.	\$6.75 ea.
SM38	Speaker pole mount. 1-1/2" (38 mm) opening.	\$6.75 ea.

ENCLOSURE HANDLES

RH-1: Medium size recessed enclosure handle. All steel construction with a reinforced steel bar handle. Durable black finish. For large enclosures.

PH-1: Injection molded black plastic pocket handle. Saves weight and is easy to install. For small to medium size enclosures.

SH-1: Black plastic strap handle with spring steel insert. Chrome end caps.


Part No.	Description	Price
RH-1	8.69" x 6.38" steel recessed cabinet handle.	\$8.18 ea.
PH-1	3.48" x 5.33" molded plastic pocket handle.	\$2.24 ea.
SH-1	10-1/2" black strap handle chrome end caps.	\$2.81 ea.



OZITE™ ENCLOSURE CARPET COVERING

Take your pick of either black or grey. The same heavy duty carpet covering that the pro-sound industry uses. Tough and durable like nothing else.

Part No.	Color	Description	Price / yard
BOZ-1	Black	72" wide Ozite carpet covering.	\$10.07
GOZ-1	Grey	72" wide Ozite carpet covering.	\$10.07





Heavy duty mesh grills constructed of 19 gauge steel and finished with a tough satin black enamel to withstand years of abuse. 5/16" square holes provide a total open area of 50%. Black rubber mounting gaskets ensure a tight, vibration free fit. Easily mounted with our GC-1 clamps, bolts and T-nuts. (See below.)

Part No.	Nominal speaker size	Outside diameter	Price
WG-5	5"	5-1/4"	\$1.74 ea.
WG-6	6"	6-1/4"	\$2.97 ea.
WG-6N	6-1/2"	6-1/2"	\$2.04 ea.
WG-8	8"	8-1/4"	\$2.58 ea.
WG10	10"	10-1/4"	\$3.63 ea.
WG-12	12"	12-1/4"	\$4.23 ea.
WG-15	15"	15-1/4"	\$5.91 ea.
WG-18	18"	18-1/8"	\$10.02 ea.



SC-1: Front mount speaker clamp. Die cast zinc construction. Black zinc chromate finish.

GC-1: Formed steel speaker grill clamp. Tough black enamel finish.

Bolts and T-Nuts: For use with clamps or speaker mounting. Black oxide plated.

Part No.	Description	Price
SC-1	Heavy duty front mount speaker clamp.	\$0.84 ea.
GC-1	Heavy duty angle style speaker grill clamp.	\$0.57 ea.
Bolt-14	1/4" x 20 x 1.25" truss head bolt. Robertson drive.	\$0.12 ea.
T-Nut-14	1/4" x 20 steel T-nut for above. 0.56" long.	\$0.12 ea.
Bolt-10	#10 x 32 x 1.25" truss head bolt. Robertson drive.	\$0.12 ea.
T-Nut-10	#10 x 32 steel T-nut for above. 0.56" long.	\$0.12 ea.

GC-1

BOLT & T-NUT



SC-1



ENCLOSURE SPIKES

By installing spikes on the bottom of your loudspeaker enclosures you can effectively uncouple them from the floor and walls. This prevents the walls and the floors from resonating in sympathy with the loudspeakers. The result is increased clarity, detail and sonic realism. Each spike comes complete with a knock-in insert. lock nut and a threaded spike for carpet and threaded rubber foot for hardwood or tile floors.


Part No.	Description	Price	
Spike	Spike, rubber foot, lock nut, insert.	\$1.12 ea.	

GRILL FRAME ATTACHMENT PINS

Bet you've been looking for these things. Grill pins are those little ball and cup fasteners used for removable grills on speaker enclosures. By installing the cup on your baffle board and the ball in the grill frame you can surface mount the grill to the enclosure and still remove it whenever you wish.

Grill pins are sold singly as a set (1 cup + 1 ball = 1 grill pin).

Part No.	Description	Price
Grill Pin	1 set ball and cup grill attachment fastener.	\$0.25 set.



MD4623

SF7005

SF8024


SF8066

GENUINE MELLOTONE® GRILL CLOTH

Part No	o. Color and texture	Width	Price
			per Yard
CK2003	Black double knit stretch.	32"	\$12.98
CK2004	Medium brown double knit stretch.	32"	\$12.98
CK2005	White double knit stretch.	32"	\$12.98
CK2006	Dark grey double knit stretch.	32"	\$12.98
CK2007	Grey double knit stretch.	32"	\$12.98
CK2008	Rose double knit stretch.	32"	\$12.98
CK DOU	BLE WIDE Any above.	64"	\$24.58
DF6000	Black on black poly strand.	36"	\$18.04
DF6001	White on white poly strand w/ clear mylar accent.	36"	\$18.04
DF6002	Light brown on brown poly strand.	36"	\$18.04
DF6003	White on light brown poly strand.	36"	\$18.04
DF6004	Brown on black poly strand.	36"	\$18.04
DF6005	Light brown poly strand w/ gold mylar accent.	36"	\$18.04
DF6222	Grey on black poly strand.	36"	\$18.04
DF7002	White on white poly strand.	36"	\$18.04
DF7012	Brown on dark brown poly strand.	36"	\$18.04
DF7022	White on light beige poly strand.	36"	\$18.04
DF8014	Wide brown on brown poly strand.	36"	\$18.04
DF8027	Wide black on black poly strand.	36"	\$18.04
DF DOUB	BLE WIDE Any above.	72"	\$34.34
MD4241	Wide black / brown on black poly strand.	32"	\$19.15
MD4274	Medium weight black on black poly strand.	32"	\$19.15
MD4327	Wide brown / gold on dark brown poly strand w/ gold fleck.	32"	\$19.15
MD4522	Medium weight dark golden brown on black poly strand.	32"	\$19.15
MD4623	Mottled dark brown / bronze.	32"	\$19.15
MD DOU	BLE WIDE Any Above.	64"	\$35.70
SF7005	Silver mylar on white and black poly strand.	36"	\$27.81
SF8024	Silver mylar on white and black poly strand w/ blue accent.	36"	\$27.81
SF8055	Black heavy weave.	36"	\$27.81
SF8066	Brown heavy weave.	36"	\$27.81
SF DOUE	BLE WIDE Any above.	72"	\$52.87

Please Note:

Other types, weave styles and colors are available by special order. Minimum special order quantity is 25 yards per type. Please call for details.



Features include

10 watt power rating. 5% tolerance. Non-inductive design. Axial tinned leads. Ceramic case.

WIRE WOUND POWER RESISTORS

High quality resistors ideal for building L-Pads, notch filters and impedance equalization circuits. 10 watt power rating.

Tight 5% tolerance and non-inductive construction ensure top performance.

Each	\$	0.56			
Part No.	Ohms	Part No.	Ohms	Part No.	Ohms
MCR05	0.5	MCR303	3.3	MCR10	10.0
MCR082	0.82	MCR4	4.0	MCR13	13.0
MCR1	1.0	MCR407	4.7	MCR15	15.0
MCR104	1.4	MCR506	5.6	MCR20	20.0
MCR108	1.8	MCR608	6.8	MCR47	47.0
MCR2	2.0	MCR705	7.5		
MCR207	2.7	MCR806	8.6	Ţ	





Features include

Non polarized.

Non inductive wound construction.

Rubber end seals.

Low dissipation factor.

10% tolerance.

100 volt DC rating.

Effective to 250 watts.

ELECTROLYTIC CAPACITORS

Part No.	Value F	rice ea.	1	Part No.	Value	Price ea.
MCC1E	1.0 uF	\$0.59		MCC16E	16.0 uF	\$1.26
MCC202E	2.2 uF	\$0.59		MCC20E	20.0 uF	\$1.32
MCC3E	3.0 uF	\$0.59		MCC22E	22.0 uF	\$1.32
MCC303E	3.3 uF	\$0.64		MCC33E	33.0 uF	\$1.44
MCC4E	4.0 uF	\$0.68		MCC47E	47.0 uF	\$1.72
MCC407E	4.7 uF	\$0.68		MCC50E	50.0 uF	\$1.72
MCC506E	5.6 uF	\$0.78		MCC65E	65.0 uF	\$2.04
MCC6E	6.0 uF	\$0.78		MCC75E	75.0 uF	\$2.17
MCC608E	6.8 uF	\$0.86		MCC80E	80.0 uF	\$2.08
MCC8E	8.0 uF	\$0.96		MCC100E	100.0 uF	\$3.43
MCC10E	10.0 uF	\$1.00		MCC125E	125.0 uF	\$3.40
MCC12E	12.0 uF	\$1.04		MCC150E	150.0 uF	\$3.79
MCC14E	14.0 uF	\$1.14		MCC250E	250.0 uF	\$4.66
MCC15E	15.0 uF	\$1.18		MCC375E	375.0 uF	\$8.12



Features include

Non polarized.

Non inductive wound construction.
Polyester film wrap.
Epoxy resin end seals.
Low dissipation factor.
10% tolerance.
250 volt DC rating.
Effective to 500 watts.

METALLIZED POLYESTER CAPACITORS

Part No.	Value F	Price ea.	1	Part No.	Value	Price ea.
MCC1PE	1.0 uF	\$1.26		MCC6PE	6.0 uF	\$3.48
MCC105PE	1.5 uF	\$1.62		MCC8PE	8.0 uF	\$4.84
MCC202PE	2.2 uF	\$1.99		MCC10PE	10.0 uF	\$5.20
MCC3PE	3.0 uF	\$2.17		MCC12PE	12.0 uF	\$5.47
MCC303PE	3.3 uF	\$2.71		MCC15PE	15.0 uF	\$7.45
MCC4PE	4.0 uF	\$2.76		MCC16PE	16.0 uF	\$8.12
MCC407PE	4.7 uF	\$2.80		MCC18PE	18.0 uF	\$8.45
MCC5PE	5.0 uF	\$3.04	J	MCC20PE	20.0 uF	\$11.06



Features include

10% tolerance.


Wound on plastic bobbins for a professional appearance.

High quality.

Tinned leads ready to solder.

Power Ratings

Air core - 180 watt RMS Ferrite core - 250 watt RMS



Features Include

15 gauge wire keeps resistance to a minimum.

High grade transformer steel laminate cores ensure against coil saturation.

Ideal for high power applications in home, professional and car audio.

Tinned leads ready to solder.

Power Rating

600 watt RMS

McBRIDE STANDARD INDUCTOR COILS

Part No.	Value	Power	AWG	Туре	Price ea.
MCL01	0.1 mH	180	20	Air Core	\$2.47
MCL02	0.2 mH	180	20	Air Core	\$2.71
MCL03	0.3 mH	180	20	Air Core	\$2.98
MCL04	0.4 mH	180	20	Air Core	\$3.36
MCL05	0.5 mH	180	20	Air Core	\$3.56
MCL06	0.6 mH	180	20	Air Core	\$3.82
MCL07	0.7 mH	180	20	Air Core	\$4.33
MCL08	0.8 mH	180	20	Air Core	\$4.40
MCL09	0.9 mH	180	20	Air Core	\$4.70
MCL1	1.0 mH	180	20	Air Core	\$4.98
MCL105	1.5 mH	180	20	Air Core	\$5.28
MCL2	2.0 mH	180	20	Air Core	\$5.63
MCL3	3.0 mH	250	18	Ferrite Core	\$10.94
MCL4	4.0 mH	250	18	Ferrite Core	\$11.00
MCL5	5.0 mH	250	18	Ferrite Core	\$12.38
MCL6	6.0 mH	250	18	Ferrite Core	\$13.10
MCL7	7.0 mH	250	18	Ferrite Core	\$13.81
MCL8	8.0 mH	250	18	Ferrite Core	\$14.52
MCL9	9.0 mH	250	18	Ferrite Core	\$14.39
MCL10	10.0 mH	250	18	Ferrite Core	\$15.98

McBRIDE HDL LOW DCR INDUCTORS


Our HDL heavy duty inductors use 15 gauge wire to keep resistance to a minimum. High grade transformer steel laminate cores ensure against coil saturation.


Ideal for all high power applications in home, professional and car audio. 600 watt RMS power rating.

Part No.	Value	DCR	Price ea.
HDL5	5 mH	0.28 ohm	\$21.16 ea.
HDL6	6 mH	0.30 ohm	\$21.53 ea.
HDL7	7 mH	0.34 ohm	\$22.94 ea.
HDL8	8 mH	0.36 ohm	\$24.10 ea.
HDL9	9 mH	0.39 ohm	\$25.90 ea.
HDL10	10 mH	0.41 ohm	\$26.03 ea.
HDL12	12 mH	0.46 ohm	\$28.22 ea.
HDL13	13 mH	0.50 ohm	\$29.89 ea.
HDL15	15 mH	0.53 ohm	\$31.88 ea.

CUSTOM VALUES AVAILABLE

Both our standard and HDL coils are available in custom values. Simply round the value you require up to the nearest value shown in the tables above, add \$1.00 to the price, and we will make it for you. Please inform us of the value you require when ordering.





ORDERING, SHIPPING AND WARRANTY INFORMATION

ORDERING INFORMATION

BUSINESS HOURS - Our sales office is open from 8 am to 5 pm EST, Monday through Friday. Mail-in orders and correspondence should be sent to: Q-Components, 638 Colby Dr., Waterloo, Ont. N2V 1A2. Fax orders can be sent anytime.

MINIMUM ORDER - Our minimum order is \$15.00 (merchandise value before shipping and taxes). Due to the high cost of processing small orders, there will be a \$2.00 service charge added to any order that falls below this minimum.

NON-STOCK ITEMS - We normally stock everything advertised in our catalog. If you require an item(s) not listed in our catalog and the quantity permits, we may have it available through our many domestic and overseas sources. We also stock many items that are not advertised in our catalog.

Please call us with your requirements.

PRICING - Large quantity pricing is available, call for quotations. Due to market fluctuations, prices may change without notice.

PAYMENT METHODS

C.O.D. - Cash on delivery orders are welcome.
Only cash or company cheques are accepted for
C.O.D. payments. We reserve the right to require
prepayment or "Cash Only" for C.O.D. payment at our
discretion. Sorry no personal cheques.

CHARGE CARDS - We accept Visa and Mastercard. Please have your card handy when calling. When ordering by fax or mail please provide your card number, the full name on the card and the card's expiry date. We require this information for security purposes. If authorization cannot be obtained for your card at time of shipment, you will need to make arrangements for an

alternate form of payment within one week of notification.

PREPAID - If you wish to prepay your order, please summit your order indicating prepayment and a phone or fax number where you can be reached during the day. As couriers do not accept freight collect shipments we will contact you with the total cost of your order including freight, GST and PST if applicable. At our discretion, prepaid orders may be held for up to 14 business days to clear non-certified cheques.

ONTARIO CUSTOMERS - We are required by law to collect the 8% provincial sales tax. Ontario businesses must submit a tax exemption certificate to avoid being charged PST.

RETURNED CHEQUES - There will be a \$20.00 returned cheque charge added to the face amount of **any cheque** returned to Q-Components, plus any legal fees incurred.

SHIPPING INFORMATION

SHIPPING TIME - All in-stock orders are shipped within 24 hours of receipt. Delivery times for orders shipped via UPS is 2-7 working days. Please provide us with your daytime phone number when ordering so that we can contact you regarding any delays or problems with your order.

SHIPPING METHODS - We ship via a number of different couriers depending on your location and the size of the shipment. Freight charges are prepaid by us and then added to your invoice. You may specify a courier at your option. If you have an account with a particular courier, provide us with your account number and we can ship collect.

All shipments are F.O.B. Waterloo, Ont.

IMPORTANT NOTES

RESTOCKING CHARGE - Any items ordered in error or returned to us for credit are subject to testing and a 15% restocking charge.

PARTIAL SHIPMENTS - Because we ship within 24 hours, it may occur that a line item(s) is out of stock and cannot be shipped with the rest of your order. If you prefer that your order is shipped complete and you are willing to waive the 24 hour shipping time, we will hold your order for no longer than 30 days for all merchandise to ship together. If we cannot ship within 30 days we will contact you for further instructions. Please indicate "No Partial Shipments" on your order for this option or inform our sales representative when phoning in your order.

WARRANTY INFORMATION

LIMITED WARRANTY - All products in this catalog, unless otherwise warranted in their description, are warranted only to be free of defects in material and workmanship for ninety (90) days from date of shipment. No purchase order or verbal advice shall alter this. Dissection or disassembly of any product for any reason automatically voids any and all warranties.

DISCLAIMER - There are no other warranties either express or implied which extend the foregoing, and there are no warranties of merchantability or fitness for a particular purpose. We are not responsible for incidental or consequential damage due to defective or improper use of products.

REMEDY - We will at our election and subject to availability, either replace any product we have sold with a defect in materials or workmanship, or issue a refund or credit for the purchase price plus applicable tax, providing you return such products to us, properly packaged and shipping prepaid, with a copy of your invoice and a explanation of the defect.

The foregoing shall be the exclusive remedy for defective or non-conforming merchandise.

Q-COMPONENTS

638 Colby Drive, Order Line: 1-800-363-6336 Waterloo, Ontario. Help Line: 1-519-884-1140 Fax Line: 1-519-884-0193







ORDERS ONLY: 1-800-363-6336

Help Line: 1-519-884-1140 Fax Line: 1-519-884-0193

Business Hours: Monday to Friday, 8 am to 5 pm EST

Q Components

638 Colby Drive, Waterloo, Ontario N2V 1A2 www.loudspeakers.ca

email: sales@loudspeakers.ca